**W3G630-DQ37-35**

# EC axial fan - HyBlade

sickle-shaped blades (S series)

with square full nozzle, for barn ventilation

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | |
|---|---|
| **Type** | **W3G630-DQ37-35** |
| **Motor** | **M3G112-GA** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 277 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ml |
| Speed (rpm) | $min^{-1}$ | 1000 |
| Power consumption | W | 720 |
| Current draw | A | 3.2 |
| Max. back pressure | Pa | 140 |
| Max. back pressure | inH2O | 0.56 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 60 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

## Data according to ErP Directive

| | | Actual | Req. 2015 |
|---|---|---|---|
| 01 Overall efficiency $\eta_{es}$ | % | 44.1 | 32.7 |
| 02 Measurement category | | A | |
| 03 Efficiency category | | Static | |
| 04 Efficiency grade N | | 51.4 | 40 |
| 05 Variable speed drive | | Yes | |

| | | |
|---|---|---|
| 09 Power consumption $P_{ed}$ | kW | 0.69 |
| 09 Air flow $q_v$ | $m^3/h$ | 8080 |
| 09 Pressure increase $p_{fs}$ | Pa | 124 |
| 10 Speed (rpm) n | $min^{-1}$ | 1005 |
| 11 Specific ratio* | | 1.00 |

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

LU-116825

# EC axial fan - HyBlade

sickle-shaped blades (S series)

with square full nozzle, for barn ventilation

## Technical description

| | |
|---|---|
| **Weight** | 22.5 kg |
| **Fan size** | 630 mm |
| **Rotor surface** | Painted black |
| **Electronics housing material** | Die-cast aluminum, painted black |
| **Blade material** | Press-fitted, painted sheet steel blank, sprayed with PP plastic |
| **Support ring material** | Steel, galvanized and coated with black plastic (RAL 9005) |
| **Fan housing material** | Sheet steel, galvanized and coated with black plastic (RAL 9005) |
| **Number of blades** | 5 |
| **Airflow direction** | "A" |
| **Direction of rotation** | Clockwise, viewed toward rotor |
| **Degree of protection** | IP54 |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | F4-2 |
| **Max. permitted ambient temp. for motor (transport/storage)** | +80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | -40 °C |
| **Installation position** | Shaft horizontal or rotor on top |
| **Condensation drainage holes** | On stator side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 10 mA<br>- Output 20 VDC, max. 50 mA<br>- Output for slave 0-10 V<br>- Operation and alarm display<br>- Selection of direction of rotation left/right<br>- Input for sensor 0-10 V or 4-20 mA<br>- External 24 V input (parameter setting)<br>- Alarm relay<br>- Integrated PID controller<br>- Power limiter<br>- Motor current limitation<br>- PFC, active<br>- RS-485 MODBUS-RTU<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Control interface with SELV potential safely disconnected from the mains<br>- Thermal overload protection for electronics/motor<br>- Line undervoltage / phase failure detection |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | <= 3.5 mA |
| **Electrical hookup** | Via terminal box |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 61800-5-1; CE |
| **Approval** | EAC |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

with square full nozzle, for barn ventilation

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "A" |
| 2 | Cable diameter min. 4 mm, max. 10 mm, tightening torque 4±0.6 Nm |
| 3 | Tightening torque 3.5±0.5 Nm |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

with square full nozzle, for barn ventilation

## Connection diagram




| No. | Conn. | Designation | Function/assignment |
|---|---|---|---|
| PE | - | PE | Protective earth terminal |
| KL1 | 1, 2 | N, L | Power supply 50/60 Hz |
| KL2 | 1 | NC | Floating status contact, break for failure |
| KL2 | 2 | COM | Floating status contact, changeover contact, common connection<br>(2 A, max. 250 VAC, min. 10 mA, AC1) |
| KL2 | 3 | NO | Floating status contact, make for failure |
| KL3 | 1 | OUT | Analog output, 0-10 VDC, max. 3 mA, SELV<br>output of current motor modulation level:<br>1 V corresponds to 10% modulation level.<br>10 V corresponds to 100% modulation level. |
| KL3 | 2, 8 | GND | Reference ground for control interface, SELV |
| KL3 | 3, 7 | 0-10 V | Control/current sensor value input 0-10 VDC, impedance 100 kΩ, use only as alternative to 4-20 mA input, SELV |
| KL3 | 4 | +10 V | Voltage output 10 VDC (+/- 3%), max. 10 mA,<br>power supply for ext. devices (e.g. potentiometer), SELV |
| KL3 | 5 | +20 V | Voltage output 20 VDC (+25%/-10%), max. 50 mA<br>power supply for ext. devices (e.g. sensors), SELV |
| KL3 | 6 | 4-20 mA | Control/current sensor value input 4-20 mA, impedance 100 Ω, use only as alternative to 0-10 V input, SELV |
| KL3 | 9, 11 | RSB | RS485 interface for MODBUS, RSB |
| KL3 | 10, 12 | RSA | RS485 interface for MODBUS, RSA |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

with square full nozzle, for barn ventilation

## Curves: Air performance 50 Hz




Measurement: LU-116825-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | f | n | $P_{ed}$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | qv | $p_{fs}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa | CFM | inH2O |
| 1 | 230 | 50 | 1000 | 462 | 2.11 | 65 | 71 | 71 | 12100 | 0 | 7120 | 0.00 |
| 2 | 230 | 50 | 1000 | 559 | 2.54 | 61 | 68 | 67 | 10750 | 50 | 6325 | 0.20 |
| 3 | 230 | 50 | 1000 | 653 | 2.94 | 62 | 69 | 68 | 9100 | 100 | 5355 | 0.40 |
| 4 | 230 | 50 | 1000 | 720 | 3.20 | 64 | 71 | 70 | 7595 | 140 | 4470 | 0.56 |
| 5 | 230 | 50 | 850 | 279 | 1.27 | 61 | 67 | 67 | 10230 | 0 | 6020 | 0.00 |
| 6 | 230 | 50 | 850 | 337 | 1.53 | 58 | 64 | 64 | 9085 | 36 | 5345 | 0.14 |
| 7 | 230 | 50 | 850 | 394 | 1.77 | 59 | 65 | 64 | 7685 | 72 | 4525 | 0.29 |
| 8 | 230 | 50 | 850 | 429 | 1.93 | 61 | 67 | 67 | 6415 | 100 | 3775 | 0.40 |
| 9 | 230 | 50 | 700 | 156 | 0.71 | 57 | 63 | 63 | 8420 | 0 | 4955 | 0.00 |
| 10 | 230 | 50 | 700 | 188 | 0.86 | 53 | 60 | 60 | 7480 | 24 | 4405 | 0.10 |
| 11 | 230 | 50 | 700 | 220 | 0.99 | 55 | 61 | 60 | 6330 | 49 | 3725 | 0.20 |
| 12 | 230 | 50 | 700 | 240 | 1.08 | 57 | 63 | 63 | 5280 | 68 | 3110 | 0.27 |
| 13 | 230 | 50 | 550 | 76 | 0.35 | 52 | 58 | 58 | 6615 | 0 | 3895 | 0.00 |
| 14 | 230 | 50 | 550 | 91 | 0.42 | 48 | 55 | 54 | 5880 | 15 | 3460 | 0.06 |
| 15 | 230 | 50 | 550 | 107 | 0.48 | 49 | 56 | 55 | 4975 | 30 | 2925 | 0.12 |
| 16 | 230 | 50 | 550 | 116 | 0.52 | 51 | 58 | 57 | 4150 | 42 | 2445 | 0.17 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_{ed}$ = Power consumption · I = Current draw · $LpA_{in}$ = Sound pressure level intake side · $LwA_{in}$ = Sound power level intake side
$LwA_{out}$ = Sound power level outlet side · qv = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com