

4412 F/2GP-187

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 4

3.1 Operating Data - Electrical Interface - Input 4
3.2 Electrical Operating Data 5
3.3 Operating Data - Electrical Interface -Output 6
3.4 Electrical Features 6
3.5 Aerodynamic 8
3.6 Sound Data 9

4 Environment 9

4.1 General 9
4.2 Climatic requirements*) 9

5 Safety 10

5.1 Electrical Safety 10
5.2 Approval Tests 10

1 General

Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	
Airflow direction	Air outlet over struts	
Bearing system	Sleeve bearing	
Mounting position	any	

2 Mechanics


2.1 General

Width	119,0 mm	
Height	119,0 mm	
Depth	25,4 mm	
Weight	0,175 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges Screw size	wire outlet corner: 40 Ncm remaining corners: 10 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires - Plug	
Length of lead wire Tolerance	265 mm +- 10,0 mm	
Wire gauge (AWG)	24	
Insulation diameter	1,55 mm	
Contact / Connector	see drawing	





	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	violet	PWM
Wire 4	white	Tacho

The auxilliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.

3 Operating Data


3.1 Operating Data - Electrical Interface - Input

Control input	PWM


Features

Inpute type	Open collector	
PWM - Frequency		2 kHz - 5 kHz

Characteristics



Schematics



3.2 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area should not be any solid obstruction within 0,5 m.

Δp = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

Name	Condition		
PWM 0001	PWM: 100 %;	f: 2 kHz	f: 5 kHz


Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	8,0 V		12,6 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 PWM 0001	P	2,6 W +- 17,5 %	6,5 W +- 25,0 %	6,6 W +- 25,0 %
Current consumption Tolerance	Δp = 0 PWM 0001	I	320 mA +- 17,5 %	540 mA +- 25,0 %	525 mA +- 25,0 %
Speed Tolerance	Δp = 0 PWM 0001	n	2.260 1/min +- 12,5 %	2.900 1/min +- 4,0 %	2.900 1/min +- 4,0 %
Starting current consumption				1.200 mA	

Name	Condition		
PWM 0002	PWM: 50 %;	f: 2 kHz	f: 5 kHz

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	8,0 V		12,6 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 PWM 0002	P	2,0 W +- 25,0 %	2,9 W +- 25,0 %	3,1 W +- 25,0 %
Current consumption Tolerance	Δp = 0 PWM 0002	I	255 mA +- 25,0 %	245 mA +- 25,0 %	245 mA +- 25,0 %
Speed Tolerance	Δp = 0 PWM 0002	n	1.940 1/min +- 4,0 %	1.940 1/min +- 4,0 %	1.940 1/min +- 4,0 %

3.3 Operating Data - Electrical Interface -Output

Tacho type	/2 (Open collector)




$$Ra = \frac{UBS - US\ Low}{I\ Sink}$$

Features	Note	Values
Tacho operating voltage (UBS)		<= 60 V
Tacho signal Low	I sink: 2 mA	<= 0,4 V
Tacho signal High	I source: 0 mA	<= 60 V
Maximum sink current		<= 4 mA
External resistor	External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency	(2 x n) / 60	
Tacho isolated from motor	No	
Slew rate		=> 0,5 V/us

Alarm type	None

3.4 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection Max. residual current at Un	Rectifying diode IF <= 100 uA	
Locked rotor protection	Auto restart	
Locked rotor current at Un	approx. 1.200 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,25 s / 10 s	


I
t3
t4
t


3.5 Aerodynamic

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m.

a.) Operation condition:

2.900 1/min at free air flow	PWM 100 %;	f: 2 kHz	f: 5 kHz

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	168,0 m3/h	
Max. static pressure (Δp = max. / $\dot{V}$ =0)	67 Pa	



3.6 Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

2.900 1/min at free air flow	PWM 100 %	PWM min.: ; f: 2 kHz	PWM max.:; f: 5 kHz

Optimal operating point	124,0 m3/h @ 19 Pa	
Sound power level at the optimal operating point	5,4 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	43,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	60 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic requirements*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Radiation exposure	None	
Dust requirements	None	
Salt fog requirements	None	
Harmful gas requirements	None	

*) Permittet application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 500 VAC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Air and leakage distances	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests

CE	Yes
UL	No
VDE	No
CSA	No
CCC	No

The approval tests are observed to:
Maximal permitted operating voltage (see section 3.1) and max. permitted ambient temperature TU max.


Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

Schutzvermerk nach DIN ISO 16016 beachten/
Refer to protection notice DIN ISO 16016

Steckergehäuse/
plug housing
Molex 50579040-4
Kontakt/ contact
Molex 16020088

Steckerbelegung/
PIN configuration:

Pin 1 = blau/blue
Pin 2 = rot / red
Pin 3 = weiß / white
Pin 4 = violett/violet



1) Maße für Montagewand / measures for mounting cut-out

2) Pos. 29 nur wenn in Stückliste enthalten / Pos. 29 only if included in bill of material

–Axialspiel bei Kugellagerung (K): 0 (mit Federausgleich) –axial clearance by ball bearing (K): 0 (by a pre-loaded spring)

–Axialspiel bei Gleitlagerung (G): 0.1 – 0.6 –axial clearance by sleeve bearing (G): 0.1 – 0.6

			ebmpapst	Werkstoff/Material:			Volumen/Volume (mm³):	
SAP-Status/Stat.	Kund.-Nr./Cliente-No.	AutoCAD-System-Version	CAD-Umgebung/ CAD-Environment				Gewicht/Mass (g):	
		Datum/Date	Name/Name					
		Bearb./ Drawn		Artikel/Title				
		Gepr./ Checked						
		Freig./ Release.						
Toleranzen/Tolerances:		ebmpapst		Zchg.-Nr./ Drawing-No.:			Ers.f.Zchg./ Replaces	
Allgemeintoleranzen/Gen. tolerances		ebm-papst St. Georgen GmbH & Co. KG		Dokumenttyp/Type of Document	Feld/dokument (Blatt/Page)	Index/Index	Format/Size	Maßstab/Scale

11-99