**R3G630-FB32-05**

Stulz GmbH

# EC centrifugal fan - RadiCal

backward-curved, single-intake

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **R3G630-FB32-05** |
| **Motor** | **M3G150-IF** |

| | | |
|---|---|---|
| Phase | | 3~ |
| Nominal voltage | VAC | 400 |
| Nominal voltage range | VAC | 380 .. 480 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ml |
| Status | | prelim. |
| Speed (rpm) | $min^{-1}$ | 1420 |
| Power consumption | W | 3700 |
| Current draw | A | 5.7 |
| Min. ambient temperature | °C | -40 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

## Data according to Commission Regulation (EU) 327/2011

| | | Actual | Req. 2015 |
|---|---|---|---|
| 01 Overall efficiency $\eta_{es}$ | % | 71.4 | 57.4 |
| 02 Measurement category | | A | |
| 03 Efficiency category | | Static | |
| 04 Efficiency grade N | | 76 | 62 |
| 05 Variable speed drive | | Yes | |

| | | |
|---|---|---|
| 09 Power consumption $P_{ed}$ | kW | 3.66 |
| 09 Air flow $q_v$ | $m^3/h$ | 12685 |
| 09 Pressure increase $p_{fs}$ | Pa | 711 |
| 10 Speed (rpm) n | $min^{-1}$ | 1420 |
| 11 Specific ratio* | | 1.01 |

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

LU-194121

# EC centrifugal fan - RadiCal

backward-curved, single-intake

## Technical description

| | |
|---|---|
| **Weight** | 0.001 kg |
| **Size** | 630 mm |
| **Motor size** | 150 |
| **Rotor surface** | Painted black |
| **Electronics housing material** | Die-cast aluminum |
| **Impeller material** | PP plastic |
| **Number of blades** | 6 |
| **Direction of rotation** | Clockwise, viewed toward rotor |
| **Degree of protection** | IP55 |
| **Insulation class** | "F" |
| **Moisture (F) / Environmental (H) protection class** | H1 |
| **Ambient temperature note** | Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings. |
| **Max. permitted ambient temp. for motor (transport/storage)** | +80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | -40 °C |
| **Installation position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensation drainage holes** | On rotor side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Operation and alarm display with LED<br>- External 15-50 VDC input (parameterization)<br>- Alarm relay<br>- Integrated PI controller<br>- Configurable inputs/outputs (I/O)<br>- MODBUS V6.0<br>- Motor current limitation<br>- RFID - ISO 15693 compatible<br>- RS-485 MODBUS-RTU<br>- Soft start<br>- Voltage output 3.3-24 VDC, Pmax = 800 mW<br>- Control interface with SELV potential safely disconnected from the mains<br>- Thermal overload protection for electronics/motor<br>- Line undervoltage / phase failure detection |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | <= 3.5 mA |
| **Electrical hookup** | Terminal box |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 61800-5-1; CE |
| **Approval** | CSA C22.2 No. 77 + CAN/CSA-E60730-1; EAC; UL 1004-7 + 60730-1 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal

backward-curved, single-intake

## Product drawing





| | |
|---|---|
| 1 | Accessory part: Inlet ring 63350-2-4013 not included in scope of delivery |
| 2 | Max. clearance for screw 20 mm |
| 3 | Cable Ölflex Classic 110 4x 0.75 mm² |
| | 4-pole header Wago 231-604 |
| 3.1 | GND |
| 3.2 | IO2 |
| 3.3 | COM / IO1 with bridge |
| 3.4 | NC |
| 4 | Cable Ölflex Classic 110 4G 2.5 mm² |
| | Plug with strain relief 5-pole Wago 0770-001/K011-0174/0000-0300 |
| 4.1 | Not used / no function |
| 4.2 | PE |
| 4.3 | L1 |
| 4.4 | L2 |
| 4.5 | L3 |



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

## Connection diagram




shaded gray => not brought out via leads

| No. | Conn. | Designation | Function/assignment |
|---|---|---|---|
| | CON1 | L1, L2, L3 | Power supply, phase, see nameplate for voltage range |
| | PE | PE | Protective earth |
| | CON2 | RSA | RS485 interface for MODBUS, RSA; SELV |
| | CON2 | RSB | RS485 interface for MODBUS, RSB; SELV |
| | CON2 | GND | Reference ground for control interface, SELV |
| | CON2 | IO1 | Function parameterizable (see table Optional interface functions)<br>Factory setting:<br>Digital input - high active, Function: Enable input, SELV<br>- inactive: Pin open or applied voltage < 1.5 VDC / <0.7 VAC<br>- active: applied voltage 3.5-50 VDC / 7-30 VAC |
| | CON2 | IO2 | Function parameterizable (see table Optional interface functions)<br>Factory setting:<br>Analog input 0-10 V / PWM, Ri=100 kΩ, Function: Set value<br>Characteristic curve parameterizable (see input characteristic curve P1-IN) , SELV |
| | CON2 | IO3 | Function parameterizable (see table Optional interface functions)<br>Factory setting:<br>Analog output 0-10 V, max. 5 mA, Function: Fan modulation level<br>Characteristic curve parameterizable (see output characteristic curve P3-OUT), SELV |
| | CON2 | V out | Voltage output 3.3-24 VDC ±5%, Pmax=800 mW, voltage parameterizable<br>Factory setting: 10 VDC<br>short-circuit-proof, supply for external devices, SELV<br>alternatively: 15-50 VDC input for parameterization via MODBUS without line voltage |
| | CON2 | COM | Status relay, floating status contact, common connection, contact rating 250 VAC / 2 A (AC1) / min. 10 mA, reinforced insulation on supply side and on control interface side |
| | CON2 | NC | Status relay, floating status contact, break for failure or n < 200 rpm |
| | | LED | green: status = good, ready for operation<br>orange: status = warning<br>red: status = failure |
| | | P1-IN | Input characteristic curve |
| | | P3-OUT | Output characteristic curve |



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal

backward-curved, single-intake

## Terminal/plug assignment

○ configurable option

For further information and additional functions see EC Control Software, Fan-Set-App, or MODBUS Parameter Specification V6.0

| CON2 | configurable IO mode | electrical specification | MODBUS Register for IO mode configuration | configurable IO functions: normal / inverse | INPUT: source: set value | INPUT: source: sensor value | INPUT: switch: parameter set: #1 / #2 | INPUT: switch: control function: heating (pos.) / cooling (neg.) | INPUT: switch: direction of rotation: cw / ccw | INPUT: switch: set value source | INPUT: switch: fan enable / disable | OUTPUT: signal: tach out (selected directly via IO mode) | OUTPUT: signal: diagnostics out (selected directly via IO mode) | OUTPUT: signal: fan modulation level % | OUTPUT: signal: actual speed | OUTPUT: signal: system modulation level % | OUTPUT: signal: remote control output 0-10V | pulse input for auto-adressing | pulse output for auto-adressing |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | D101 [...] | | D147 [...] | D104 [...] | D12E [...] | D148 [...] | D16C [...] | D16A [...] | | | | D130 [0] | D130 [1] | D130 [2] | D130 [5] | D00C [1] | D130 [4] |
| IO1 | ○ **Din1 (active high)**: digital input | not active: pin open or applied voltage < 1,5VDC<br>active: applied voltage 3,5-50VDC, SELV | D158 [0] | | | | ○ | ○ | ○ | ○ | ○ | | | | | | | | |
| | ○ **Ain1 0-10V/PWM**: analog input | Ri=100K, characteristic curve parameterizable, $f_{PWM}$=1k..10KHz, SELV | D158 [2] | | ○ | | | | | | | | | | | | | | |
| | ○ **Tach out** (open collector output) | Umax=50VDC, Imax=20mA SELV | D158 [5] | | | | | | | | | ○ | | | | | | | |
| | ○ **Diagnostics out** (open collector output) | Umax=50VDC, Imax=20mA SELV | D158 [6] | | | | | | | | | | ○ | | | | | | |
| IO2 | ○ **Din2 (active high)**: digital input | not active: pin open or applied voltage < 1,5VDC<br>active: applied voltage 3,5-50VDC, SELV | D159 [0] | | | | ○ | ○ | ○ | ○ | ○ | | | | | | | | |
| | ○ **Ain2 0-10V/PWM**: analog input | Ri=100K, characteristic curve parameterizable, fPWM=1k..10KHz, SELV | D159 [2] | | ○ | | | | | | | | | | | | | | |
| | ○ **Ain2 4-20mA**: analog input | Ri=125R, characteristic curve parameterizable, SELV | D159 [3] | | | | | | | | | | | | | | | | |
| IO3 | ○ **Din3 (active high)**: digital input | not active: pin open or applied voltage < 1,5VDC<br>active: applied voltage 3,5-50VDC, SELV | D15A [0] | | | | | ○ | ○ | ○ | ○ | | | | | | | | |
| | ○ **Din3 (active low)**: digital input | active: pin open or applied voltage 3,5-50VDC<br>not active: applied voltage < 1,5VDC, SELV | D15A [1] | | | | | | | | | | | | | | | | |
| | ○ **PWMin3**: digital input | 40Hz - 10kHz, characteristics parameterizable<br>not active: pin open or applied voltage 3,5-50VDC<br>active: applied voltage < 1,5VDC, SELV | D15A [7] | | ○ | | | | | | | | | | | | | | |
| | ○ **Aout3 0-10V**: analog output | function parameterizable, max. 5mA, max output frequency 300Hz, SELV | D15A [4] | | | | | | | | | | ○ | | | | ○ | | |
| | ○ **Tacho out** (pulses), analog output | 0-10V max. 5mA, max output frequency 300Hz, SELV | D15A [5] | | | | | | | | | ○ | | | | | | | |
| | ○ **Diagnostics out** (pulses) | 0-10V max. 5mA, max output frequency 300Hz, SELV | D15A [6] | | | | | | | | | | ○ | | | | | | |
| RSA<br>RSB | RS485 bus connection, | MODBUS RTU, specification V6.0, SELV | | | ○ | | ○ | ○ | ○ | ○ | ○ | | | | | | | | |
| Vout | voltage output | voltage parameterizable 3,3...24VDC +/- 5,5%, Pmax=800mW, short-circuit-proof, supply for external devices, SELV | D16E [...] | | | | | | | | | | | | | | | | |
| | alternatively: Input auxiliary power supply for parameter-ization via RS485/MODBUS RTU without line voltage | 15...50VDC | | | | | | | | | | | | | | | | | |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal

backward-curved, single-intake

## Curves: Air performance 50 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-194121-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | Wired | U | f | n | $P_{ed}$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa | cfm | in. wg |
| 1 | 3~ | 400 | 50 | 1420 | 2234 | 3.47 | 81 | 89 | 92 | 21540 | 0 | 12680 | 0.00 |
| 2 | 3~ | 400 | 50 | 1420 | 3118 | 4.78 | 80 | 86 | 89 | 18535 | 300 | 10910 | 1.20 |
| 3 | 3~ | 400 | 50 | 1420 | 3700 | 5.70 | 73 | 81 | 85 | 14655 | 600 | 8625 | 2.41 |
| 4 | 3~ | 400 | 50 | 1420 | 3520 | 5.38 | 73 | 81 | 85 | 10010 | 780 | 5890 | 3.13 |
| 5 | 3~ | 400 | 50 | 1250 | 1517 | 2.36 | 78 | 86 | 89 | 18935 | 0 | 11145 | 0.00 |
| 6 | 3~ | 400 | 50 | 1250 | 2118 | 3.25 | 77 | 83 | 85 | 16295 | 232 | 9590 | 0.93 |
| 7 | 3~ | 400 | 50 | 1250 | 2514 | 3.84 | 70 | 78 | 82 | 12875 | 465 | 7580 | 1.87 |
| 8 | 3~ | 400 | 50 | 1250 | 2391 | 3.65 | 70 | 78 | 82 | 8800 | 609 | 5180 | 2.44 |
| 9 | 3~ | 400 | 50 | 1050 | 899 | 1.40 | 74 | 82 | 84 | 15905 | 0 | 9365 | 0.00 |
| 10 | 3~ | 400 | 50 | 1050 | 1255 | 1.92 | 73 | 78 | 81 | 13685 | 164 | 8055 | 0.66 |
| 11 | 3~ | 400 | 50 | 1050 | 1490 | 2.27 | 65 | 73 | 77 | 10815 | 328 | 6365 | 1.32 |
| 12 | 3~ | 400 | 50 | 1050 | 1417 | 2.16 | 65 | 73 | 77 | 7390 | 430 | 4350 | 1.73 |
| 13 | 3~ | 400 | 50 | 850 | 477 | 0.74 | 68 | 76 | 79 | 12875 | 0 | 7580 | 0.00 |
| 14 | 3~ | 400 | 50 | 850 | 666 | 1.02 | 67 | 73 | 76 | 11080 | 107 | 6520 | 0.43 |
| 15 | 3~ | 400 | 50 | 850 | 791 | 1.21 | 60 | 68 | 72 | 8755 | 215 | 5155 | 0.86 |
| 16 | 3~ | 400 | 50 | 850 | 752 | 1.15 | 60 | 68 | 72 | 5985 | 282 | 3520 | 1.13 |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · $P_{ed}$ = Power consumption · I = Current draw · $LpA_{in}$ = Sound pressure level intake side · $LwA_{in}$ = Sound power level intake side $LwA_{out}$ = Sound power level outlet side · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com