**R3G310-RS01-I1**

# EC centrifugal fan - RadiCal®

backward curved, single inlet



**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | | |
|---|---|---|
| **Type** | **R3G310-RS01-I1** | |
| **Motor** | **M3G084-FA** | |
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 277 |
| Frequency | Hz | 50/60 |
| Type of data definition | | ml |
| Speed | $min^{-1}$ | 2640 |
| Power input | W | 730 |
| Current draw | A | 3.20 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 60 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

## Data according to ErP directive

| | |
|---|---|
| Installation category | A |
| Efficiency category | Static |
| Variable speed drive | Yes |
| Specific ratio* | 1.01 |

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

| | | Actual | Request 2013 | Request 2015 |
|---|---|---|---|---|
| Overall efficiency $\eta_{es}$ | % | 65.3 | 46.1 | 50.1 |
| Efficiency grade N | | 77.2 | 58 | 62 |
| Power input $P_{ed}$ | kW | 0.74 | | |
| Air flow $q_v$ | $m^3/h$ | 2410 | | |
| Pressure increase $p_{fs}$ | Pa | 661 | | |
| Speed n | $min^{-1}$ | 2640 | | |

Data definition with optimum efficiency. LU-149466
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.



ebmpapst

# EC centrifugal fan - RadiCal®

backward curved, single inlet

## Technical features

| | |
|---|---|
| **Mass** | 5.7 kg |
| **Size** | 310 mm |
| **Surface of rotor** | Coated in black |
| **Material of electronics housing** | Die-cast aluminium |
| **Material of impeller** | PP plastic |
| **Number of blades** | 6 |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 54 |
| **Insulation class** | "F" |
| **Humidity class** | F3-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | +80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | -40 °C |
| **Mounting position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensate discharge holes** | Rotor-side |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 10 mA<br>- Operation and alarm display<br>- Alarm relay<br>- Integrated PID controller<br>- Output limit<br>- Motor current limit<br>- PFC, active<br>- RS485 MODBUS RTU<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Control interface with SELV potential safely disconnected from the mains<br>- Over-temperature protected electronics / motor<br>- Line undervoltage / phase failure detection |
| **EMC interference immunity** | Acc. to EN 61000-6-2 (industrial environment) |
| **EMC harmonics** | Acc. to EN 61000-3-2/3 |
| **EMC interference emission** | Acc. to EN 61000-6-3 (household environment) |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | <= 3.5 mA |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Cable exit** | Variable |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 61800-5-1; EN 60335-1; CE |
| **Approval** | EAC |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal®

backward curved, single inlet

## Product drawing




| | |
|---|---|
| 1 | Accessory part: inlet nozzle 31000-2-4013 not included in scope of delivery |
| 2 | Depth of screw max. 10 mm |
| 3 | Connection line PVC AWG18, 5x crimped core-end sleeves |
| 4 | Connection line PVC AWG22, 5x crimped core-end sleeves |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal®

backward curved, single inlet

## Accessory part







ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal®

backward curved, single inlet

## Connection screen




| No. | Conn. | Designation | Colour | Function / assignment |
|---|---|---|---|---|
| 1 | 1, 2 | PE | green/yellow | Protective earth |
| 1 | 3 | N | blue | Supply voltage, neutral conductor, 50/60 Hz |
| 1 | 5 | L | black | Supply voltage, phase, 50/60 Hz |
| 1 | 6 | NC | white 1 | Status relay, floating status contact; break for failure, contact rating 250 VAC / 2A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side |
| 1 | 7 | COM | white 2 | Status relay, floating status contact; common connection, contact rating 250 VAC / 2A (AC1) min. 10 mA, basic insulation on mains side and reinforced insulation on control interface side |
| 2 | 8 | 0-10V | yellow | Analogue input 1 (set value); 0-10 V; Ri=100kΩ; parametrisable curve |
| 2 | 10 | RSB | brown | RS485 interface for Modbus, RSB |
| 2 | 11 | RSA | white | RS485 interface for Modbus, RSA |
| 2 | 12 | GND | blue | Reference ground for control interface, SELV |
| 2 | 13 | +10V | red | Fixed voltage output 10 VDC; +10 V +/-3%; max. 10 mA; short-circuit-proof; power supply for external devices (e.g. potentiometer) |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan - RadiCal®

backward curved, single inlet

## Charts: Air flow 50 Hz




Measurement: LU-149466

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_{ed}$ | I | $LpA_{in}$ | $LwA_{in}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | 230 | 50 | 2700 | 550 | 2.45 | 76 | 84 | 4020 | 0 |
| 2 | 230 | 50 | 2700 | 729 | 3.20 | 72 | 79 | 3355 | 400 |
| 3 | 230 | 50 | 2640 | 730 | 3.20 | 68 | 75 | 2355 | 700 |
| 4 | 230 | 50 | 2700 | 730 | 3.20 | 72 | 79 | 1600 | 900 |
| 5 | 230 | 50 | 2300 | 333 | 1.48 | 72 | 80 | 3400 | 0 |
| 6 | 230 | 50 | 2300 | 442 | 1.94 | 68 | 75 | 2840 | 287 |
| 7 | 230 | 50 | 2300 | 489 | 2.15 | 65 | 71 | 2050 | 530 |
| 8 | 230 | 50 | 2300 | 442 | 1.95 | 67 | 74 | 1355 | 644 |
| 9 | 230 | 50 | 1900 | 188 | 0.83 | 67 | 75 | 2810 | 0 |
| 10 | 230 | 50 | 1900 | 249 | 1.10 | 63 | 70 | 2345 | 196 |
| 11 | 230 | 50 | 1900 | 275 | 1.21 | 60 | 67 | 1695 | 362 |
| 12 | 230 | 50 | 1900 | 249 | 1.10 | 63 | 70 | 1120 | 440 |
| 13 | 230 | 50 | 1500 | 92 | 0.41 | 61 | 69 | 2215 | 0 |
| 14 | 230 | 50 | 1500 | 123 | 0.54 | 57 | 64 | 1850 | 122 |
| 15 | 230 | 50 | 1500 | 136 | 0.60 | 54 | 61 | 1340 | 225 |
| 16 | 230 | 50 | 1500 | 123 | 0.54 | 57 | 64 | 885 | 274 |

U = Supply voltage · f = Frequency · n = Speed · $P_{ed}$ = Power input · I = Current draw · $LpA_{in}$ = Sound pressure level inlet side · $LwA_{in}$ = Sound power level inlet side · qv = Air flow
$p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com