**K3G310-AN12-94**

# EC centrifugal module

backward-curved, single-intake

with support bracket, for rail applications

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | | |
|---|---|---|
| **Type** | **K3G310-AN12-94** | |
| **Motor** | **M3G084-FA** | |
| Nominal voltage | VDC | 110 |
| Nominal voltage range | VDC | 77 .. 145 |
| Method of obtaining data | | ml |
| Speed (rpm) | min$^{-1}$ | 2300 |
| Power consumption | W | 410 |
| Current draw | A | 3.7 |
| Min. ambient temperature | °C | -40 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# EC centrifugal module

backward-curved, single-intake

with support bracket, for rail applications

## Technical description

| | |
|---|---|
| **Weight** | 8.4 kg |
| **Fan size** | 310 mm |
| **Rotor surface** | Painted black |
| **Electronics housing material** | Die-cast aluminum, painted black |
| **Impeller material** | Sheet aluminum, painted black |
| **Support plate material** | Sheet aluminum, painted black |
| **Support bracket material** | Steel, painted black |
| **Number of blades** | 6 |
| **Direction of rotation** | Clockwise, viewed toward rotor |
| **Degree of protection** | IP54 |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | F3-1 |
| **Max. permitted ambient temp. for motor (transport/storage)** | +80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | -40 °C |
| **Installation position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensation drainage holes** | On rotor side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 1.1 mA<br>- Alarm relay<br>- Motor current limitation<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Control interface with SELV potential safely disconnected from the mains<br>- Thermal overload protection for electronics/motor<br>- Line undervoltage detection |
| **EMC immunity to interference** | According to EN 61000-6-2 (industrial environment) |
| **EMC interference emission** | According to EN 61000-6-4 (industrial environment) |
| **Electrical hookup** | With plug |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 61800-5-1 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support bracket, for rail applications

## Product drawing




| | |
|---|---|
| 1 | Cable XLPE/XLPO 5x 1.0 mm², 4x plug pin Harting part number 0933 000 6105 |
| 2 | Cable XLPE/XLPO 3x 0.33 mm², 3x plug pin Harting part number 0915 000 6104 |
| 3 | Connector housing Harting part number 19 20 003 1250 with connector housing Harting part number 09 12 005 3001 |
| 3.1 | COM |
| 3.2 | NC |
| 3.3 | +110 V |
| 3.4 | not used |
| 3.5 | - |
| 3.6 | PE |
| 4 | Connector housing Harting part number 19 20 003 1250 with connector housing Harting part number 09 12 007 3001 |
| 4.1 | GND |
| 4.2 | 0-10 V/PWM |
| 4.3 | not used |
| 4.4 | +10 V |
| 4.5 | not used |
| 4.6 | not used |
| 4.7 | not used |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support bracket, for rail applications

## Connection diagram




| No. | Conn. | Designation | Color | Function/assignment |
|---|---|---|---|---|
| 1 | 1 | PE | green/yellow | Protective earth |
| 1 | 3 | - | blue | Power supply, GND (110 VDC) |
| 1 | 4 | + | red | Power supply, 110 VDC |
| 1 | 5 | NC | white 1 | Floating status contact, break for failure |
| 1 | 6 | COM | white 2 | Floating status contact, break for failure<br>(0.6 A-110 VDC, 1 A-80 VDC, 3 A-30 VDC) |
| 2 | 8 | 0-10 V | yellow | Control input, set value 0-10 VDC, impedance 100 kΩ, SELV |
| 2 | 11 | 10 VDC | red | Voltage output 10 VDC (±3%), max. 1.1 mA,<br>power supply for external devices (e.g. potentiometers), SELV |
| 2 | 12 | GND | blue | Reference ground for control interface, SELV |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support bracket, for rail applications

## Curves: Air performance




Measurement: LU-104537-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | n | $P_{ed}$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|
| | V | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 110 | 2385 | 309 | 2.80 | 2705 | 0 | 1590 | 0.00 |
| 2 | 110 | 2340 | 369 | 3.35 | 2265 | 250 | 1335 | 1.00 |
| 3 | 110 | 2300 | 410 | 3.70 | 1630 | 500 | 960 | 2.01 |
| 4 | 110 | 2330 | 385 | 3.50 | 1025 | 650 | 605 | 2.61 |
| 5 | 110 | 2100 | 211 | 1.91 | 2380 | 0 | 1400 | 0.00 |
| 6 | 110 | 2100 | 267 | 2.43 | 2030 | 201 | 1195 | 0.81 |
| 7 | 110 | 2100 | 308 | 2.80 | 1485 | 414 | 875 | 1.66 |
| 8 | 110 | 2100 | 282 | 2.56 | 925 | 527 | 545 | 2.12 |
| 9 | 110 | 1700 | 112 | 1.01 | 1925 | 0 | 1135 | 0.00 |
| 10 | 110 | 1700 | 142 | 1.29 | 1645 | 132 | 970 | 0.53 |
| 11 | 110 | 1700 | 163 | 1.48 | 1200 | 271 | 705 | 1.09 |
| 12 | 110 | 1700 | 150 | 1.36 | 750 | 346 | 440 | 1.39 |
| 13 | 110 | 1300 | 50 | 0.45 | 1475 | 0 | 870 | 0.00 |
| 14 | 110 | 1300 | 63 | 0.58 | 1260 | 77 | 740 | 0.31 |
| 15 | 110 | 1300 | 73 | 0.66 | 920 | 159 | 540 | 0.64 |
| 16 | 110 | 1300 | 67 | 0.61 | 570 | 202 | 335 | 0.81 |

U = Power supply · n = Speed (rpm) · $P_{ed}$ = Power consumption · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com