Product Data Sheet | 4312/12M



The engineer's choice

ebmpapst

4312/12M

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 3

3.1 Operating Data - Electrical Interface - Input 3
3.2 Electrical Operating Data 4
3.3 Operating Data - Electrical Interface -Output 4
3.4 Electrical Features 5
3.5 Aerodynamic 6
3.6 Sound Data 7

4 Environment 7

4.1 General 7
4.2 Climatic requirements*) 7

5 Safety 8

5.1 Electrical Safety 8
5.2 Approval Tests 8

6 Reliability 8

6.1 General 8

1 General

Fan type	Fan	
Rotational direction looking at rotor	clockwise	
Airflow direction	Air outlet over struts	
Bearing system	Ball bearing	
Mounting position	any	


2 Mechanics

2.1 General

Width	119,0 mm	
Height	119,0 mm	
Depth	32,0 mm	
Weight	0,220 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges Screw size	wire outlet corner: 20 Ncm remaining corners: 20 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Length of lead wire Tolerance	L = 310 mm +- 10,0 mm	
Wire gauge (AWG)	22	
Insulation diameter	1,70 mm	
Contact	see drawing	



	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	yellow	Tacho

3 Operating Data

3.1 Operating Data - Electrical Interface - Input

Control input	None

3.2 Electrical Operating Data


Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area should not be any solid obstruction within 0,5 m.

Δp = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	6,0 V		15,0 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 0001	P	0,6 W +- 17,5 %	3,1 W +- 12,5 %	5,1 W +- 15,0 %
Current consumption Tolerance	Δp = 0 0001	I	116 mA +- 17,5 %	258 mA +- 12,5 %	340 mA +- 15,0 %
Speed Tolerance	Δp = 0 0001	n	1.250 1/min +- 12,5 %	2.300 1/min +- 7,5 %	2.700 1/min +- 10,0 %
Starting current consumption				< 860 mA	

3.3 Operating Data - Electrical Interface -Output

Tacho type	/12 (TTL)




Features	Note	Values
Tacho signal TTL High		Min.: 2,5 V Max.: 5,5 V
Tacho signal Low	I sink: 1 mA	<= 0,4 V
Tacho signal High	I source: 1 mA	
Maximum sink current		<= 1 mA
External resistor	All voltages measured to GND.	
Tacho frequency	(2 x n) / 60	
Tacho isolated from motor	No	
Slew rate		=> 0,5 V/us

Alarm type	None

3.4 Electrical Features

Electronic function	None	
Reversed polarity protection Max. residual current at Un	Rectifying diode IF <= 600 uA	
Locked rotor protection	Auto restart	
Locked rotor current at Un	approx. 860 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,6 s / 10 s	



Block1: special locked rotor protection: 5 cycles t3 / t4 = 0,6 s / 1 s Block2: locked rotor protection t3 / t4 = 0,6 s / 10 s


3.5 Aerodynamic

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

2.300 1/min at free air flow

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	138,0 m3/h	
Max. static pressure (Δp = max. / $\dot{V}$ =0)	54 Pa	



3.6 Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

2.300 1/min at free air flow

Optimal operating point	118,0 m3/h @ 9 Pa	
Sound power level at the optimal operating point	5,3 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	39,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	75 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic requirements*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Dust requirements	None	
Salt fog requirements	None	

*) Permittet application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.
Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.Please require severity levels and specification parameters from the responsible development departments

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 500 VAC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
clearance / creepage distance	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests

CE	Yes
UL	Yes / UL507, Electric Fans
VDE	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Yes / C22.2 No. 113 Fans and Ventilators
CCC	No


6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	70.000 h	
Life expectancy L10 at TU max.	30.000 h	
Life expectancy L10 Delta (40 °C)	135.000 h	

Copies of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

Schutzvermerk nach DIN 34 beachten



	Erzeugnis-Nr.	Typ	Lagersystem K=Kugellager G=Gleitlager	Litzenl?nge L	Schlauch-l?nge L1
	929 4305 020	4312 S	K	310 ±10	–
	929 4305 021	4314 S	K	310 ±10	–
	929 4305 024	4312 WS	K	310 ±10	–
	929 4305 043	4318/2	K	310 ±10	–
	929 4305 072	4312 WV	K	310 ±10	–
	929 4305 085	4312 WV VP	K	310 ±10	–
	929 4305 097	4312 WS-097	K	310 ±10	–
	929 4305 101	4318/2-101	K	310 ±10	–
	929 4305 107	4314/12	K	310 ±10	–
	929 4305 122	4312 V VP	K	310 ±10	–
	929 4305 127	4318/2-127	K	310 ±10	–
	929 4305 156	4312/10 V	K	310 ±10	–
	929 4305 171	4314/19-171	K	310 ±10	–
	929 4305 174	4312 LS-174	K	310 ±10	–
	929 4305 196	4312/17 L	K	310 ±10	–
	929 4305 236	4314/12-236	K	310 ±10	–
	929 4305 237	4312/12-237	K	310 ±10	–
	929 4305 239	4314/12-239	K	310 ±10	–
	929 4305 240	4318/12-240	K	310 ±10	–
	929 4305 243	4312/12 L-243	K	310 ±10	–
	929 4305 245	4312/12 M	K	310 ±10	–
	929 4305 253	4314/2	K	310 ±10	–
	929 4305 273	4318/12	K	310 ±10	–
	929 4305 277	4318/17 M	K	310 ±10	–
	929 4305 280	4314 V	K	310 ±10	–
	929 4305 290	4318/2 W	K	310 ±10	–
	929 4305 293	4312/2	K	310 ±10	–
	929 4305 296	4312 V-296	K	310 ±10	–
	929 4305 303	4312 L/12	K	310 ±10	–
	929 4305 311	4312/2-311	K	310 ±10	–
	929 4305 343	4318/2-343	K	310 ±10	–
ⓔ	929 4305 350	4314/17 U-350	K	660 ±10	620 ±10
ⓕ	929 4305 361	4312 V-361	K	625 ±10	–
ⓗ	929 4305 383	4312/10 VR	K	310 ±10	–

1) Rotor?berstand bis max. 0.4 mm zul?ssig.

Axialspiel bei
- Kugellagerung (K): 0 (mit Federausgleich)
- Gleitlagerung (G): 0.1 – 0.6

⑨ 2) Pos. 35 nur wenn in St?ckliste vermerkt

Allgemeintoleranzen						
h	Erg?nzung	09.06.98	Koletzki M.		Datum	Name
g	98047	27.01.98	Knapp U.	Erstellt	07.12.95	Kieninger
f	Erg?nzung	27.01.98	Kieninger	Gepr?ft	12.12.95	Wrobel G.
e	97695	10.11.97	Knapp U.			
d	Erg?nzung	05.11.97	Kieninger			
Index	Znd.-Nr.	Datum	Ge?ndert von			

Zur Verwendung im Verteiler freigegeben von Koletzki M. am 10.06.98

PAPST

PAPST-MOTOREN GmbH & Co KG
D-78112 St.Georgen
Germany

Artikel: Axiall?fter

Maßstab: 1:1

Zchg.-Nr.: 929 4305 020

Blatt 2

Ers.f.Zchg.: gl. Nr. v. 24.03.86

K:\929\4305\

516
210
232
235
240
3..