**D3G250-ED01-71**

# EC centrifugal fan

forward curved, dual inlet

with housing (flange)



**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | | |
|---|---|---|
| **Type** | **D3G250-ED01-71** | |
| **Motor** | **M3G084-GF** | |
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Frequency | Hz | 50/60 |
| Type of data definition | | ml |
| Speed | $min^{-1}$ | 1085 |
| Power input | W | 450 |
| Current draw | A | 2.8 |
| Min. back pressure | Pa | 100 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

## Data according to ErP directive

| | |
|---|---|
| Installation category | A |
| Efficiency category | Static |
| Variable speed drive | Yes |
| Specific ratio* | 1.00 |

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

| | | Actual | Request 2013 | Request 2015 |
|---|---|---|---|---|
| Overall efficiency $\eta_{es}$ | % | 50.9 | 27.2 | 34.2 |
| Efficiency grade N | | 60.7 | 37 | 44 |
| Power input $P_{ed}$ | kW | 0.28 | | |
| Air flow $q_v$ | $m^3/h$ | 1605 | | |
| Pressure increase $p_{fs}$ | Pa | 292 | | |
| Speed n | $min^{-1}$ | 1235 | | |

Data definition with optimum efficiency. LU-109916
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.



ebmpapst

# EC centrifugal fan

forward curved, dual inlet

with housing (flange)

## Technical features

| | |
|---|---|
| **Mass** | 12.9 kg |
| **Size** | 250 mm |
| **Surface of rotor** | Coated in black |
| **Material of electronics housing** | Die-cast aluminum |
| **Material of impeller** | Sheet steel, hot-galvanised |
| **Housing material** | Sheet steel, hot-galvanised |
| **Motor suspension** | Motor anti-vibration mounted on one side via brackets |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 54 |
| **Insulation class** | "B" |
| **Humidity class** | F3-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | +80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | -40 °C |
| **Mounting position** | Shaft horizontal |
| **Condensate discharge holes** | None |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 1.1 mA<br>- Alarm relay<br>- Motor current limit<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Control interface with SELV potential safely disconnected from the mains<br>- Over-temperature protected electronics / motor<br>- Line undervoltage detection |
| **EMC interference immunity** | Acc. to EN 61000-6-2 (industrial environment) |
| **EMC harmonics** | Acc. to EN 61000-3-2/3 |
| **EMC interference emission** | Acc. to EN 61000-6-3 (household environment) |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | <= 3.5 mA |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Cable exit** | Variable |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 61800-5-1; CE |
| **Approval** | EAC |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

forward curved, dual inlet

with housing (flange)

## Product drawing




Cable length from electronics enclosure: 800+20 mm

| | |
|---|---|
| 1 | Connection line PVC AWG18, 5x crimped core-end sleeves |
| 2 | Connection line PVC AWG22, 3x crimped core-end sleeves |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

forward curved, dual inlet

with housing (flange)

## Connection screen







ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

forward curved, dual inlet

with housing (flange)

## Charts: Air flow 50 Hz




Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_{ed}$ | I | $LpA_{in}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | dB(A) | $m^3/h$ | Pa |
| 1 | 230 | 50 | 1085 | 450 | 2.80 | 71 | 2765 | 100 |
| 2 | 230 | 50 | 1125 | 401 | 2.55 | 69 | 2435 | 175 |
| 3 | 230 | 50 | 1175 | 346 | 2.20 | 67 | 2040 | 250 |
| 4 | 230 | 50 | 1285 | 232 | 1.50 | 65 | 1195 | 325 |
| 5 | 230 | 50 | 1000 | 346 | 2.21 | 69 | 2550 | 86 |
| 6 | 230 | 50 | 1000 | 282 | 1.80 | 66 | 2165 | 138 |
| 7 | 230 | 50 | 1000 | 213 | 1.36 | 63 | 1735 | 182 |
| 8 | 230 | 50 | 1000 | 110 | 0.71 | 58 | 930 | 199 |
| 9 | 230 | 50 | 800 | 177 | 1.13 | 63 | 2040 | 55 |
| 10 | 230 | 50 | 800 | 145 | 0.92 | 60 | 1730 | 88 |
| 11 | 230 | 50 | 800 | 109 | 0.70 | 56 | 1390 | 116 |
| 12 | 230 | 50 | 800 | 56 | 0.37 | 52 | 745 | 127 |
| 13 | 230 | 50 | 600 | 75 | 0.48 | 55 | 1530 | 31 |
| 14 | 230 | 50 | 600 | 61 | 0.39 | 51 | 1300 | 50 |
| 15 | 230 | 50 | 600 | 46 | 0.29 | 48 | 1040 | 66 |
| 16 | 230 | 50 | 600 | 24 | 0.15 | 44 | 560 | 72 |

U = Supply voltage · f = Frequency · n = Speed · $P_{ed}$ = Power input · I = Current draw · $LpA_{in}$ = Sound pressure level inlet side · qv = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com