**R3G250-AH52-01**

# EC centrifugal fan

backward curved, single inlet

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | |
|---|---|
| **Type** | **R3G250-AH52-01** |
| **Motor** | **M3G074-CF** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 277 |
| Frequency | Hz | 50/60 |
| Type of data definition | | ml |
| Speed | $min^{-1}$ | 2600 |
| Power input | W | 160 |
| Current draw | A | 1.2 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 60 |

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

## Data according to ErP directive

| | |
|---|---|
| Installation category | A |
| Efficiency category | Static |
| Variable speed drive | Yes |
| Specific ratio* | 1.00 |

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

| | | Actual | Request 2013 | Request 2015 |
|---|---|---|---|---|
| Overall efficiency $\eta_{es}$ | | 47.1 | 39.1 | 43.1 |
| Efficiency grade N | | 66 | 58 | 62 |
| Power input $P_{ed}$ | kW | 0.16 | | |
| Air flow $q_v$ | $m^3/h$ | 690 | | |
| Pressure increase $p_{fs}$ | Pa | 350 | | |
| Speed n | $min^{-1}$ | 2595 | | |

Data established at point of optimum efficiency



ebmpapst

# EC centrifugal fan

backward curved, single inlet

## Technical features

| | |
|---|---|
| **Mass** | 2.4 kg |
| **Size** | 250 mm |
| **Surface of rotor** | Thick layer passivated |
| **Material of electronics housing** | Die-cast aluminium |
| **Material of impeller** | Plastic PA66, fibreglass-reinforced |
| **Number of blades** | 11 |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 44; Depending on installation and position |
| **Insulation class** | "B" |
| **Humidity class** | F3-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | + 80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | - 40 °C |
| **Mounting position** | Shaft horizontal or rotor on top; rotor on bottom on request |
| **Condensate discharge holes** | None |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 1.1 mA<br>- Tach output<br>- Motor current limit<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Over-temperature protected electronics / motor |
| **EMC interference immunity** | Acc. to EN 61000-6-2 (industrial environment) |
| **EMC harmonics** | Acc. to EN 61000-3-2/3 |
| **EMC interference emission** | Acc. to EN 61000-6-3 (household environment) |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | <= 3.5 mA |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Cable exit** | Variable |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 60335-1; EN 60950-1; EN 61800-5-1; CE |
| **Approval** | UL 2111; CCC; CSA C22.2 Nr.77 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

backward curved, single inlet

## Product drawing




| | |
|---|---|
| 1 | Connection line AWG18, 3 x crimped core-end sleeves |
| 2 | Connection line AWG22, 4 x crimped core-end sleeves |
| 3 | Accessory part: inlet nozzle 96359-2-4013 not included in the standard scope of delivery; other inlet nozzles on request |
| 4 | Depth of screw 8 - 10 mm, tightening torque 2.5±0.2 Nm; gluing the screws is recommended |
| 5 | Pilot hole prepared for self-tapping screw M4, depth of screw max. 6 mm |
| 6 | Pilot hole prepared for self-tapping screw M4, depth of screw max. 8 mm |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

backward curved, single inlet

## Connection screen




| Line | No. | Signal | Colour | Function / assignment |
|---|---|---|---|---|
| | 4 | L | black | Power supply 230 VAC, 50-60 Hz, see type plate for voltage range |
| | 3 | N | blue | Neutral conductor |
| | 1 | PE | green/yellow | Protective earth |
| | 8 | 0-10 V PWM | yellow | Control input 0 - 10 V or PWM, electrically isolated |
| | 9 | Tach | white | Tach output: open collector, 1 pulse per revolution, electrically isolated |
| | 11 | 10V / max 1.1 mA | red | Voltage output 10 V / max. 1.1 mA, electrically isolated |
| | 12 | GND | blue | GND - Connection for control interface |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal fan

backward curved, single inlet

## Charts: Air flow 50 Hz




Measurement: LU-74719
Measurement: LU-67431
Measurement: LU-67432
Measurement: LU-67433

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_{ed}$ | I | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa |
| 1 | 230 | 50 | 2770 | 123 | 0.90 | 1295 | 0 |
| 2 | 230 | 50 | 2660 | 148 | 1.08 | 1030 | 175 |
| 3 | 230 | 50 | 2600 | 160 | 1.20 | 670 | 375 |
| 4 | 230 | 50 | 2680 | 147 | 1.08 | 355 | 500 |
| 5 | 230 | 50 | 2455 | 88 | 0.66 | 1155 | 0 |
| 6 | 230 | 50 | 2380 | 106 | 0.81 | 930 | 141 |
| 7 | 230 | 50 | 2335 | 116 | 0.87 | 600 | 302 |
| 8 | 230 | 50 | 2400 | 105 | 0.79 | 315 | 399 |
| 9 | 230 | 50 | 2000 | 53 | 0.40 | 945 | 0 |
| 10 | 230 | 50 | 1960 | 62 | 0.47 | 765 | 96 |
| 11 | 230 | 50 | 1935 | 69 | 0.51 | 500 | 208 |
| 12 | 230 | 50 | 1965 | 61 | 0.46 | 260 | 270 |
| 13 | 230 | 50 | 1380 | 22 | 0.17 | 640 | 0 |
| 14 | 230 | 50 | 1365 | 25 | 0.20 | 525 | 45 |
| 15 | 230 | 50 | 1350 | 28 | 0.22 | 345 | 100 |
| 16 | 230 | 50 | 1360 | 25 | 0.19 | 180 | 130 |

U = Supply voltage · f = Frequency · n = Speed · $P_{ed}$ = Power input · I = Current draw · qv = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com