**S3G800-BS39-10**

TRANE SAS

# EC axial fan - HyBlade

sickled blades (S series)

with guard grille for full nozzle

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | | |
|---|---|---|
| **Type** | **S3G800-BS39-10** | |
| **Motor** | **M3G150-FF** | |
| Phase | | 3~ |
| Nominal voltage | VAC | 400 |
| Nominal voltage range | VAC | 380 .. 480 |
| Frequency | Hz | 50/60 |
| Type of data definition | | ml |
| Speed | $min^{-1}$ | 1020 |
| Power input | W | 1950 |
| Current draw | A | 3.0 |
| Max. back pressure | Pa | 80 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 70 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

## Data according to ErP directive

| | |
|---|---|
| Installation category | A |
| Efficiency category | Static |
| Variable speed drive | Yes |
| Specific ratio* | 1.00 |

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

| | | Actual | Request 2015 |
|---|---|---|---|
| Overall efficiency $\eta_{es}$ | % | 43.4 | 36 |
| Efficiency grade N | | 47.4 | 40 |
| Power input $P_{ed}$ | kW | 2.37 | |
| Air flow $q_v$ | $m^3/h$ | 17695 | |
| Pressure increase $p_{fs}$ | Pa | 198 | |
| Speed n | $min^{-1}$ | 1025 | |

Data definition with optimum efficiency. LU-163024
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.



ebmpapst

# EC axial fan - HyBlade

sickled blades (S series)
with guard grille for full nozzle

## Technical features

| | |
|---|---|
| **Mass** | 32.9 kg |
| **Size** | 800 mm |
| **Surface of rotor** | Coated in black |
| **Material of electronics housing** | Die-cast aluminium, coated in black |
| **Material of blades** | Aluminium sheet insert, sprayed with PP plastic |
| **Material of guard grille** | Steel, coated in black plastic (RAL9005) |
| **Number of blades** | 5 |
| **Blade angle** | 0° |
| **Direction of air flow** | "V" |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 54 |
| **Insulation class** | "F" |
| **Humidity class** | F4-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | +80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | -40 °C |
| **Mounting position** | Shaft horizontal or rotor on bottom |
| **Condensate discharge holes** | Rotor-side |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Output 10 VDC, max. 10 mA<br>- Output 20 VDC, max. 50 mA<br>- Output for slave 0-10 V<br>- Operation and alarm display<br>- Input for sensor 0-10 V or 4-20 mA<br>- External 24 V input (programming)<br>- External release input<br>- Alarm relay<br>- Integrated PID controller<br>- Motor current limit<br>- PFC, passive<br>- RS485 MODBUS RTU<br>- Soft start<br>- Control input 0-10 VDC / PWM<br>- Control interface with SELV potential safely disconnected from the mains<br>- Over-temperature protected electronics / motor<br>- Line undervoltage / phase failure detection |
| **EMC interference immunity** | Acc. to EN 61000-6-2 (industrial environment) |
| **EMC interference emission** | Acc. to EN 61000-6-3 (household environment), except EN 61000-3-2 for professionally used devices with a total rated power greater than 1 kW |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | <= 3.5 mA |
| **Motor protection** | Reverse polarity and locked-rotor protection |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 61800-5-1; CE |
| **Approval** | EAC |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickled blades (S series)
with guard grille for full nozzle

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Connection line Ölflex Heat 105 MC 4G 1.0 mm² with connector housing WESTEC 7803.6231.1 and 5-pole pin insert WESTEC 7204.6102.4 |
| 2.1 | not used |
| 2.2 | Din 1 |
| 2.3 | Ain 1 U |
| 2.4 | GND |
| 2.5 | not used |
| 3 | Connection line Ölflex Heat 105 MC 4G 1.5 mm² with connector housing WESTEC 7803.6227.1 and 4-pole pin insert WESTEC 7203.6101.0 |
| 3.1 | L1 |
| 3.2 | L2 |
| 3.3 | L3 |
| 3.4 | PE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickled blades (S series)
with guard grille for full nozzle

## Connection screen




grey shaded => not brought out via leads

| No. | Conn. | Designation | Function / assignment |
|---|---|---|---|
| KL 1 | 1 | L1 | Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz |
| KL 1 | 2 | L2 | Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz |
| KL 1 | 3 | L3 | Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz |
| PE | | PE | Earth connection, PE connection |
| KL 2 | 1 | NO | Status relay, floating status contact; make for failure |
| KL2 | 2 | COM | Status relay; floating status contact; changeover contact; common connection; contact rating 250 VAC / max. 2 A (AC1) / min. 10 mA |
| KL2 | 3 | NC | Status relay, floating status contact; break for failure |
| KL 3 | 1 | RSA | Bus connection RS-485, RSA, MODBUS RTU; SELV |
| KL 3 | 2 | RSB | Bus connection RS-485, RSB, MODBUS RTU; SELV |
| KL 3 | 3 / 10 | GND | Signal ground for control interface; SELV |
| KL 3 | 4 | Ain1 U | Analogue input 1, set value: 0-10 V, Ri = 100 kΩ, parametrisable curve, only usable as alternative to input Ain1; SELV |
| KL 3 | 5 | + 10 V | Fixed voltage output 10 VDC, +10 V ±3%, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometer); SELV |
| KL 3 | 6 | Ain1 I | Analogue input 1, set value: 4-20 mA; Ri = 100 Ω, parametrisable curve, only usable as alternative to input Ain1 U; SELV |
| KL 3 | 7 | Din1 | Digital input 1: enabling of electronics,<br>enabling: open pin or applied voltage 5-50 VDC<br>disabling: bridge to GND or applied voltage <1 VDC<br>reset function: triggers software reset after a level change to <1 V; SELV |
| KL 3 | 8 | Din2 | Digital input 2: parameter set switch 1/2, according to EEPROM setting, the valid/used parameter set can be selected via bus or via digital input DIN2.<br>Parameter set 1: open pin or applied voltage 5-50 VDC<br>Parameter set 2: bridge to GND or applied voltage <1 VDC; SELV |
| KL 3 | 9 | Din3 | Digital input 3: controller function of integrated controller, according to EEPROM setting, the controller function of the integrated controller is normally/inversely selectable per bus or per digital input<br>normal: open pin or applied voltage 5-50 VDC<br>inverse: bridge to GND or applied voltage <0.8 VDC; SELV |
| KL 3 | 11 | Ain2 U | Analogue input 2, actual value: 0-10 V, Ri = 100 kΩ, parametrisable curve, only usable as alternative to input Ain2; SELV |
| KL 3 | 12 | + 20 V | Fixed voltage output 20 VDC, +20 V +25/-10%, max. 50 mA, short-circuit-proof, power supply for external devices (e.g. sensors); SELV |



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

| No. | Conn. | Designation | Function / assignment |
|---|---|---|---|
| KL 3 | 13 | Ain2 I | Analogue input 2, actual value: 4-20 mA, Ri = 100 Ω, parametrisable curve, only usable as alternative to input Ain2 U; SELV |
| KL 3 | 14 | Aout | Analogue output 0-10 VDC, max. 5 mA, output of the current motor level control coefficient / motor speed parametrisable curve; SELV |



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

**S3G800-BS39-10**


TRANE SAS

# EC axial fan - HyBlade

sickled blades (S series)

with guard grille for full nozzle

## Charts: Air flow 50 Hz




Measurement: LU-163024

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_{ed}$ | I | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa |
| 1 | 400 | 50 | 1020 | 1694 | 2.64 | 26935 | 0 |
| 2 | 400 | 50 | 1020 | 1798 | 2.79 | 25710 | 30 |
| 3 | 400 | 50 | 1020 | 1869 | 2.90 | 24890 | 50 |
| 4 | 400 | 50 | 1020 | 1950 | 3.00 | 23645 | 80 |
| 5 | 400 | 50 | 900 | 1130 | 1.76 | 23535 | 0 |
| 6 | 400 | 50 | 900 | 1206 | 1.87 | 22505 | 23 |
| 7 | 400 | 50 | 900 | 1258 | 1.95 | 21810 | 39 |
| 8 | 400 | 50 | 900 | 1334 | 2.06 | 20745 | 62 |
| 9 | 400 | 50 | 800 | 794 | 1.24 | 20920 | 0 |
| 10 | 400 | 50 | 800 | 847 | 1.32 | 20005 | 18 |
| 11 | 400 | 50 | 800 | 884 | 1.37 | 19385 | 31 |
| 12 | 400 | 50 | 800 | 937 | 1.45 | 18440 | 49 |
| 13 | 400 | 50 | 700 | 532 | 0.83 | 18305 | 0 |
| 14 | 400 | 50 | 700 | 568 | 0.88 | 17505 | 14 |
| 15 | 400 | 50 | 700 | 592 | 0.92 | 16965 | 23 |
| 16 | 400 | 50 | 700 | 628 | 0.97 | 16135 | 37 |

U = Supply voltage · f = Frequency · n = Speed · $P_{ed}$ = Power input · I = Current draw · qv = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com