3412 NGMI-377

Customer specification: No
Version: 1.0
Created: 07.07.2011

INDEX

1 General 2

2 Mechanics 2

2.1 General 2
2.2 Motor 2
2.3 Connections 3

3 Operating Data 4

3.1 Operating Data - Electrical Interface - Input 4
3.2 Electrical Operating Data 5
3.3 Operating Data - Electrical Interface -Output 6
3.4 Electrical Features 6
3.5 Aerodynamic 6
3.6 Sound Data 7

4 Environment 7

4.1 General 7
4.2 Climatic requirements 7
4.3 Mechanical requirements 8
4.4 EMC 8

5 Safety 8

5.1 Electrical Safety 8
5.2 Approval Tests 8

6 Reliability 8

6.1 General 8
6.2 Additional Data 8

Special features according to QMH 2-5.4.7 and company standard 1-23.00 have the following definitions:

"A" : Product features or process parameters which influence the safety of a product or the compliance of legal requirements. (Must not necessary verified and documented 100%. Standards and legal requirements must be considered.)

"FK" : Product features or process parameters which influence the fit and function of a product or which have to be controlled or documented for some other reasons (e.g. Customer requirements).

General

Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	**FK**
Airflow direction	Air outlet over struts	**FK**
Bearing system	Sleeve bearing	
Lubrication	see sectional drawing of the bearing	
Mounting position Tolerance	any	
Balancing grade	16	**FK**
Impeller weight	36,0 g	

Mechanics

General

Width	92,0 mm	
Height	92,0 mm	
Depth	25,4 mm	
Diameter	0,0 mm	
Weight	0,106 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges Screw size	wire outlet corner: 40 Ncm remaining corners: 60 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	


Motor

Type of motor	Electronically commutated external rotor	
Diameter of the motor	25,0 mm	
Height of the motor	6,0 mm	
Number of phases	1	
Number of windings	1	
Operating mode	Continuous duty	
Insulation material class	E	

Connections

Electrical connection	Wires - Plug	
Length of lead wire Tolerance	300 mm +- 10,0 mm	
Length of tube Tolerance		
Wire gauge (AWG)	22	
Insulation diameter	1,70 mm	
Plug	see drawing	
Contact	see drawing	







	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND

Operating Data

Operating Data - Electrical Interface - Input

Control input	Internal Temperature Sensor

Features

Characteristics	
Schematics	

Electrical Operating Data

Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area should not be any solid obstruction within 0,5 m.

Δp = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

Name	Condition		
TU 0001	TU: >= 50 °C		
NTC 0001			

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	8,0 V		14,0 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 TU / NTC: 0001	P	0,9 W +- 20,0 %	2,0 W +- 20,0 %	2,8 W +- 20,0 %
Current consumption Tolerance	Δp = 0 TU / NTC: 0001	I	110 mA +- 20,0 %	170 mA*) +- 20,0 %	200 mA +- 20,0 %
Speed Tolerance	Δp = 0 TU / NTC: 0001	n	1.500 1/min +- 10,0 %	2.300 1/min*) +- 10,0 %	2.700 1/min +- 10,0 %
Starting current consumption				460 mA	

Name	Condition		
TU 0002	TU: <= 30 °C		
NTC 0002			

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	8,0 V		14,0 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 TU / NTC: 0002	P	0,9 W +- 20,0 %	1,4 W +- 20,0 %	1,7 W +- 20,0 %
Current consumption Tolerance	Δp = 0 TU / NTC: 0002	I	115 mA +- 20,0 %	120 mA*) +- 20,0 %	120 mA +- 20,0 %
Speed Tolerance	Δp = 0 TU / NTC: 0002	n	1.400 1/min +- 10,0 %	1.400 1/min*) +- 10,0 %	1.400 1/min +- 10,0 %

*) Attention: Marked values are "FK" features


Operating Data - Electrical Interface -Output

Tacho type	None

Alarm type	None

Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection Max. residual current at Un	Rectifying diode IF <= 50 uA	**A**
Locked rotor protection	Auto restart	**A**
Locked rotor current at Un	approx. 460 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,23 s / 1,1 s t3: 0,06 s... 0,77 s t4: 0,3 s... 3,6 s	



Aerodynamic

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m.

a.) Operation condition:

2.300 1/min at free air flow	TU >= 50 °C		

Max. free-air flow (Δp = 0 / V̇ = max.)	70,0 m3/h	**FK**
Max. static pressure (Δp = max. / V̇ =0)	25 Pa	**FK**

Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

2.300 1/min at free air flow	TU >= 50 °C		

Optimal operating point	51,0 m3/h @ 8 Pa	
Sound power level at the optimal operating point	4,2 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	26,0 dB(A)	

Environment

General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	65 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

Climatic requirements*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Radiation exposure	None	
Dust requirements	None	
Salt fog requirements	None	
Harmful gas requirements	None	

*) Permittet application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

Mechanical requirements

Please require severity levels and specification parameters from the responsible development departments

EMC

not specified

Safety

Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	Not applicable Not applicable	**A**
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Air and leakage distances	1,0 mm / 1,2 mm	
Protection class	III	

Approval Tests

CE	Yes
UL	Yes / UL507, Electric Fans
VDE	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment - Part 1 Safety - Connection to a SELV circuit.
CSA	Yes / C22.2 No. 113-M1984 Fans and Ventilators
CCC	No

The approval tests are observed to:
Maximal permitted operating voltage (see section 3.1) and max. permitted ambient temperature TU max.

Reliability

General

Life expectancy L10 at TU = 40 °C	75.000 h	

Additional Data

not specified