R3G500-AG06-15

Fa. Stulz GmbH

EC centrifugal fan

backward curved, single inlet



ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

Nominal data

Type	**R3G500-AG06-15**
Motor	**M3G150-FF**

Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
Speed	min^{-1}	1700
Power input	W	2700
Current draw	A	4.3
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.01

* Specific ratio = 1 + p_{fs} / 100 000 Pa

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}		57.8	51.8	55.8
Efficiency grade N		64	58	62
Power input P_{ed}	kW	2.58		
Air flow q_v	m^3/h	6510		
Pressure increase p_{fs}	Pa	780		
Speed n	min^{-1}	1715		

Data established at point of optimum efficiency

ebmpapst

EC centrifugal fan

backward curved, single inlet

Technical features


Mass	22.7 kg
Size	500 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Number of blades	9
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity class	F4-1
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - Alarm relay - Integrated PID controller - Run monitoring - Motor current limit - PFC, passive - RS485 ebmBUS - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
EMC interference immunity	Acc. to EN 61000-6-2 (industrial environment)
EMC interference emission	Acc. to EN 61000-6-3 (household environment)
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	UL 2111; GOST; VDE; CSA C22.2 Nr.77

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal fan

backward curved, single inlet

Product drawing




1	Accessory part: Inlet nozzle 63072-2-4013, not included in the standard scope of delivery.
2	Depth of screw max. 25 mm
3	Cable diameter: min. 4 mm, max. 10 mm, tightening torque: 4±0.6 Nm
4	Cable diameter: min. 6 mm, max. 12 mm, tightening torque: 4±0.6 Nm
5	Tightening torque 3.5±0.5 Nm

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal fan

backward curved, single inlet

Connection screen



No.	Pin	Signal	Function / assignment
PE	-	PE	Protective earth connection
1	1, 2, 3	L1, L2, L3	Supply voltage 50 / 60 Hz
2	1	NC	Floating status message contact and run monitoring, normally closed for error or n < 80 / min
2	2	COM	Floating status message contact, changeover contact, common connection (2 A, max. 250 VAC, min. 10 mA, AC1)
2	3	NO	Floating status message contact and run monitoring, normally open for error or n < 80 / min
3	1	OUT	Analogue output, 0-10 VDC, max. 3 mA, SELV Output of the current motor level control coefficient: 1V corresponds to 10% modulation level. 10V corresponds to 100% modulation level
3	2, 8	GND	Reference mass for control interface, SELV
3	3, 7	0 -10 V	Use control / actual value input 0 -10 VDC, impedance 100 kohms only as alternative to 4-20 mA input, SELV
3	4	+ 10 V	Voltage output 10 VDC (+/-3%), max. 10 mA, supply voltage for ext. devices (e.g. potentiometer), SELV
3	5	+ 20 V	Voltage output 20 VDC (+25%/-10%), max. 50 mA, supply voltage for ext. devices (e.g. sensors), SELV
3	6	4-20 mA	Use control / actual value input 4-20 mA, impedance 100 ohms, only as alternative to 0-10 V input, SELV
3	9, 11	RSB	RS485 interface for ebm Bus, RSB; SELV
3	10, 12	RSA	RS485 interface for ebm Bus, RSA; SELV

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com


R3G500-AG06-15

Fa. Stulz GmbH

EC centrifugal fan

backward curved, single inlet

Charts: Air flow 50 Hz



Measurement: LU-109946

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P_{ed}	I	LpA_{in}	LwA_{in}	LwA_{out}	qv	p_{fs}
	V	Hz	min^{-1}	W	A	dB(A)	dB(A)	dB(A)	m^3/h	Pa
1	400	50	1700	1904	2.90	84	91	96	10900	0
2	400	50	1700	2307	3.49	80	87	93	9190	350
3	400	50	1700	2700	4.30	76	83	90	7495	700
4	400	50	1700	2401	3.64	76	83	90	4990	925
5	400	50	1400	1045	1.59	80	87	92	8925	0
6	400	50	1400	1262	1.91	76	82	88	7515	234
7	400	50	1400	1422	2.16	72	78	85	6120	468
8	400	50	1400	1306	1.98	72	78	85	4075	616
9	400	50	1100	507	0.77	75	81	86	7010	0
10	400	50	1100	612	0.93	70	77	83	5905	145
11	400	50	1100	690	1.05	66	73	80	4810	289
12	400	50	1100	634	0.96	66	73	80	3200	380
13	400	50	800	195	0.30	68	75	79	5100	0
14	400	50	800	236	0.36	63	70	76	4295	77
15	400	50	800	265	0.40	59	66	73	3500	153
16	400	50	800	244	0.37	60	66	73	2325	201

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side · LwA_{out} = Sound power level outlet side
qv = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com