**R4E280-AD50-14**

# AC centrifugal fan

backward-curved, single-intake

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **R4E280-AD50-14** |
| **Motor** | **M4E068-DF** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Frequency | Hz | 50 |
| Method of obtaining data | | fa |
| Valid for approval/standard | | CE |
| Speed (rpm) | $min^{-1}$ | 1410 |
| Power consumption | W | 78 |
| Current draw | A | 0.35 |
| Capacitor | µF | 2.5 |
| Capacitor voltage | VDB | 400 |
| Capacitor standard | | S2 (CE) |
| Min. back pressure | Pa | 0 |
| Min. back pressure | inH2O | 0 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# AC centrifugal fan

backward-curved, single-intake

## Technical description

| | |
|---|---|
| **Weight** | 2.8 kg |
| **Fan size** | 280 mm |
| **Rotor surface** | Painted black |
| **Impeller material** | Sheet steel, painted black |
| **Number of blades** | 11 |
| **Direction of rotation** | Clockwise, viewed toward rotor |
| **Degree of protection** | IP44; installation- and position-dependent as per EN 60034-5 |
| **Insulation class** | "F" |
| **Moisture (F) / Environmental (H) protection class** | H0+ |
| **Max. permitted ambient temp. for motor (transport/storage)** | + 80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | - 40 °C |
| **Installation position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensation drainage holes** | On rotor side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Speed levels** | 3 |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | < 0.75 mA |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **With cable** | Axial |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 60335-1; CE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan

backward-curved, single-intake

## Product drawing




| | |
|---|---|
| 1 | Accessory part: inlet ring 96360-2-4013 not included in scope of delivery |
| 2 | Max. clearance for screw 5 mm |
| 3 | Cable halogen-silicone-free 7G 0.5 mm², 4x splices and 3x flat push-on receptacle 6.3 x 0.8 mm (green/yellow, brown, yellow) crimped |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan

backward-curved, single-intake

## Connection diagram




Note: High speed (step III); low speed (step I)

| | | | | | |
|---|---|---|---|---|---|
| 1 | blue (N) | 2 | brown | 3 | yellow |
| 4 | Step 1 (white) | 5 | Step 2 (gray) | 6 | Step 3 (black) |
| 7 | L1 | 8 | PE (green/yellow) | | |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan

backward-curved, single-intake

## Curves: Air performance 50 Hz




Measurement: LU-30707-1
Measurement: LU-30708-1
Measurement: LU-30709-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | Stage | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 3 | 230 | 50 | 1410 | 78 | 0.35 | 1405 | 0 | 830 | 0.00 |
| 2 | 3 | 230 | 50 | 1380 | 86 | 0.39 | 1155 | 60 | 680 | 0.24 |
| 3 | 3 | 230 | 50 | 1360 | 92 | 0.41 | 850 | 120 | 500 | 0.48 |
| 4 | 3 | 230 | 50 | 1365 | 89 | 0.40 | 550 | 160 | 325 | 0.64 |
| 5 | 2 | 230 | 50 | 1310 | 68 | 0.29 | 1305 | 0 | 770 | 0.00 |
| 6 | 2 | 230 | 50 | 1195 | 82 | 0.35 | 995 | 45 | 585 | 0.18 |
| 7 | 2 | 230 | 50 | 1135 | 88 | 0.38 | 705 | 83 | 415 | 0.33 |
| 8 | 2 | 230 | 50 | 1140 | 86 | 0.37 | 460 | 113 | 270 | 0.45 |
| 9 | 1 | 230 | 50 | 1230 | 67 | 0.29 | 1210 | 0 | 715 | 0.00 |
| 10 | 1 | 230 | 50 | 1015 | 82 | 0.35 | 845 | 32 | 500 | 0.13 |
| 11 | 1 | 230 | 50 | 880 | 87 | 0.38 | 555 | 51 | 325 | 0.20 |
| 12 | 1 | 230 | 50 | 900 | 86 | 0.37 | 365 | 70 | 215 | 0.28 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_e$ = Power consumption · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com