G3G250-MW50-01

EC centrifugal fan

backward curved, single inlet

with housing (flange), Gas blower for gas-condensing heating



ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

Nominal data

Type	**G3G250-MW50-01**
Motor	**M3G112-EA**

Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
Speed	min^{-1}	6100
Power input	W	2400
Current draw	A	4.0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	+50
Min. temp. of flow medium	°C	-25
Max. temp. of flow medium	°C	+50

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.00

* Specific ratio = 1 + p_{fs} / 100 000 Pa

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}		59.8	51.3	54.3
Efficiency grade N		66.5	58	61
Power input P_{ed}	kW	2.29		
Air flow q_v	m^3/h	1165		
Pressure increase p_{fs}	Pa	4000		
Speed n	min^{-1}	6495		

Data established at point of optimum efficiency

ebmpapst

EC centrifugal fan

backward curved, single inlet

with housing (flange), Gas blower for gas-condensing heating

Technical features

Mass	22.3 kg
Size	250 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Housing material	Die-cast aluminium
Material of distancing profiles	Aluminium
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 20
Insulation class	"B"
Humidity class	F0
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Any
Cooling bore / aperture	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Tach output - Alarm relay - Motor current limit - PFC, passive - Soft start - Control input 0-10 VDC / PWM - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box
Motor protection	Thermal overload protector (TOP) wired internally
Protection class	I (if protective earth is connected by customer)
Approval	UL 1004-7 + 60730


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal fan

backward curved, single inlet

with housing (flange), Gas blower for gas-condensing heating

Product drawing



1	Cable diameter: min. 4 mm, max. 10 mm; tightening torque: 4±0.6 Nm


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal fan

backward curved, single inlet

with housing (flange), Gas blower for gas-condensing heating

Connection screen



No.	Pin	Signal	Function / assignment
1	1,2,3	L1,L2,L3	Power supply 3-phase, 50/60 Hz
		PE	Protective earth
2	1	NO	Alarm relay, make for failure
2	2	COM	Alarm relay, common connection (2A, 250VAC,AC1)
2	3	NC	Alarm relay, break for failure
3	PWM	PWM	Set value input via PWM; 16-45 V high level; 1-10 kHz; can be used exclusively as an alternative to connection 0-10 V
3	GND	GND	Signal ground for control interface
3	GND	GND	Signal ground for control interface
3	0 - 10 V	0 - 10 V	Analogue setpoint input, 0 - 10 V (impedance 100 kΩ), can be used exclusively as an alternative to connection PWM; for correct function, the PWM input must be bridged with GND.
3	+ 20 V	+ 20 V	Supply for external sensor; 20 VDC(±20%) max. 50 mA
3	+ 10 V	+ 10 V	Supply for external potentiometer, 10 VDC(±10%) max. 10 mA
3	Tach	Tach	Speed monitoring output; 12 VDC(±10%) max. 10 mA; impedance 1 kΩ; 4 pulses / revolution


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal fan

backward curved, single inlet

with housing (flange), Gas blower for gas-condensing heating

Charts: Air flow 50 Hz



Measurement: LU-130108

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P_{ed}	I	qv	p_{fs}
	V	Hz	min^{-1}	W	A	m^3/h	Pa
1	400	50	6315	2301	3.51	2185	0
2	400	50	6100	2400	3.65	1730	2000
3	400	50	6260	2343	3.51	1360	3400
4	400	50	6505	2063	3.13	935	4600
5	400	50	5500	1522	2.32	1900	0
6	400	50	5500	1755	2.67	1560	1628
7	400	50	5500	1588	2.38	1195	2617
8	400	50	5500	1247	1.89	790	3286
9	400	50	4500	834	1.27	1555	0
10	400	50	4500	961	1.46	1275	1090
11	400	50	4500	870	1.30	980	1752
12	400	50	4500	683	1.04	645	2200
13	400	50	3500	392	0.60	1210	0
14	400	50	3500	452	0.69	990	659
15	400	50	3500	409	0.61	760	1060
16	400	50	3500	321	0.49	500	1331

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com