W3G250-EC24-01

EC axial fan

with brushless DC motor

Automotive



ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	**W3G250-EC24-01**	
Motor	**M3G074-BA**	
Nominal voltage	VDC	26
Method of obtaining data		fa
Status		prelim.
Speed (rpm)	min^{-1}	2050
Power consumption	W	38
Current draw	A	1.45
Max. back pressure	Pa	85
Max. back pressure	in. wg	0.34
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	85

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

EC axial fan

with brushless DC motor

Automotive

Technical description

Weight	1.1 kg
Size	250 mm
Motor size	74
Blade material	PP plastic
Fan housing material	PA plastic
Number of blades	7
Airflow direction	V
Balancing grade according to DIN ISO 21940-11	G 10
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	Motor IP24 KM, electronics IP6K9K (mating connector installed)
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H4
Ambient temperature note	Above +70°C with temperature derating; External sources of heat above +85°C can affect the service life; Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), a fan design with special low-temperature bearings must be used.
Max. permitted ambient temp. for motor (transport/storage)	+85 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing; (sealed)
Life expectancy	40,000 h (typical)
Technical features	- Tach output - Power limiter - Load dump (58 V) - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Temperature derating - Thermal overload protection for electronics - Reverse polarity protection
Electrical hookup	Plug; Standby current less than 350 µA
Motor protection	Locked-rotor protection
Comment	E1 approval in preparation


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan

with brushless DC motor

Automotive

Product drawing



1	4-pole plug, pluggable with cable from accessories
1.1	PWM/LIN
1.2	Diagnostic output
1.3	+ UB
1.4	GND
	Accessory part: Cable (460 mm) with mating connector, part no. 02025-4-1021 not included in scope of delivery 4-pole mating connector TE 1-1418390-1, 2x socket TE 968857-1, 2x socket TE 968855-1, 2x seal TE 828905-1, 2x seal TE 828904-1
	Accessory part: Guard grill (18605-2-4039) not included in scope of delivery
2	Bayonet attachment (both sides) for sheet metal or plastic 1.5, 2.0 or 2.5 mm thick
	Alternatively four fastening holes in each case (on both sides)
	A detailed drawing of the recess required for bayonet attachment can be obtained from ebm-papst.
3	Airflow direction "V"


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan

with brushless DC motor

Automotive

Connection diagram



No.	Conn.	Designation	Function/assignment
	3	+	Power supply +
	1	0-10 V / PWM	Typical values Control input Ri > 36 kΩ 0-10 V: - < 1 V ⇒ n=0 - 1,5 V ⇒ n=min - > 9.5 V ⇒ n=max or PWM (> 10 V; 1-10 kHz): - < 4 % ⇒ n=0 - 10 % ⇒ n=min - > 95% ⇒ n=max
	2	Tacho	Tach output: open collector, 1 pulse per revolution, Isink max = 10 mA, Ri = 2.1 kΩ
	4	-	Power supply -


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan

with brushless DC motor

Automotive

Curves: Air performance



ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-179792-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	n	P_{ed}	I	LpA_{in}	LwA_{in}	q_V	p_{fs}	q_V	p_{fs}
	V	min^{-1}	W	A	dB(A)	dB(A)	m^3/h	Pa	cfm	in. wg
1	26	2050	38	1.45	59	67	1240	0	730	0.00
2	26	2020	42	1.61	58	66	1115	30	655	0.12
3	26	1990	45	1.72	58	66	975	60	575	0.24
4	26	1965	47	1.80	59	66	800	85	470	0.34

U = Voltage · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side · q_V = Air flow
p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com