**S4D400-AP26-71**

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **S4D400-AP26-71** |
| **Motor** | **M4D074-EI** |

| | | | |
|---|---|---|---|
| Phase | | 3~ | 3~ |
| Nominal voltage | VAC | 230 | 230 |
| Connection | | Y | Y |
| Frequency | Hz | 50 | 60 |
| Type of data definition | | fa | fa |
| Valid for approval / standard | | CE | CE |
| Speed (rpm) | $min^{-1}$ | 1400 | 1550 |
| Power input | W | 125 | 185 |
| Current draw | A | 0.5 | 0.55 |
| Max. back pressure | Pa | 95 | 105 |
| Min. ambient temperature | °C | -40 | -40 |
| Max. ambient temperature | °C | 70 | 45 |
| Starting current | A | 1.7 | 1.8 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

## Data according to ErP directive

| | | Actual | Request 2015 |
|---|---|---|---|
| 01 Overall efficiency $\eta_{es}$ | % | 35.7 | 28.8 |
| 02 Measurement category | | A | |
| 03 Efficiency category | | Static | |
| 04 Efficiency grade N | | 46.9 | 40 |
| 05 Variable speed drive | | No | |

| | | |
|---|---|---|
| 09 Power input $P_e$ | kW | 0.17 |
| 09 Air flow $q_v$ | $m^3/h$ | 2705 |
| 09 Pressure increase $p_{fs}$ | Pa | 83 |
| 10 Speed (rpm) n | $min^{-1}$ | 1320 |
| 11 Specific ratio* | | 1.00 |

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

LU-177558

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

## Technical features

| | |
|---|---|
| **Mass** | 6.2 kg |
| **Size** | 400 mm |
| **Surface of rotor** | Coated in black |
| **Material of terminal box** | PC/ABS plastic, black |
| **Material of blades** | Sheet steel, coated in black |
| **Material of guard grille** | Steel, phosphated and coated with black plastic |
| **Number of blades** | 5 |
| **Direction of air flow** | "V" |
| **Direction of rotation** | Counter-clockwise, seen on rotor |
| **Type of protection** | IP 44 |
| **Insulation class** | "F" |
| **Humidity (F)/environmental protection class (H)** | F2-2 |
| **Max. permissible ambient motor temp. (transp./ storage)** | + 70 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | - 40 °C |
| **Mounting position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensate discharge holes** | Rotor-side |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing with anti-freezing grease |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | < 0.75 mA |
| **Electrical leads** | Via terminal box |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Cable exit** | Variable |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 60335-1; CE |
| **Approval** | CSA C22.2 No.100; UL 1004-1 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Tightening torque 0.5±0.1 Nm |
| 3 | Cable diameter max. 7.5 mm, tightening torque 1.3±0.2 Nm |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

## Connection screen




Change direction of rotation by reversing two phases

| | |
|---|---|
| | Three-phase motor |
| Y | Star connection |
| 1 | Anti-clockwise operation |
| L1 | = V1 = blue |
| L2 | = U1 = black |
| L3 | = W1 = brown |
| 2 | Clockwise operation |
| L1 | =U1=black |
| L2 | =V1=blue |
| L3 | =W1=brown |
| PE | green / yellow |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

## Charts: Air flow 50 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-177558-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | Conn. | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | Y | 230 | 50 | 1400 | 125 | 0.50 | 3990 | 0 | 2350 | 0.00 |
| 2 | Y | 230 | 50 | 1355 | 150 | 0.53 | 3475 | 40 | 2045 | 0.16 |
| 3 | Y | 230 | 50 | 1330 | 168 | 0.57 | 2990 | 70 | 1760 | 0.28 |
| 4 | Y | 230 | 50 | 1310 | 182 | 0.59 | 2365 | 95 | 1395 | 0.38 |

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · $P_e$ = Power input · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

sickled blades (S series)

with guard grille for short nozzle

## Charts: Air flow 60 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-177625-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | Conn. | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | Y | 230 | 60 | 1550 | 185 | 0.55 | 4470 | 0 | 2630 | 0.00 |
| 2 | Y | 230 | 60 | 1505 | 210 | 0.63 | 3990 | 35 | 2350 | 0.14 |
| 3 | Y | 230 | 60 | 1455 | 234 | 0.70 | 3440 | 70 | 2025 | 0.28 |
| 4 | Y | 230 | 60 | 1395 | 258 | 0.76 | 2575 | 105 | 1515 | 0.42 |

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · $P_e$ = Power input · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com