
MAER	Product model	YZF45L45P4-34
	product type	Shaded pole motor
	customer code	/
	Product number	/
	certification	CE,CCC

Rotation direction of motor



Technical requirement

1. motor components should be assembled with no oil or dirt on the surface, no apparent distortion, mechanical damage and other defects.
2. motor rotation is flexible, no card stagnation, running sound, fixed rotor without edge and other bad phenomena.
3. fan safety requirements according to GB12350-2009, electrical strength of 1500. Min; the insulation level resistance at room temperature is not less than 100MΩ.
4. The size of outgoing wire is 0.5mm², and the color of three-core wire is brown, blue and yellow green ground wire.（引出线规格0.5mm²，三芯线颜色为棕、蓝、黄绿地线）
5. The movement clearance of the motor is 1-1.5mm.（电机窜动间隙1-1.5mm）
6. The shipping mark shall be affixed to the upper left corner of the packing box.（唛头贴在包装箱左上角）
7. Tighten the bracket nut.（支架螺母打紧）
8. insulation grade of motor: CLASS B. level of motor protection IP42.
9. environment temperature: -25 ℃ ~40 ℃.
10. The line is 0.75m long.（线长0.75米）

MAER MOTORS & FANS SHADED POLE MOTOR

MODEL:YZF45L45P4-34
VOLTAGE:220V/50Hz
N. W/G. W. 24/24. 5KG
MEAS:44. 5X34. 5X12. 5 CM
Quantity:12
CL. B xxxxxxx

Nameplate:

YZF45L45P4-34
220V/50Hz 110W 0.85A 1300r/min
CL.B IP42 2022/11

Main motor parameters:

Motor model	UAC (V) ±5%	f (Hz)	P2 (W)	P1 (W)	I (A)	n (r/min)
YZF45L45P4-34	220	50	34	110	0.85	1300

版本/Ver.		Page		
重量/WG.	Kg	签名/Name	日期/Date	
绘图/Drawing				
审核/Checked				
批准/Approved				
客户确认/Customer confirmation				

浙江马尔风机有限公司
MAER Fan Motor ZHEJIANG MAER FAN MOTOR CO.,LTD.

产品规格书
Product Specification

型号/Model	YZF45L45P4-34
品号 P/N	