4114 N/2H6P-304

Customer specification: No
Version: 1.1
Created: 12.08.2010

technical project manager:	responsible for technical design:	responsible for electronical design:
Langeneck, Gunter, 560	Kieninger, Annemarie, 560	Langeneck, Gunter, 560

INDEX

1 General 2
2 Mechanics 2
2.1 General 2
2.2 Motor 2
2.3 Connections 3
3 Operating Data 4
3.1 Operating Data - Electrical Interface - Input 4
3.2 Electrical Operating Data 5
3.3 Operating Data - Electrical Interface -Output 6
3.4 Electrical Features 7
3.5 Aerodynamic 8
3.6 Sound Data 8
4 Environment 8
4.1 General 9
4.2 Climatic requirements 9
4.3 Mechanical requirements 9
4.4 EMC 9
5 Safety 9
5.1 Electrical Safety 9
5.2 Approval Tests 9
6 Reliability 10
6.1 General 10
6.2 Additional Data 10

Special features according to QMH 2-5.4.7 and company standard 1-23.00 have the following definitions:

"A" : Product features or process parameters which influence the safety of a product or the compliance of legal requirements. (Must not necessary verified and documented 100%. Standards and legal requirements must be considered.)

"FK" : Product features or process parameters which influence the fit and function of a product or which have to be controlled or documented for some other reasons (e.g. Customer requirements).

1 General

Fan type	Fan	
Rotational direction looking at rotor	clockwise	**FK**
Airflow direction	Air intake over struts	**FK**
Bearing system	Ball bearing	
Lubrication	see sectional drawing of the bearing	
Mounting position Tolerance	any	
Balancing grade	6,3	**FK**
Impeller weight	125,0 g	

2 Mechanics

2.1 General

Width	119,0 mm	
Height	119,0 mm	
Depth	38,0 mm	
Diameter	0,0 mm	
Weight	0,390 kg	
Housing material	Metal	
Impeller material	Plastic	


2.2 Motor

Type of motor	Electronically commutated external rotor	
Diameter of the motor	43,0 mm	
Height of the motor	10,5 mm	
Number of phases	1	
Number of windings	1	
Operating mode	Continuous duty	
Insulation material class	E	

2.3 Connections

Electrical connection	Wires	
Length of lead wire Tolerance	310 mm +- 10,0 mm	
Length of tube Tolerance		
Wire gauge (AWG)	22	
Insulation diameter	1,70 mm	
Plug	see drawing	
Contact	see drawing	





	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	violet	PWM
Wire 4	white	Tacho

The auxiliary shown on the schematic diagram which are required for the intended use are not part of our delivery.

3 Operating Data


3.1 Operating Data - Electrical Interface - Input

Control input	PWM


Features

Inpute type	Open collector	
PWM - Frequency		1 kHz - 10 kHz Typical: 2 kHz

Characteristics



Schematics



Speed control: 0...100 % PWM; 5 V pull-up, max 2 mA

Transistor requirements: VCEmax. >12V; Isink max. >5mA;

VCEsat <0,15V

3.2 Electrical Operating Data

Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area there may not be any solid obstruction within 0,5 m.

Δp = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

Name	**Condition**		
PWM 0001	PWM: 100 %; f: 2 kHz		

Features	**Condition**	**Symbol**	**Values**		
Voltage range	Δp = 0	U	16,0 V		30,0 V
Nominal voltage	Δp = 0	U_N		24,0 V	
Power consumption Tolerance	Δp = 0 PWM 0001	P	29,0 W +- 15,0 %	62,0 W +- 15,0 %	62 W +- 15,0 %
Current consumption Tolerance	Δp = 0 PWM 0001	I	1.810 mA +- 15,0 %	2.580 mA*) +- 15,0 %	2.065 mA +- 15,0 %
Speed Tolerance	Δp = 0 PWM 0001	n	6.400 1/min +- 10,0 %	8.400 1/min*) +- 10,0 %	8.400 1/min +- 10,0 %
Starting current consumption				5.000 mA	
Typical current curve (A = least and B = largest current curve in a revolution) A and B = neighboring current curves MPE 891001				1,0 <= A B <= 1,3	

****)**
To note inrush current @ U nom:
The internal electrolytic capacitor 120uF / 50V
has no resistor or inrush current limitation,
essentially the type and length of the connecting cable is limiting the Inrush current.

Name	**Condition**		
PWM 0002	PWM: 50 %; f: 2 kHz		

Features	**Condition**	**Symbol**	**Values**		
Voltage range	Δp = 0	U	16,0 V		30,0 V
Nominal voltage	Δp = 0	U_N		24,0 V	
Power consumption Tolerance	Δp = 0 PWM 0002	P	11,6 W +- 15,0 %	11,8 W +- 15,0 %	12,2 W +- 15,0 %
Current consumption Tolerance	Δp = 0 PWM 0002	I	725 mA +- 15,0 %	490 mA*) +- 15,0 %	405 mA +- 15,0 %
Speed Tolerance	Δp = 0 PWM 0002	n	4.400 1/min +- 10,0 %	4.400 1/min*) +- 10,0 %	4.400 1/min +- 10,0 %

Name	Condition		
PWM 0003	PWM: 8 %; f: 2 kHz		

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	16,0 V		30,0 V
Nominal voltage	Δp = 0	U_N		24,0 V	
Power consumption Tolerance	Δp = 0 PWM 0003	P	1,2 W +- 15,0 %	1,4 W +- 15,0 %	1,7 W +- 15,0 %
Current consumption Tolerance	Δp = 0 PWM 0003	I	75 mA +- 15,0 %	60 mA*) +- 15,0 %	55 mA +- 15,0 %
Speed Tolerance	Δp = 0 PWM 0003	n	1.000 1/min +- 10,0 %	1.000 1/min*) +- 10,0 %	1.000 1/min +- 10,0 %


Name	Condition		
PWM 0004	PWM: 0 %; f: 2 kHz		

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	16,0 V		30,0 V
Nominal voltage	Δp = 0	U_N		24,0 V	
Power consumption Tolerance	Δp = 0 PWM 0004	P	< 0,5 W	< 0,3 W	< 0,4 W
Current consumption Tolerance	Δp = 0 PWM 0004	I	< 15 mA	< 15 mA*)	< 15 mA
Speed Tolerance	Δp = 0 PWM 0004	n	0 1/min	0 1/min*)	0 1/min

*) Attention: Marked values are "FK" features

3.3 Operating Data - Electrical Interface -Output

Tacho type	/2 (Open collector)



$$Ra = \frac{UBS - US\ Low}{I\ Sink}$$


Features	Note	Values
Tacho operating voltage (UBS)		<= 60 V
Tacho signal Low *)	I sink: 2 mA	<= 0,4 V
Tacho signal High *)	I source: 0 mA	60 V
Maximum sink current		<= 10 mA
External resistor	External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency *)	(2 x n) / 60	
Tacho isolated from motor	No	
Slew rate of the tacho output voltage		=> 0,5 V/us

*) Attention: Marked values are "FK" features

Alarm type	None

3.4 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection Max. residual current at Un	Polarity protected diode IF <= 10 mA	**A**
Locked rotor protection	Electronically restart	**A**
Locked rotor current at Un	approx. 1.850 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,5 s / 5,0 s t3: 0,4 s... 0,6 s t4: 4,8 s... 5,2 s	



Max. current when decelerate @ Unom = 11A (peak/peak)

3.5 Aerodynamic

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN 24163 Part 3. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area there may not be any solid obstruction within 0,5 m.

a.) Operation condition:

8.400 1/min at free air flow	PWM 100 %; f: 2 kHz		

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	440,0 m3/h	**FK**
Max. static pressure (Δp = max. / $\dot{V}$ =0)	670 Pa	**FK**

3.6 Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

8.400 1/min at free air flow	PWM 100 %; f: 2 kHz	PWM min.:	PWM max.:

Optimal operating point	340,0 m3/h @ 236,0 Pa	
Sound power level at the optimal operating point	8,1 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	73,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	65 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic requirements*)

*) Permittet application area:
The product is for the use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoid.

4.3 Mechanical requirements

not specified

4.4 EMC

not specified

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 500 VAC / 1 Sec.	**A**
Insulation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Air and leakage distances	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests

CE	No
UL	Yes / UL507, Electric Fans
VDE	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment - Part 1 Safety - Connection to a SELV circuit.
CSA	Yes / C22.2 No. 113-M1984 Fans and Ventilators
CCC	No

The approval tests are observed to:
U approval max.:30,0 V @ TU approval max.: 65,0 °C

6 Reliability

6.1 General

Life expectancy L10 at TU = 20 °C		
Life expectancy L10 at TU = 40 °C	62.500 hrs	
Life expectancy L10 at TU = 60 °C		
Life expectancy L10 at TU max.	35.000 hrs	
Life expectancy L15 at TU = 45 °C		
Life expectancy L10 Delta (40 °C)	125.000 hrs	

6.2 Additional Data

not specified