8317087810 Sample

VMA0350HSNFS

EC axial panel fan - HyBlade

sickle-shaped blades (S series)

with guard grille for short nozzle

ebm-papst Ventilator (Xi'an) Co.,Ltd.
No.2555, No.5 Weishui Road, Weibei Industry Park, Lintong District,
Xi'an, China, 710605
Phone: +86(0)29-81366100
www.ebmpapst.com

Nominal data

Item	**8317087810**
Motor	**E07436-29**

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 240
Frequency	Hz	50/60
Method of obtaining data		ml
Status		prelim.
Speed (rpm)	min^{-1}	1510
Power consumption	W	170
Current draw	A	1.3
Max. back pressure	Pa	103
Max. back pressure	in. wg	0.41
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Preliminary

Data according to Commission Regulation (EU) 327/2011 (prEN 17166)

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	38.7	28.8
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		55.4	40
05 Variable speed drive		Yes	

09 Power consumption P_{ed}	kW	0.17
09 Air flow q_v	m^3/h	2375
09 Pressure increase p_{fs}	Pa	100
10 Speed (rpm) n	min^{-1}	1510
11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + p_{fs} / 100 000 Pa

ID-19753

8317087810 Sample

VMA0350HSNFS

EC axial panel fan - HyBlade

sickle-shaped blades (S series)

with guard grille for short nozzle

Technical description


Size	350 mm
Motor size	74
Rotor surface	Thick-film passivated
Electronics housing material	Die-cast aluminum
Impeller material	Press-fitted sheet steel blank, sprayed with PP plastic
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Airflow direction	V
Direction of rotation	Counterclockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Tach output - Power limiter - Motor current limitation - Soft start - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage detection
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Locked-rotor detection
With cable	Variable
Protection class assignment	I; If a protective earth is connected by the customer This component for installation may have several local protection classes. This information relates to this component's basic design. The final protection class is based on the component's intended installation and connection.
Conformity with standards	GB12350, CCC; CE

Preliminary

EC axial panel fan - HyBlade

sickle-shaped blades (S series)
with guard grille for short nozzle

Product drawing




Preliminary

1	Airflow direction "V"
2	Supply line (PWR) PVC AWG20
	3x splice
3	Control wire (CTRL) PVC AWG22
	4x splice

EC axial panel fan - HyBlade

sickle-shaped blades (S series)
with guard grille for short nozzle

Connection diagram




Preliminary

No.	Conn.	Designation	Color	Function/assignment
	CON10	L	black	Supply connection, power supply, phase, see nameplate for voltage range
	CON11	N	blue	Supply connection, power supply, neutral conductor, see nameplate for voltage range
	CON12	PE	green/yellow	Protective earth
	3	+10 V	red	Fixed voltage output 10 VDC +/-3 %, Imax. 10 mA, short-circuit-proof, power supply for ext. devices (e.g. pot), SELV
	2	0-10V / PWM	yellow	0-10 V / PWM control input, Ri=100 kΩ, SELV
	1	GND	blue	Reference ground for control interface, SELV
	4	Tach	white	Tach output, open collector, 1 pulse per revolution, Isink max = 10 mA, SELV

EC axial panel fan - HyBlade

sickle-shaped blades (S series)
with guard grille for short nozzle

Curves: Air performance 50 Hz



ρ = 1.2 kg/m³ ± 2 %

Measurement: LU-19753
Date:20250403
Housing:18901-2-4037

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Preliminary

Measured values

	U	f	n	P1	I	qv	pfs	qv	Pfs
	V	Hz	min-1	W	A	m³/h	Pa	cfm	in.wg
1	230	50	1650	166	1.2	3862	0	2275	0.00
2	230	50	1595	168	1.2	3431	35	2021	0.14
3	230	50	1547	169	1.2	2939	70	1731	0.28
4	230	50	1508	170	1.3	2293	103	1351	0.41
5	230	50	1450	113	0.8	3394	0	1999	0.00
6	230	50	1450	127	0.9	3121	29	1838	0.12
7	230	50	1450	140	1.0	2756	61	1623	0.24
8	230	50	1450	151	1.1	2205	95	1299	0.38
9	230	50	1200	64	0.5	2808	0	1654	0.00
10	230	50	1200	72	0.5	2583	20	1521	0.08
11	230	50	1200	79	0.6	2281	42	1344	0.17
12	230	50	1200	85	0.6	1825	65	1075	0.26
13	230	50	950	32	0.2	2223	0	1309	0.00
14	230	50	950	36	0.3	2045	13	1205	0.05
15	230	50	950	39	0.3	1805	26	1063	0.10
16	230	50	950	42	0.3	1445	41	851	0.16

U = Voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · q_V = Air flow · p_{fs} = Pressure increase