Product Data Sheet | 8452/2 GN



The engineer's choice

ebmpapst

8452/2 GN

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 5

3.1 Operating Data - Electrical Interface - Input 5
3.2 Electrical Operating Data 6
3.3 Operating Data - Electrical Interface -Output 6
3.4 Electrical Features 7
3.5 Aerodynamic 8
3.6 Sound Data 8

4 Environment 8

4.1 General 8
4.2 Climatic requirements*) 8
4.3 EMC 9

5 Safety 11

5.1 Electrical Safety 11
5.2 Approval Tests 11

6 Reliability 11

6.1 General 11

1 General

Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	
Airflow direction	Air outlet over struts	
Bearing system	Sleeve bearing	
Mounting position	horizontal/vertical rotor up	


2 Mechanics

2.1 General

Width	80,0 mm	
Height	80,0 mm	
Depth	25,0 mm	
Weight	0,110 kg	
Housing material	Plastic	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges Screw size	wire outlet corner: 30 Ncm remaining corners: 50 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Length of lead wire Tolerance	L = 310 mm +- 10,0 mm	
Wire gauge (AWG)	24	
Insulation diameter	1,55 mm	
Contact	see drawing	



	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	white	Tacho

The auxilliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.

3 Operating Data

3.1 Operating Data - Electrical Interface - Input

Control input	None

3.2 Electrical Operating Data


Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area should not be any solid obstruction within 0,5 m.

Δp = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	8,0 V		15,0 V
Nominal voltage	Δp = 0	U_N		12,0 V	
Power consumption Tolerance	Δp = 0 0001	P	0,7 W +- 17,5 %	1,8 W +- 12,5 %	2,9 W +- 15,0 %
Current consumption Tolerance	Δp = 0 0001	I	90 mA +- 17,5 %	150 mA +- 12,5 %	190 mA +- 15,0 %
Speed Tolerance	Δp = 0 0001	n	2.500 1/min +- 12,5 %	3.600 1/min +- 7,5 %	4.200 1/min +- 10,0 %
Starting current consumption				500 mA	

3.3 Operating Data - Electrical Interface -Output

Tacho type	/2 (Open collector)




$$Ra = \frac{UBS - US\ Low}{I\ Sink}$$

Features	Note	Values
Tacho operating voltage (UBS)		<= 28 V
Tacho signal Low	I sink: 2 mA	<= 0,4 V
Tacho signal High	I source: 0 mA	28 V
Maximum sink current		<= 4 mA
External resistor	External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency	(2 x n) / 60	120 Hz
Tacho isolated from motor	No	
Slew rate		=> 0,5 V/us

Alarm type	None

3.4 Electrical Features

Electronic function	None	
Reversed polarity protection Max. residual current at Un	Rectifying diode IF <= 10 mA	
Locked rotor protection	Auto restart	
Locked rotor current at Un	approx. 500 mA	
Clock signal t3/t4 at locked rotor	Typical: 0,27 s / 1,2 s t3: 0,11 s... 0,67 s t4: 0,41 s... 3,8 s	



3.5 Aerodynamic

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

3.600 1/min at free air flow

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	68,0 m3/h	
Max. static pressure (Δp = max. / $\dot{V}$ =0)	45 Pa	

3.6 Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

3.600 1/min at free air flow

Optimal operating point	52,0 m3/h @ 14 Pa	
Sound power level at the optimal operating point	5,1 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	35,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	70 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic requirements*)

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Dust requirements	None	
Salt fog requirements	None	

*) Permittet application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly

exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

Please require severity levels and specification parameters from the responsible development departments

4.3 EMC

Kind	**Conducted Emission; Voltage; 150 kHz-30 MHz**
According	DIN EN 55022:2007-04
Ceck accuracy / Limit	Class B
Measurement setup - Source	EUT connected with LISN CISPR 16
Measurement setup - Input	Open
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state with maximum emission within range of normal use, free air flow.
Monitoring	Speed
Result	Below limit Class B

According	DIN EN 55022:2007-04
Ceck accuracy / Limit	Class B
Measurement setup - Source	GHz-TEM-cell
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state with maximum emission within range of normal use, free air flow.
Monitoring	Speed
Result	Below limit Class B

Kind	**Electrostatic Discharge Immunity Test**
According	DIN EN 61000-4-2:2001-12
Ceck accuracy / Limit	Contact Discharge +/- 4 kV; Air Discharge +/- 8 kV
Measurement setup - Source	Tabletop unit
Measurement setup - Output	Active
Measurement setup - Earthing	ungrounded
Operating mode	Operating state within range of normal use (time dominant operating state); free air flow
Monitoring	Speed
Result	A: The monitored function operates as designed during and after exposure to a disturbance.

Kind	**Electromagnetic Field Immunity Test**
According	DIN EN 61000-4-3:2006-12
Ceck accuracy / Limit	10 V/m; 80 - 1000 MHz; m = 0,8; f = 1 kHz; 1%; t = 3 s
Measurement setup - Source	GHz-TEM-cell
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state within range of normal use (time dominant operating state); free air flow
Monitoring	Speed
Result	A: The monitored function operates as designed during and after exposure to a disturbance.

Kind	Electrical Fast Transient / Burst Immunity Test
According	DIN EN 61000-4-4:2005-07
Ceck accuracy / Limit	+/- 2 kV on Power Lines; Coupling: POS, NEG, {PE}, ALL, 5 kHz and 100 kHz; 1 min
Measurement setup - Source	By capacitive coupling clamp
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state within range of normal use (time dominant operating state); free air flow
Monitoring	Speed
Result	A: The monitored function operates as designed during and after exposure to a disturbance.

Kind	Electrical Fast Transient / Burst Immunity Test
According	DIN EN 61000-4-4:2005-07
Ceck accuracy / Limit	+/- 1 kV on Power Lines; 5 kHz / 100 kHz; 1 min
Measurement setup - Source	EUT connected with generator
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state within range of normal use (time dominant operating state); free air flow
Monitoring	Speed
Result	A: The monitored function operates as designed during and after exposure to a disturbance.

Kind	Immunity to Conducted Disturbances, Induced by RF-Fields
According	DIN EN 61000-4-6:2001-12
Ceck accuracy / Limit	10 Vrms; 150 kHz - 80 MHz; m = 0,8; f = 1 kHz; 1%; t = 3 s
Measurement setup - Source	Test item via CDN
Measurement setup - Output	Open
Measurement setup - Earthing	ungrounded
Operating mode	Operating state within range of normal use (time dominant operating state); free air flow
Monitoring	Speed
Result	A: The monitored function operates as designed during and after exposure to a disturbance.

The information to the EMC corresponding only to a summary of a comprehensive test report.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 500 VAC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
clearance / creepage distance	1,0 mm / 1,2 mm	
Protection class	III	

5.2 Approval Tests


CE	Yes
UL	Yes / UL audited by CSA according to UL507, Electric Fans
VDE	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Yes / C22.2 No. 113 Fans and Ventilators
CCC	No

The approval tests are observed to:
Maximal permitted operating voltage (see section 3.1) and max. permitted ambient temperature TU max.

6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	70.000 h	
Life expectancy L10 at TU max.	35.000 h	
Life expectancy L10 Delta (40 °C)	140.000 h	



1) Maße für Montagewand