K3G310-AY90-N1

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	**K3G310-AY90-N1**
Motor	**M3G112-EA**

Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Method of obtaining data		ml
Speed (rpm)	min^{-1}	3000
Power consumption	W	1200
Current draw	A	1.8
Min. ambient temperature	°C	-40
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

Technical description

Weight	17.9 kg
Fan size	310 mm
Rotor surface	Painted black
Electronics housing material	Die-cast aluminum
Impeller material	Sheet aluminum
Support plate material	Sheet steel, galvanized and painted black
Spacer material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Inlet nozzle material	Sheet steel, galvanized
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP55; installation- and position-dependent
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H3
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensation drainage holes	On rotor side
Mode	S1
Motor bearing	Ball bearing; (sealed)
Technical features	- Output 10 VDC, max. 10 mA - Alarm relay - Integrated PID controller - Run monitoring - Power limiter - Motor current limitation - Emergency operation - PFC, passive - RS-485 MODBUS-RTU - Soft start - EEPROM write cycles: 100,000 maximum - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Overvoltage detection - Thermal overload protection for electronics/motor - Line undervoltage / phase failure detection
EMC regulations	According to EN 50121-3-2
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Motor protection	Thermal overload protector (TOP) internally connected
With cable	Lateral
Protection class	I (with customer connection of protective earth)
Conformity with standards	EN 15085-1, CPC3: 2013; EN 45545-2, HL3: 2013; EN 50121-3-2: 2006; EN 50155: 2008; EN 61373, Cat. 1B: 2010

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

Comment	A prerequisite for operation is a Class 1 vehicle electrical system architecture according to EN 50533; if supply potential (e.g. 230 VAC) is passed through the alarm relay, the SELV signal wires lose their property of reinforced insulation and they then have only basic insulation The SELV property (reinforced insulation) is not lost when voltages of up to 110 VDC are passed through the alarm relay.


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

Product drawing



1	Cable halogen-free, BETAtrans® 3 GKW flex, 4G 1.5 mm², 4x crimped ferrules
2	Cable halogen-free, BETAtrans® 3 GKW flex, 7x 0.5 mm², 7x crimped ferrules
3	Connector housing Harting 19 20 003 1250 with connector housing Harting 09 12 007 3001
3.1	not used
3.2	not used
3.3	L2
3.4	L3
3.5	L1
3.6	PE
4	Connector housing Harting 19 20 003 1250 with pin insert Harting 09 20 005 3001
4.1	GND
4.2	0-10 V
4.3	RSB
4.4	+10 V
4.5	RSA
4.6	COM
4.7	NC


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

Connection diagram



No.	Conn.	Designation	Function/assignment
1	1, 2	PE	Protective earth
1	3	L1	Power supply, phase
1	4	L2	Power supply, phase
1	5	L3	Power supply, phase
2	6	COM	Status relay, floating status contact, common connection, contact rating 250 VAC / 30 VDC 5 A minimum contact separation 1 mA / 5 VDC, reinforced insulation on supply side, basic insulation on control interface side
2	7	NC	Status relay, floating status contact, break for failure, contact rating 250 VAC / 30 VDC 5 A minimum contact separation 1 mA / 5 VDC, reinforced insulation on supply side, basic insulation on control interface side
2	8	0-10 V	Analog input (set value) SELV, 0-10 V, Ri = 100 kΩ, adjustable curve
2	10	RSB	RS485 interface for MODBUS, RSB; SELV
2	11	RSA	RS485 interface for MODBUS, RSA; SELV
2	12	GND	Reference ground for interface, SELV
2	13	+10 V	Fixed voltage output 10 VDC, SELV, +10 V +/-3%, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometers)


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward-curved, single-intake

with support structure, for rail applications

Curves: Air performance 50 Hz



ρ = 1.173 kg/m³ ± 2 %

Measurement: LU-177434-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	U	f	n	P_{ed}	I	LpA_{in}	LwA_{in}	LwA_{out}	q_V	p_{fs}	q_V	p_{fs}
	V	Hz	min^{-1}	W	A	dB(A)	dB(A)	dB(A)	m^3/h	Pa	cfm	in. wg
1	400	50	3000	861	1.33	83	91	95	4100	0	2415	0.00
2	400	50	3000	1054	1.61	78	86	91	3290	500	1935	2.01
3	400	50	3000	1200	1.80	78	87	90	2380	950	1400	3.81
4	400	50	3000	1088	1.66	79	88	92	1605	1100	945	4.42
5	400	50	2600	558	0.86	80	88	92	3550	0	2090	0.00
6	400	50	2600	683	1.05	74	82	87	2845	374	1675	1.50
7	400	50	2600	770	1.18	75	83	86	2060	709	1215	2.85
8	400	50	2600	706	1.08	75	84	88	1390	826	820	3.32
9	400	50	2200	338	0.52	75	83	88	3005	0	1765	0.00
10	400	50	2200	414	0.63	70	78	83	2410	268	1415	1.08
11	400	50	2200	467	0.71	70	79	82	1745	507	1025	2.04
12	400	50	2200	428	0.65	71	80	84	1175	591	690	2.37
13	400	50	1800	185	0.29	70	78	83	2455	0	1445	0.00
14	400	50	1800	227	0.35	65	73	78	1970	179	1160	0.72
15	400	50	1800	256	0.39	65	74	77	1425	340	840	1.36
16	400	50	1800	234	0.36	66	75	79	960	396	565	1.59

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_V = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com