W3GZ50-EF02-01

EC axial fan - HyBlade

sickled blades (S series)

Round full nozzle with diffuser

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

Nominal data

Type	**W3GZ50-EF02-01**	
Motor	**M3G200-QA**	
Phase		3~
Nominal voltage	VAC	400
Nominal voltage range	VAC	380 .. 480
Frequency	Hz	50/60
Type of data definition		ml
State		prelim.
Speed (rpm)	min^{-1}	820
Power input	W	6000
Current draw	A	9.2
Max. back pressure	Pa	295
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

		Actual	Request 2015
01 Overall efficiency η_{es}	%	54.7	38.4
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		56.3	40
05 Variable speed drive		Yes	

09 Power input P_{ed}	kW	5.6
09 Air flow q_v	m^3/h	42355
09 Pressure increase p_{fs}	Pa	250
10 Speed (rpm) n	min^{-1}	820
11 Specific ratio*		1.00

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

* Specific ratio = 1 + p_{fs} / 100 000 Pa

LU-165207

EC axial fan - HyBlade

sickled blades (S series)

Round full nozzle with diffuser

Technical features

Mass	193 kg
Size	1250 mm
Surface of rotor	Coated in black
Material of terminal box	PC plastic
Material of electronics housing	Die-cast aluminium, coated in black
Material of blades	Die-cast aluminium
Material of mounting ring	Steel, coated in black plastic (RAL 9005)
Material of wall ring	Sheet steel, galvanised and coated in black plastic (RAL 9005)
Material of guard grille	Steel, coated in black plastic (RAL9005)
Material of outer diffuser	Sheet steel, galvanised and coated in black plastic (RAL 9005)
Material of inner diffuser including lid	Sheet steel, galvanised and coated in black plastic (RAL 9005)
Number of blades	5
Blade angle	-5°
Direction of air flow	"V"
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 54
Insulation class	"F"
Humidity (F)/environmental protection class (H)	H2
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Output 10 VDC, max. 10 mA - Output 20 VDC, max. 50 mA - Output for slave 0-10 V - Input for sensor 0-10 V or 4-20 mA - External 24 V input (programming) - External release input - Alarm relay - Integrated PID controller - Motor current limit - PFC, passive - RS485 MODBUS RTU - Soft start -Maximum EEPROM write cycles 100,000 - Control input 0-10 VDC / PWM - Control interface with SELV potential safely disconnected from the mains - Over-temperature protected electronics / motor - Line undervoltage / phase failure detection
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	Via terminal box

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan - HyBlade

sickled blades (S series)

Round full nozzle with diffuser

Motor protection	Reverse polarity and locked-rotor protection
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	UL 1004-7 + 60730; C22.2 Nr.77 + CAN/CSA-E60730-1; EAC


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan - HyBlade

sickled blades (S series)

Round full nozzle with diffuser

Product drawing



1	Direction of air flow "V"
2	Tightening torque 1.7±0.2 Nm
3	Cable diameter min. 6 mm, max. 12 mm, tightening torque 4±0.6 Nm
4	Cable diameter min. 9 mm, max. 16 mm, tightening torque 4±0.6 Nm


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan - HyBlade


sickled blades (S series)

Round full nozzle with diffuser

Connection screen



KL 1



KL 2

No.	Conn.	Designation	Function / assignment
KL 1		L1	Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz
KL 1		L2	Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz
KL 1		L3	Mains connection, power supply 3-phase 380-480 VAC; 50/60 Hz
KL 1		PE	Earth connection, PE connection
KL 2		RSA	Bus connection RS-485, RSA, MODBUS RTU; SELV
KL 2		RSB	Bus connection RS-485, RSB, MODBUS RTU; SELV
KL 2		GND	Reference earth for control interface; SELV
KL 2		Din1	Digital input 1 enabling of electronics, Enabling: Pin open or applied voltage 5-50 VDC Disabling: Bridge to GND or applied voltage <1 VDC Reset function: Triggering of software reset after level change to <1 V; SELV
KL 2		+ 10 V	Fixed voltage output 10 VDC, +10 V ±3%, max. 10 mA, short-circuit-proof, power supply for external devices (e.g. potentiometers); SELV
KL 2		Ain1 U	Analogue input 1, set value: 0-10 V, Ri = 100 kΩ, parametrizable curve; SELV
KL2		COM	Status relay; floating status contact; changeover contact; common connection; contact rating 250 VAC / max. 2 A (AC1) / min. 10 mA
KL2		NC	Status relay, floating status contact; NC contact for faults


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC axial fan - HyBlade

sickled blades (S series)

Round full nozzle with diffuser

Charts: Air flow 50 Hz



ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-165207-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Conn.	U	f	n	P_{ed}	I	LpA_{in}	LwA_{in}	LwA_{out}	q_V	p_{fs}	q_V	p_{fs}
		V	Hz	min^{-1}	W	A	dB(A)	dB(A)	dB(A)	m^3/h	Pa	cfm	inH2O
1	3~ BRUE	400	50	820	3204	4.96	78	86	87	64690	0	38075	0.00
2	3~ BRUE	400	50	820	4201	6.44	75	83	84	57310	100	33730	0.40
3	3~ BRUE	400	50	820	5115	7.79	78	85	86	48005	200	28255	0.80
4	3~ BRUE	400	50	820	6000	9.20	86	94	95	33980	295	20000	1.18
5	3~ BRUE	400	50	750	2407	3.73	76	84	85	58810	0	34615	0.00
6	3~ BRUE	400	50	750	3180	4.87	73	81	82	52220	84	30735	0.34
7	3~ BRUE	400	50	750	3871	5.90	75	83	84	43750	167	25750	0.67
8	3~ BRUE	400	50	750	4552	6.92	84	91	93	30945	243	18215	0.98
9	3~ BRUE	400	50	650	1567	2.43	72	80	81	50965	0	30000	0.00
10	3~ BRUE	400	50	650	2070	3.17	69	77	78	45255	63	26635	0.25
11	3~ BRUE	400	50	650	2520	3.84	72	79	80	37915	125	22315	0.50
12	3~ BRUE	400	50	650	2963	4.51	80	88	89	26820	183	15785	0.73
13	3~ BRUE	400	50	550	949	1.47	68	76	77	43125	0	25385	0.00
14	3~ BRUE	400	50	550	1254	1.92	65	73	74	38295	45	22540	0.18
15	3~ BRUE	400	50	550	1527	2.33	67	75	76	32085	90	18885	0.36
16	3~ BRUE	400	50	550	1795	2.73	76	84	85	22695	131	13355	0.53

Conn. = Connection · U = Supply voltage · f = Frequency · n = Speed (rpm) · P_{ed} = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · LwA_{in} = Sound power level inlet side LwA_{out} = Sound power level outlet side · q_V = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com