**S6D710-AH01-01**

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner: Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

## Nominal data

| | |
|---|---|
| **Type** | **S6D710-AH01-01** |
| **Motor** | **M6D138-HF** |

| | | | | | |
|---|---|---|---|---|---|
| Phase | | 3~ | 3~ | 3~ | 3~ |
| Nominal voltage | VAC | 400 | 400 | 480 | 480 |
| Connection | | **Δ** | Y | **Δ** | Y |
| Frequency | Hz | 50 | 50 | 60 | 60 |
| Type of data definition | | ml | ml | ml | ml |
| Valid for approval / standard | | CE | CE | CE | CE |
| Speed | $min^{-1}$ | 905 | 730 | 1060 | 780 |
| Power input | W | 1030 | 690 | 1700 | 1030 |
| Current draw | A | 2.35 | 1.34 | 2.87 | 1.72 |
| Max. back pressure | Pa | 125 | 80 | 170 | 92 |
| Max. ambient temperature | °C | 80 | 80 | 60 | 60 |

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

## Data according to ErP directive

| | |
|---|---|
| Installation category | A |
| Efficiency category | Static |
| Closed-loop speed control | No |
| Specific ratio* | 1,00 |

* Specific ratio = 1 + $p_{sf}$ / 100 000

| | | Actual | Request 2013 | Request 2015 |
|---|---|---|---|---|
| Overall efficiency $\eta_e$ | | 33,6 | 29,6 | 33,6 |
| Efficiency grade N | | 40 | 36 | 40 |
| Power input $P_e$ | kW | 0,97 | | |
| Air flow $q_v$ | $m^3/h$ | 10730 | | |
| Pressure increase Total $p_{sf}$ | Pa | 111 | | |
| Speed n | $min^{-1}$ | 910 | | |

Data established at point of optimum efficiency

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

## Technical features

| | |
|---|---|
| **Mass** | 27.9 kg |
| **Size** | 710 mm |
| **Surface of rotor** | Cast in aluminium |
| **Material of terminal box** | Plastic, fibreglass-reinforced |
| **Material of blades** | Aluminium sheet insert, sprayed with PP plastic |
| **Material of guard grille** | Steel, phosphated and coated in black plastic |
| **Number of blades** | 5 |
| **Blade angle** | -5° |
| **Direction of air flow** | "V" |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 54 |
| **Insulation class** | "F" |
| **Humidity class** | F3-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | + 80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | - 40 °C |
| **Mounting position** | Any |
| **Condensate discharge holes** | On rotor and stator sides |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Leakage current** | <= 3.5 mA |
| **Electrical leads** | Via terminal box |
| **Motor protection** | Thermal overload protector (TOP) brought out |
| **Cable exit** | Axial |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 61800-5-1; EN 60034; CE |
| **Approval** | VDE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "V" |
| 2 | Tightening torque 1.5 ± 0.2 Nm |
| 3 | Cable diameter: min. 7 mm, max. 14 mm, tightening torque: 2.0 ± 0.3 Nm |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

## Connection screen




Note: Direction of rotation changes when two phases are reversed

| | | | | | |
|---|---|---|---|---|---|
| Δ | Delta connection | Y | Star connection | L1 | = U1 = black |
| L2 | = V1 = blue | L3 | = W1 = brown | W2 | yellow |
| U2 | green | V2 | white | TW | 2 x grey |
| PE | green/yellow | | | | |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

## Charts: Air flow 50 Hz




Measurement: LU-113715
Measurement: LU-113738

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | Conn. | U | f | n | $P_e$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | qv | $p_{sf}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | Δ | 400 | 50 | 940 | 725 | 2.07 | 64 | 71 | 70 | 16080 | 0 |
| 2 | Δ | 400 | 50 | 925 | 859 | 2.18 | 62 | 69 | 69 | 13950 | 50 |
| 3 | Δ | 400 | 50 | 915 | 939 | 2.26 | 64 | 70 | 69 | 12060 | 90 |
| 4 | Δ | 400 | 50 | 905 | 1030 | 2.35 | 67 | 73 | 72 | 9910 | 125 |
| 5 | Y | 400 | 50 | 820 | 542 | 1.05 | 61 | 67 | 67 | 14000 | 0 |
| 6 | Y | 400 | 50 | 780 | 617 | 1.19 | 58 | 65 | 64 | 11760 | 36 |
| 7 | Y | 400 | 50 | 755 | 658 | 1.27 | 58 | 65 | 64 | 9845 | 60 |
| 8 | Y | 400 | 50 | 730 | 690 | 1.34 | 61 | 68 | 67 | 7940 | 80 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade®

sickled blades (S series)

with guard grille for short nozzle

## Charts: Air flow 60 Hz




Measurement: LU-121540
Measurement: LU-121544

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | Conn. | U | f | n | $P_e$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | qv | $p_{sf}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | Δ | 480 | 60 | 1115 | 1191 | 2.48 | 67 | 74 | 74 | 18960 | 0 |
| 2 | Δ | 480 | 60 | 1090 | 1438 | 2.71 | 66 | 73 | 73 | 16000 | 80 |
| 3 | Δ | 480 | 60 | 1075 | 1554 | 2.83 | 68 | 74 | 74 | 13990 | 130 |
| 4 | Δ | 480 | 60 | 1060 | 1700 | 2.87 | 71 | 78 | 77 | 11690 | 170 |
| 5 | Y | 480 | 60 | 930 | 853 | 1.35 | 63 | 70 | 69 | 15750 | 0 |
| 6 | Y | 480 | 60 | 860 | 956 | 1.53 | 60 | 67 | 66 | 12600 | 50 |
| 7 | Y | 480 | 60 | 825 | 994 | 1.61 | 60 | 67 | 66 | 10710 | 76 |
| 8 | Y | 480 | 60 | 780 | 1030 | 1.72 | 63 | 69 | 69 | 8695 | 92 |



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com