**W8D800-CD05-84**

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **W8D800-CD05-84** |
| **Motor** | **M8D138-LA** |

| | | | | | |
|---|---|---|---|---|---|
| Phase | | 3~ | 3~ | 3~ | 3~ |
| Nominal voltage | VAC | 230 | 277 | 400 | 480 |
| Wiring | | Δ | Δ | Y | Y |
| Frequency | Hz | 50 | 60 | 50 | 60 |
| Method of obtaining data | | fa | fa | fa | fa |
| Valid for approval/standard | | - | - | - | - |
| Speed | $min^{-1}$ | 685 | 810 | 685 | 810 |
| Power consumption | W | 705 | 1090 | 705 | 1090 |
| Current draw | A | 3.6 | 4.2 | 2.1 | 2.4 |
| Max. back pressure | Pa | 80 | 65 | 80 | 65 |
| Min. ambient temperature | °C | -40 | -40 | -40 | -40 |
| Max. ambient temperature | °C | 70 | 70 | 70 | 70 |
| Starting current | A | 11 | 12 | 6.5 | 7 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

## Technical description

| | |
|---|---|
| **Weight** | 45 kg |
| **Fan size** | 800 mm |
| **Rotor surface** | Painted black |
| **Terminal box material** | Die-cast aluminum, painted black |
| **Blade material** | Sheet aluminum insert (painted black), sprayed with PP plastic |
| **Fan housing material** | Sheet steel, galvanized and coated with white aluminum plastic (RAL 9006) |
| **Guard grille material** | Steel, galvanized and coated with white-aluminum plastic (RAL 9006) |
| **Number of blades** | 5 |
| **Blade pitch** | 0° |
| **Airflow direction** | "A" |
| **Direction of rotation** | Counterclockwise, viewed toward rotor |
| **Degree of protection** | IP54 |
| **Insulation class** | "F" |
| **Moisture (F) / Environmental (H) protection class** | F4-2 |
| **Max. permitted ambient temp. for motor (transport/storage)** | +80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | -40 °C |
| **Installation position** | Shaft horizontal or rotor on top; rotor on bottom on request |
| **Condensation drainage holes** | On stator side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | <= 3.5 mA |
| **Electrical hookup** | Via terminal box |
| **Motor protection** | Thermal overload protector (TOP) with basic insulation |
| **With cable** | Axial |
| **Protection class** | I (if protective earth is connected by customer to the housing's connection point) |
| **Conformity with standards** | EN 60034-1 (2010); EN 61800-5-1 |
| **Approval** | CSA C22.2 No. 100; EAC; UL 1004-1 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "A" |
| 2 | Tightening torque 2.5 ± 0.4 Nm |
| 3 | Cable diameter min. 10 mm, max. 12 mm; tightening torque 4 ± 0.4 Nm |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

## Connection diagram




Change of rotation direction by reversing two phases

| | | | | | |
|---|---|---|---|---|---|
| Δ | Delta connection | Y | Star connection | L2 | = U1 = black |
| L1 | = V1 = blue | L3 | = W1 = brown | W2 | yellow |
| U2 | green | V2 | white | TOP | 2x gray |
| PE | green/yellow | | | | |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

## Curves: Air performance 50 Hz




ρ = 1.176 kg/m³ ± 2 %

Measurement: LU-159547-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | Wired | U | f | n | $P_e$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | Y | 400 | 50 | 685 | 705 | 2.10 | 65 | 72 | 71 | 17020 | 0 |
| 2 | Y | 400 | 50 | 680 | 751 | 2.06 | 64 | 71 | 70 | 15180 | 30 |
| 3 | Y | 400 | 50 | 675 | 804 | 2.11 | 64 | 70 | 70 | 12930 | 60 |
| 4 | Y | 400 | 50 | 670 | 842 | 2.15 | 65 | 71 | 70 | 10535 | 80 |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed · $P_e$ = Power consumption · I = Current draw · $LpA_{in}$ = Sound pressure level intake side · $LwA_{in}$ = Sound power level intake side
$LwA_{out}$ = Sound power level outlet side · qv = Air flow · $p_{fs}$ = Pressure increase




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan - HyBlade

sickle-shaped blades (S series)

with round full nozzle

## Curves: Air performance 60 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-170001-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | Wired | U | f | n | $P_e$ | I | $LpA_{in}$ | $LwA_{in}$ | $LwA_{out}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | Y | 480 | 60 | 810 | 1090 | 2.40 | 69 | 75 | 75 | 20110 | 0 |
| 2 | Y | 480 | 60 | 805 | 1133 | 2.44 | 68 | 75 | 74 | 19020 | 20 |
| 3 | Y | 480 | 60 | 800 | 1175 | 2.49 | 68 | 74 | 73 | 17900 | 40 |
| 4 | Y | 480 | 60 | 795 | 1230 | 2.55 | 67 | 74 | 73 | 16370 | 65 |

Wired = Wiring · U = Power supply · f = Frequency · n = Speed · $P_e$ = Power consumption · I = Current draw · $LpA_{in}$ = Sound pressure level intake side · $LwA_{in}$ = Sound power level intake side
$LwA_{out}$ = Sound power level outlet side · qv = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com