**W4E250-GA04-11**

# AC axial fan

straight blades (A series)

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **W4E250-GA04-11** |
| **Motor** | **M4E068-CF** |

| | | | | |
|---|---|---|---|---|
| Phase | | 1~ | 1~ | 1~ |
| Nominal voltage | VAC | 230 | 230 | 230 |
| Frequency | Hz | 50 | 60 | 60 |
| Method of obtaining data | | ce | ce | ce |
| Valid for approval/standard | | CE | CE | UL 2111 |
| Speed (rpm) | $min^{-1}$ | 1410 | 1650 | 1650 |
| Power consumption | W | 28 | 35 | 37 |
| Current draw | A | 0.13 | 0.16 | 0.17 |
| Capacitor | µF | 1 | 1 | 1 |
| Capacitor voltage | VDB | 400 | 400 | 400 |
| Capacitor standard | | S0 (CE) | S0 (CE) | S0 (CE) |
| Min. ambient temperature | °C | -25 | -25 | -25 |
| Max. ambient temperature | °C | - | - | - |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# AC axial fan

straight blades (A series)

## Technical description

| | |
|---|---|
| **Weight** | 2.1 kg |
| **Fan size** | 250 mm |
| **Rotor surface** | Painted black |
| **Impeller material** | Sheet steel, hot-dip galvanized |
| **Fan housing material** | PA 6 plastic, glass-fiber reinforced |
| **Number of blades** | 5 |
| **Airflow direction** | "V" |
| **Direction of rotation** | Counterclockwise, viewed toward rotor |
| **Degree of protection** | IP44; installation- and position-dependent as per EN 60034-5 |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | H0+ |
| **Max. permitted ambient temp. for motor (transport/storage)** | + 80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | - 40 °C |
| **Installation position** | Shaft horizontal or rotor on bottom; rotor on top on request |
| **Condensation drainage holes** | On rotor side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | < 0.75 mA |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **With cable** | Variable |
| **Protection class** | I (with customer connection of protective earth) |
| **Motor capacitor according to EN 60252-1 in safety protection class** | S0 |
| **Conformity with standards** | EN 60335-1; CE |
| **Approval** | CSA C22.2 No. 77; CCC; UL 2111 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan


straight blades (A series)

## Product drawing




| | |
|---|---|
| 1 | Cable PVC 4G AWG20, 1x AMP connector housing 350766-4 with 2x AMP plug pin 926883-1, 1x flat push-on receptacle, crimped |
| 1.1 | black + capacitor |
| 1.2 | blue |
| 2 | Direction of air flow "V" |

## Connection diagram




| | | | | | |
|---|---|---|---|---|---|
| L | blue | N | black | PE | green/yellow |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

straight blades (A series)

## Curves: Air performance 50 Hz




Measurement: LU-35562-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | f | n | $P_e$ | I | $q_V$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | cfm | inH2O |
| 1 | 230 | 50 | 1410 | 28 | 0.13 | 860 | 505 | 0.00 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_e$ = Power consumption · I = Current draw · $q_V$ = Air flow




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC axial fan

straight blades (A series)

## Curves: Air performance 60 Hz




Measurement: LU-35563-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | f | n | $P_e$ | I | $q_V$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | cfm | inH2O |
| 1 | 230 | 60 | 1650 | 35 | 0.16 | 1005 | 595 | 0.00 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_e$ = Power consumption · I = Current draw · $q_V$ = Air flow



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com