Product Data Sheet RER225-55/18/2TDO

ebmpapst

The engineer's choice



GREEN TECH

RER225-55/18/2TDO

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 5

3.1 Electrical Interface - Input 5
3.2 Electrical Operating Data 7
3.3 Electrical Interface - Output 8
3.4 Electrical Features 9
3.5 Data According ErP Directive 9
3.6 Aerodynamics 10
3.7 Sound Data 11

4 Environment 11

4.1 General 11
4.2 Climatic Requirements 11

5 Safety 12

5.1 Electrical Safety 12
5.2 Approval Tests 12

6 Reliability 12

6.1 General 12

1 General

Fan type	Blower without chassis with intake nozzle	
Rotating direction looking at rotor	Clockwise	
Airflow direction	Air in axially, Air out radially	
Bearing system	Ball bearing	
Mounting position - shaft	Any	

2 Mechanics


2.1 General

Depth	99 mm	
Diameter	225 mm	
Mass	0 kg	
Housing material		
Impeller material	Plastic	

2.2 Connections

Electrical connection	Wires	
Lead wire length Tolerance	L = 410 mm +- 10,0 mm	
Tube length Tolerance	S = 120 mm +- 5,0 mm	
Wire size (AWG)	20	
Insulation diameter	2,05 mm	





Wire	Color	Operation
1	red	+ UB
2	blue	- GND
3	violet	CONTR
4	white	Tacho

The auxilliaries shown on the schematic diagram (which are required for the intended use) are not part of our delivery.

3 Operating Data


3.1 Electrical Interface - Input


Control input	Analog

Features


PWM - Frequency		1 kHz - 10 kHz typical: 2 kHz
Input voltage range		0 V - 10 V

Characteristics





Schematics



Input voltage divider:
R1 = 47 kOhm
R2 = 36 kOhm
For protection: There is parallel to R2 a 5,1 V Z-Diode

Speed control:
By pulse-width modulation (PWM) 0 ... 100%
with switching transistor in emitter circuit and collector resistance to 12 V
Frequency = 2 kHz (1 - 10 kHz)

Information to the curve PWM:

0% - <10% PWM:	0 1/min
10% PWM:	800 1/min (Fan on, comming from 0% PWM)
10% - 13% PWM:	800 1/min (corresponding to min. speed)
13% - 78% PWM:	linear increasing curve
78% - 100% PWM:	3.500 1/min (corresponding to max. speed)
10% - >8% PWM:	linear decreasing curve (comming from 100% PWM)
8% PWM:	600 1/min or 0 1/min (Fan off, comming from 100% PWM)

or:

Speed control:
By analog voltage 0 - 10 V

Information to the curve analog:

0 V - < 1,3 V:	0 1/min
1,3 V:	800 1/min (Fan on, comming from von 0 V)
1,3 V - 1,6 V:	800 1/min (corresponding to min. speed)
1,6 V - 9,4 V:	linear increasing curve
9,4 V - 10 V:	3.500 1/min (corresponding to max. speed)
1,3 V - > 1,0 V:	linear decreasing curve (comming from 10 V)
1,0 V:	600 1/min or 0 1/min (Fan off, comming from 10 V)

The fan does not provide a sensor break detection!

3.2 Electrical Operating Data

Measurement conditions: Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified).
In the intake and outlet area should not be any solid obstruction within 0,5 m.

Measurement setup:	Measured between two steel plates
Steel plate:	230 mm x 230 mm
Intake nozzle:	D: 146 mm; R: 25 mm
Distance between bottom and top plate:	123,5 mm
Overlapping impeller / nozzle:	2 mm


Δp = 0: corresp. to free air flow (see chapter aerodynamics)
I: corresp. to arithm. mean current value

Name	**Condition**		
U Contr. 0001	U Contr.: 10 V		

Features	**Condition**	**Symbol**	**Values**		
Voltage range		U	36 V		72,0 V
Nominal voltage		U_N		48,0 V	
Power consumption Tolerance	Δp = 0 U Contr. 0010	P	123 W +- 10,0 %	226 W +- 10,0 %	230 W +- 10,0 %
Current consumption Tolerance	Δp = 0 U Contr.0010	I	3.500 mA +- 10,0 %	4.700 mA +- 10,0 %	3.200 mA +- 10,0 %
Speed Tolerance	Δp = 0 U Contr. 0010	n	2.960 1/min +- 7,5 %	3.500 1/min +- 5,0 %	3.500 1/min +- 5,0 %

3.3 Electrical Interface - Output

Tacho type	/2 (open collector)




Features		Note	Values
Tacho operating voltage	U_{BS}		<= 60,0 V
Tacho signal Low	$U_{S\ low}$	I sink: 2 mA	<=0,4 V
Tacho signal High	$U_{S\ high}$	I source: 0 mA	<=60,0 V
Maximum sink current	I_{sink}		<= 20 mA
External resistor		External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency		(3 x n) / 60	175 Hz @ 3.500 1/min
Tacho isolated from motor		No	
Slew rate			=> 0,5 V/us

n = revolutions per minute (1/min)

Please note:
At zero speed the tacho signal is at a static HIGH. It will be also HIGH when the fan is still spinning, but the speed control signal is set to zero speed already.
The tacho signal is only activated after the start-up is completed.

3.4 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection Max. residual current at U_N	P-CH FET I_F <= 5 mA	
Locked rotor protection	Auto restart	
Locked rotor current at U_N	I_{block} approx. 2.000 mA	
Clock signal at locked rotor	t_3 / t_4 typical: 7,2 s / 10,0 s	



Locked rotor signal t5:
After 2 failed start-ups there is an extended timeout of 50 s.

3.5 Data According ErP Directive

Installation / Efficency category	A / static
Speed control	integrated
Specific ratio	1,00640
Target overall efficiency 2015	45,6 %
Overall efficiency	59,4 %
Efficiency grade	62
Power input	273,8 W
Speed	3.450 1/min

All values measured in optimum energy efficiency point.

3.6 Aerodynamics


Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

Measurement setup:	Measured between two steel plates
Steel plate:	230 mm x 230 mm
Intake nozzle:	D: 146 mm; R: 25 mm
Distance between bottom and top plate:	123,5 mm
Overlapping impeller / nozzle:	2 mm

a.) Operation condition:

3.500 1/min at free air flow	U Contr. 10 V		

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	1.540 m3/h	
Max. static pressure (Δp = max. / $\dot{V}$ =0)	840 Pa	



3.7 Sound Data

Measurement conditions:	Sound pressure level: 1 meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

3.500 1/min at free air flow	U Contr. 10 V		

Optimal operating point	1.002 m3/h @ 514 Pa	
Sound power level at the optimal operating point	8 bel(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	55 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic Requirements

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Dust requirements	None	
Salt fog requirements	None	

Permitted application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	1000 VAC / 1 Min. 1000 VAC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Clearance / creepage distance	1,0 mm / 1,5 mm	
Protection class	I	


5.2 Approval Tests


CE	EC Declaration of Conformity	Yes
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL507, Electric Fans
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Yes / GB 12350 Safety Requirements for small Power Motors


6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	50.000 h	
Life expectancy L10 at TU max.	35.000 h	
Life expectancy L10 acc. to IPC 9591 at TU = 40 °C	85.000 h	







-- Axialspiel der Kugellager spielfrei verspannt.
1.) Anzahl und Länge der Litzen sowie Länge des Schlauchs siehe Produktspezifikation.

-- Ball bearings without axial clearance by a pre-load spring.
1.) Number and length of wires and length of tube see product specification.

Ebmpapst-Werke / Ebmpapst-St.Georgen		EMTA-Version/ EMTA-Version	EMTA-Ausgabe/ EMTA-Issue date	Werkstoff / Material:		Version / Version Index:	
						Gewicht / Mass [g]:	
Kunst.-Nr./ Change-No.		3D Referenzmodell / 3D Reference model		Titel / Title:			
Toleranzen / Tolerances:		Datum	Name				
	Bearb./ Drawn						
Allgemeintoleranzen / Gen. Tolerances:	Gepr./ Checked			Zchg.-Nr./ Drawing No:		Prüf./Zchn. / Tag/Stamp:	
	Freig./ Released						
ebmpapst				Dokumentart / Type of document	Technikdokument / Technical Report	Index / Index: -	Format / Size: Massstab/Scale
ebm-papst St. Georgen GmbH & Co. KG							