# Product Data Sheet 4414 HU

ebmpapst

The engineer's choice



GREEN TECH

**4414 HU**

**INDEX**

**1 General ..... 3**
**2 Mechanics ..... 3**
2.1 General ..... 3
2.2 Connections ..... 3
**3 Operating Data ..... 5**
3.1 Operating Data - Electrical Interface - Input ..... 5
3.2 Electrical Operating Data ..... 6
3.3 Operating Data - Electrical Interface - Output ..... 6
3.4 Electrical Features ..... 7
3.5 Aerodynamics ..... 8
3.6 Sound Data ..... 9
**4 Environment ..... 9**
4.1 General ..... 9
4.2 Climatic Requirements*) ..... 9
**5 Safety ..... 10**
5.1 Electrical Safety ..... 10
5.2 Approval Tests ..... 10
**6 Reliability ..... 10**
6.1 General ..... 10

## 1 General

| | | |
|---|---|---|
| Fan type | Fan | |
| Rotating direction looking at rotor | Clockwise | |
| Airflow direction | Air outlet over struts | |
| Bearing system | Ball bearing | |
| Mounting position | Any | |


## 2 Mechanics

### 2.1 General

| | | |
|---|---|---|
| Width | 119,0 mm | |
| Height | 119,0 mm | |
| Depth | 38,0 mm | |
| Mass | 0,270 kg | |
| Housing material | Plastic | |
| Impeller material | Plastic | |
| Max. torque when mounted across both mounting flanges<br>Screw size | wire outlet corner: 80 Ncm<br>remaining corners: 80 Ncm<br>ISO 4762 - M4 degreased, without an additional brace and without washer | |

### 2.2 Connections

| | | |
|---|---|---|
| Electrical connection | Wires | |
| Lead wire length<br>Tolerance | L = 310 mm<br>+- 10,0 mm | |
| Wire size (AWG) | 24 | |
| Insulation diameter | 1,10 mm | |
| Contact | See drawing | |




| | Colour | Operation |
|---|---|---|
| Wire 1 | red | + UB |
| Wire 2 | blue | - GND |

# 3 Operating Data

## 3.1 Operating Data - Electrical Interface - Input

| | |
|---|---|
| Control input | None |

### 3.2 Electrical Operating Data

| | |
|---|---|
| Measurement conditions: | Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal;warm-up time before measuring 5 minutes (unless otherwise specified).In the intake and outlet area should not be any solid obstruction within 0,5 m. |

∆p = 0: corresp. to free air flow (see section 3.5)
I: corresp. to arithm. mean current value

| Features | Condition | Symbol | Values | | |
|---|---|---|---|---|---|
| Voltage range | ∆p = 0 | U | 12,0 V | | 27,6 V |
| Nominal voltage | ∆p = 0 | $U_N$ | | 24,0 V | |
| Power consumption<br>Tolerance | ∆p = 0<br>0010 | P | 1,9 W<br>+- 17,5 % | 8,2 W<br>+- 25,0 % | 9,1 W<br>+- 25,0 % |
| Current consumption<br>Tolerance | ∆p = 0<br>0010 | I | 157 mA<br>+- 17,5 % | 340 mA<br>+- 25,0 % | 330 mA<br>+- 25,0 % |
| Speed<br>Tolerance | ∆p = 0<br>0010 | n | 2.460 1/min<br>+- 12,5 % | 4.300 1/min<br>+- 3,0 % | 4.300 1/min<br>+- 3,0 % |


### 3.3 Operating Data - Electrical Interface - Output

| | |
|---|---|
| Tacho type | None |

| | |
|---|---|
| Alarm type | None |

### 3.4 Electrical Features

| | | |
|---|---|---|
| Electronic function | Speed-Controlled | |
| Reversed polarity protection<br>Max. residual current at Un | Rectifying diode<br>IF <= 100 uA | |
| Locked rotor protection | Auto restart | |
| Locked rotor current at Un | approx. 2.150 mA | |
| Clock signal t3/t4 at locked rotor | Typical: 0,5 s / 10 s | |




### 3.5 Aerodynamics

| | |
|---|---|
| Measurement conditions: | Measured with a double chamber intake rig acc. to DIN EN ISO 5801.<br>Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C;<br>In the intake and outlet area should not be any solid obstruction within 0,5 m.<br>The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions. |

a.) Operation condition:

| |
|---|
| 4.300 1/min at free air flow |

| | | |
|---|---|---|
| Max. free-air flow (Δp = 0 / V̇ = max.) | 240,0 m3/h | |
| Max. static pressure (Δp = max. / V̇ =0) | 160 Pa | |



### 3.6 Sound Data

| | |
|---|---|
| Measurement conditions: | Sound pressure level: 1 Meter distance between microphone and the air intake.<br>Sound power level: Acc. to DIN 45635 part 38 (ISO 10302)<br>Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A)<br>For further measurement conditions see section 3.5 |

a.) Operation condition:

| |
|---|
| 4.300 1/min at free air flow |

| | | |
|---|---|---|
| Optimal operating point | 148,0 m3/h @ 60 Pa | |
| Sound power level at the optimal operating point | 6,0 bel(A) | |
| Sound pressure level at free air flow, measured in rubber bands | 50,0 dB(A) | |

## 4 Environment

### 4.1 General

| | | |
|---|---|---|
| Min. permitted ambient temperature TU min. | -20 °C | |
| Max. permitted ambient temperature TU max. | 70 °C | |
| Min. permitted storage temperature TL min. | -40 °C | |
| Max. permitted storage temperature TL max. | 80 °C | |

### 4.2 Climatic Requirements*)*

| | | |
|---|---|---|
| Humidity requirements | humid temperature, cyclic; according to DIN EN 60068-2-38, 10 cycle and condensation water check; according to DIN EN ISO 6270-2, 14 days | |
| Water exposure | Splash water check IPX4; according to DIN EN 60529 VDE 0470, not certified | |
| Dust requirements | Dust check IP5X; according to DIN EN 60529 VDE 0470, not certified | |
| Salt fog requirements | salt fog, cyclic, in operation; according to DIN EN 60068-2-52, 3 cycle | |

*) Permittet application area:
The product is for the use in open and unsheltered areas. Direct exposure to water as well as saline ambient conditions are allowed provided that this does not prevent the normal operation.

Pollution degree 3 (according DIN EN 60664-1)
It occurs conductive pollution or dry non-conductive pollution which becomes conductive due to condensation.

Please require severity levels and specification parameters from the responsible development departments

## 5 Safety

### 5.1 Electrical Safety

| | | |
|---|---|---|
| Dielectric strength<br>DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700)<br>A.) Type test<br>Measuring conditions: After 48h of storage at 95% R.H. and 25°C.<br>No arcing or breakdown is allowed!<br>All connections together to ground.<br>B.) Routine test<br>Measuring conditions: At indoor climate.<br>No arcing or breakdown is allowed!<br>All connections together to ground. | 500 VAC / 1 Min.<br><br>500 VAC / 1 Sec. | |
| Isolation resistance<br>Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min. | RI > 10 MOhm | |
| clearance / creepage distance | 1,0 mm / 1,2 mm | |
| Protection class | III | |


### 5.2 Approval Tests


| | | |
|---|---|---|
| CE | EC Declaration of Conformity | Yes |
| EAC | Eurasian Conformity | Yes |
| UL | Underwriters Laboratories | Yes / UL507, Electric Fans |
| VDE | Association for Electrical, Electronic and Information Technologies | Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment |
| CSA | Canadian Standards Association | Yes / C22.2 No. 113 Fans and Ventilators |
| CCC | China Compulsory Certification | No |


## 6 Reliability

### 6.1 General

| | | |
|---|---|---|
| Life expectancy L10 at TU = 40 °C | 57.500 h | |
| Life expectancy L10 at TU max. | 27.500 h | |
| Life expectancy L10 Delta (40 °C) | 92.500 h | |




1.) Maße fuer Montageausschnitt:
- Axia spiel: mit Feder spielfrei verspannt
  Max. Anzugsmoment be Montage
  über beide Befestigungsl ansche – 0.8 Nm

1.) measures for mounting cut-out
- without axial clearance by a pre-loaded spring
- Max. torque when mounted
  across both mounting ' anges = 0.8 Nm

VZ – vers on / l nged

ebmpapst