K1G200-AA73-63

EC centrifugal module

sickle-shaped blades (S series)

with support bracket

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

Nominal data

Type	**K1G200-AA73-63**
Motor	**M1G055-BD**

Phase		1~	1~
Nominal voltage	VAC	230	230
Frequency	Hz	50/60	50/60
Method of obtaining data			ml
Speed (rpm)	min^{-1}	1500	2000
Power consumption	W	-	35
Current draw	A		0.3
Min. ambient temperature	°C	-30	-30
Max. ambient temperature	°C	50	50

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

EC centrifugal module

sickle-shaped blades (S series)

with support bracket

Technical description

Weight	1.2 kg
Fan size	200 mm
Impeller material	PA plastic
Support bracket material	PA plastic
Inlet nozzle material	PA plastic
Number of blades	7
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"B"
Moisture (F) / Environmental (H) protection class	H1
Max. permitted ambient temp. for motor (transport/storage)	+ 80 °C
Min. permitted ambient temp. for motor (transport/storage)	- 40 °C
Installation position	Any
Condensation drainage holes	None, open rotor
Mode	S1
Motor bearing	Ball bearing
Technical features	- Speed setting input (230 V) - ESM+ expandable with plug-in module - Soft start - Thermal overload protection for motor
Speed levels	2
Motor protection	Thermal overload protector (TOP) internally connected
Protection class	II
Conformity with standards	EN 60335-1; CE
Approval	CSA C22.2 No. 77; UL 1004-3; VDE


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

sickle-shaped blades (S series)

with support bracket

Product drawing



	Stepless speed control from 10-100%
1	Direction of air flow "V"
2	Cable PVC AWG22, 4x crimped splices
3	Cable PVC AWG22, 2x crimped splices


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

sickle-shaped blades (S series)

with support bracket

Connection diagram



No.	Conn.	Designation	Color	Function/assignment
CON10	1	L	black	Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range
CON10	2	N	blue	Neutral conductor
CON50	1	10V/max 1.1mA	red	Voltage output 10 V/1.1 mA, electrically isolated, not short-circuit-proof.
CON50	2	Tach	white	Tach output: Open collector, 1 pulse per revolution, electrically isolated
CON50	3	0-10V PWM	yellow	Control input 0-10 V or PWM, electrically isolated
CON50	4	GND	blue	GND connection for control interface


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

sickle-shaped blades (S series)

with support bracket

Curves: Air performance 50 Hz



Measurement: LU-123220-1
Measurement: LU-123224-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Measured values

	Stage	U	f	n	P_{ed}	I	qv	p_{fs}	qv	p_{fs}
		V	Hz	min^{-1}	W	A	m^3/h	Pa	CFM	inH2O
1	1	230	50	2000	31	0.24	580	0	340	0.00
2	1	230	50	2000	33	0.26	505	40	295	0.16
3	1	230	50	2000	35	0.30	420	80	245	0.32
4	1	230	50	2000	35	0.27	290	120	170	0.48
5	2	230	50	1500	16	0.13	430	0	250	0.00
6	2	230	50	1500	19	0.14	375	22	220	0.09
7	2	230	50	1500	20	0.18	315	45	185	0.18
8	2	230	50	1500	18	0.14	220	68	130	0.27

U = Power supply · f = Frequency · n = Speed (rpm) · P_{ed} = Power consumption · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com