K3G400-AC30-65

EC centrifugal module

backward curved, single inlet

with support plate

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

ErP2015 EXCEEDS THE NORM

Nominal data

Type	**K3G400-AC30-65**
Motor	**M3G084-FA**

Phase		1~
Nominal voltage	VAC	230
Nominal voltage range	VAC	200 .. 277
Frequency	Hz	50/60
Type of data definition		ml
Speed	min^{-1}	1304
Power input	W	370
Current draw	A	1.8 (200V)
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	30

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

Data according to ErP directive

Installation category	A
Efficiency category	Static
Variable speed drive	Yes
Specific ratio*	1.00

* Specific ratio = 1 + p_{fs} / 100 000 Pa

		Actual	Request 2013	Request 2015
Overall efficiency η_{es}	%	58.2	42.4	46.4
Efficiency grade N		73.8	58	62
Power input P_{ed}	kW	0.33		
Air flow q_v	m^3/h	2080		
Pressure increase p_{fs}	Pa	300		
Speed n	min^{-1}	1310		

Data definition with optimum efficiency. LU-70774
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

EC centrifugal module

backward curved, single inlet

with support plate

Technical features

Mass	10 kg
Size	400 mm
Surface of rotor	Coated in black
Material of electronics housing	Die-cast aluminium
Material of impeller	Aluminium sheet
Material of mounting plate	Aluminium sheet
Material of distancing profiles	Aluminium
Material of inlet nozzle	Aluminium sheet
Number of blades	6
Direction of rotation	Clockwise, seen on rotor
Type of protection	IP 20
Insulation class	"B"
Humidity class	F0
Max. permissible ambient motor temp. (transp./ storage)	+80 °C
Min. permissible ambient motor temp. (transp./storage)	-40 °C
Mounting position	Rotor on top
Condensate discharge holes	None
Operation mode	S1
Motor bearing	Ball bearing
Technical features	- Operation and fault indication via LED - Integrated PID controller - LON / RS485 with DCI function - Motor current limit - PFC, active - Soft start - Control interface with SELV potential safely isolated from the mains - Electronics / motor excess temperature protection - Line undervoltage / phase failure detection
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	<= 3.5 mA
Electrical leads	With plug
Motor protection	Thermal overload protector (TOP) wired internally
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 61800-5-1; CE
Approval	CSA C22.2 Nr.113; UL 507


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward curved, single inlet

with support plate

Product drawing



1	Terminal box
2	Connector housing 3-pole GST18/3 Wieland 92.032.9058.1
2.1	N
2.2	PE
2.3	L
3	Connector housing 8-pole Tyco 100616-2
4	Connector housing 8-pole Tyco 100616-2
5	Switch, ARCOLECTRIC SWITCHES P L C (no. H8550VBACF) As-delivered condition end customer switch set to "OFF"


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward curved, single inlet

with support plate

Connection screen



LED1 / LED2

Status	Priority	Address S/N	Speed	LED red	LED green
General malfunction	1	S/N any	n any	"Flashing 1 Hz"	"OFF"
Signal function	2	S/N <> 1/1	n any	"OFF"	"Flashing 10 Hz"
Factory default setting	3	S/N = 1/1	n > 0	Permanent "ON"	"OFF"
After initialisation	3	S/N <> 1/1	n > 0	"OFF"	Permanent "ON"
Fan to speed 0	3	S/N <> 1/1	n = 0	"OFF"	"Flashing 1 Hz"
Factory default setting	3	S/N = 1/1	n = 0	Permanent "ON"	"Flashing 1 Hz"

No.	Conn.	Designation	Function / assignment
ST1/ST3	1	LON_A	Bus connection RS485; LON_A
ST1/ST3	2	LON_B	Bus connection RS485; LON_B
ST1/ST3	3	LON_A	Bus connection RS485; LON_A
ST1/ST3	4	-	Bridge ST1 – ST3
ST1/ST3	5	-	Bridge ST1 – ST3
ST1/ST3	6	LON_B	Bus connection RS485; LON_B
ST1/ST3	7	GND	Reference earth
ST1/ST3	8	DCI	Daisy chain signal
ST1/ST3	S	Schirm	Shield for RJ45 CAT5 wire


ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

EC centrifugal module

backward curved, single inlet

with support plate

Charts: Air flow 50 Hz



Measurement: LU-70774

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	U	f	n	P_{ed}	I	qv	p_{fs}
	V	Hz	min^{-1}	W	A	m^3/h	Pa
1	200	50	1305	284	1.44	3680	0
2	200	50	1305	330	1.67	3060	150
3	200	50	1305	350	1.80	2555	250
4	200	50	1305	314	1.59	1600	350
5	200	50	1100	167	0.85	3085	0
6	200	50	1100	196	0.99	2570	107
7	200	50	1100	207	1.05	2145	177
8	200	50	1100	186	0.94	1345	247
9	200	50	900	91	0.46	2525	0
10	200	50	900	107	0.54	2105	71
11	200	50	900	114	0.57	1755	118
12	200	50	900	102	0.51	1100	166
13	200	50	700	43	0.22	1965	0
14	200	50	700	50	0.26	1635	43
15	200	50	700	53	0.27	1365	72
16	200	50	700	48	0.24	855	100

U = Supply voltage · f = Frequency · n = Speed · P_{ed} = Power input · I = Current draw · qv = Air flow · p_{fs} = Pressure increase

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com