Product Data Sheet 2218F/2TDH4OR-227

ebmpapst

Die Wahl der Ingenieure



GREEN TECH

2218F/2TDH4OR-227

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 4

3.1 Operating Data - Electrical Interface - Input 4
3.2 Electrical Operating Data 6
3.3 Operating Data - Electrical Interface -Output 7
3.4 Electrical Features 7
3.5 Data According ErP Directive 8
3.6 Aerodynamics 9
3.7 Sound Data 10

4 Environment 10

4.1 General 10
4.2 Climatic Requirements*) 10
4.3 Mechanical Requirements 11

5 Safety 13

5.1 Electrical Safety 13
5.2 Approval Tests 13

6 Reliability 13

6.1 General 13

1 General

Fan type	Fan	
Rotational direction looking at rotor	counterclockwise	
Airflow direction	Air outlet over struts	
Bearing system	Ball bearing	
Mounting position	any	

2 Mechanics


2.1 General

Width	200 mm	
Height	200 mm	
Depth	51 mm	
Diameter	220 mm	
Weight	1,06 kg	
Housing material	Metal	
Impeller material	Plastic	

2.2 Connections

Electrical connection	Wires		
Length of lead wire Tolerance	L = 450 mm +- 10 mm		
Length of tube Tolerance	S = 410 mm +- 10 mm		
Wire gauge (AWG)	22	18	
Insulation diameter	1,7 mm	2,2 mm	
Contact	see drawing		





	Colour	Operation
Wire 1	red	+ UB
Wire 2	blue	- GND
Wire 3	violet	CONTR
Wire 4	white	Tacho

The auxiliaries shown in the schematic diagram (which are required for the intended use) are not part of our delivery.
Lead wire 1 - 2: AWG18 (Insulation diameter 2,2 mm)
Lead wire 3 - 4: AWG22 (Insulation diameter 1,7 mm)

3 Operating Data


3.1 Operating Data - Electrical Interface - Input

Control input	Analog


Features


PWM - Frequency		1 kHz - 10 kHz Typical: 2 kHz
Inpute voltage range		0 V - 10 V

Characteristics



Schematics





Input voltage divider:
R1 = 47 kOhm
R2 = 36 kOhm
For protection: There is parallel to R2 a 5,1 V Z-Diode

Speed control:
By pulse-width modulation (PWM) 0 ... 100%
with switching transistor in emitter circuit and collector resistance to 12 V
Frequency = 2 kHz (1 - 10 kHz)

Information to the curve PWM:

0% - <10% PWM:	0 1/min
10% PWM:	1.000 1/min (Fan on, coming from 0% PWM)
10% - 13% PWM:	1.000 1/min (corresponding to min. speed)
13% - 78% PWM:	linear increasing curve
78% - 100% PWM:	6.600 1/min (corresponding to max. speed)
10% - >8% PWM:	linear decreasing curve (coming from 100% PWM)
8% PWM:	800 1/min or 0 1/min (Fan off, coming from 100% PWM)

or:

Speed control:
By analog voltage 0 - 10 V

Information to the curve analog:

0 V - < 1,3 V:	0 1/min
1,3 V:	1.000 1/min (Fan on, coming from von 0 V)
1,3 V - 1,6 V:	1.000 1/min (corresponding to min. speed)
1,6 V - 9,4 V:	linear increasing curve
9,4 V - 10 V:	6.600 1/min (corresponding to max. speed)
1,3 V - > 1,0 V:	linear decreasing curve (coming from 10 V)
1,0 V:	800 1/min or 0 1/min (Fan off, coming from 10 V)

Note:
It must be ensured that the power supply is applied before the control signal (U Contr) is turned on

The fan has no sensor break detection.

3.2 Electrical Operating Data

Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.
Δp = 0:	corresp. to free air flow (see section 3.5)
I:	corresp. to arithm. mean current value


Name	Condition
U Contr. 0001	U Contr.: 10 V

Features	Condition	Symbol	Values		
Voltage range	Δp = 0	U	36,0 V		72,0 V
Nominal voltage	Δp = 0	U_N		48,0 V	
Power consumption Tolerance	Δp = 0 U Contr. 0001	P	78 W +- 12,0 %	99 W +- 10,0 %	101 W +- 10,0 %
Current consumption Tolerance	Δp = 0 U Contr. 0001	I	2.170 mA +- 12,0 %	2.060 mA +- 10,0 %	1.400 mA +- 10,0 %
Speed Tolerance	Δp = 0 U Contr. 0001	n	6.150 1/min +- 5,0 %	6.600 1/min +- 3,0 %	6.600 1/min +- 3,0 %

Built into the fan is an additional under- and overvoltage control, which switches the power stage and the fan off if the following conditions are reached.
At U <= 32 V and / or U >= 80 V is n= 0 1/min

3.3 Operating Data - Electrical Interface -Output

Tacho type	/2 (open collector)




$$Ra = \frac{UBS - US\ Low}{I\ Sink}$$

Features	Note	Values
Tacho operating voltage (UBS)		<= 60 V
Tacho signal Low	I sink: 2 mA	<= 0,4 V
Tacho signal High	I source: 0 mA	<= 60 V
Maximum sink current		<= 20 mA
External resistor	External resistor Ra from UBS to US required. All voltages measured to GND.	
Tacho frequency	(6 x n) / 60	
Tacho isolated from motor	No	
Slew rate		=> 0,5 V/us

Alarm type	None

3.4 Electrical Features

Electronic function	Speed-Controlled
Reversed polarity protection Max. residual current at Un	P-CH FET IF <= 5 mA
Locked rotor protection	Auto restart
Locked rotor current at Un	approx. 2.500 mA
Clock signal t3/t4 at locked rotor	Typical: 3,0 s / 10,0 s



Internal Fuse:

Littelfuse NANO2(R) FUSE; Very fast acting 451 Series; 10 A (Art.-Nr.: 0451010.MRL)

Inrush current limiter:

This fan is equipped with an inrush current limiter to reduce the charging current of the internal capacitor. By this circuit the fan gets a start-up delay of 2 s after connecting the supply voltage. Only a short peak current can be measured at the inrush by charging the small internal filter capacitors with approximately 6,6 uF.

3.5 Data According ErP Directive

Installation / Efficency category	A / static
Speed control	integrated
Specific ratio	1,00359
Target overall efficiency 2015	29,1 %
Overall efficiency	52,4 %
Efficiency grade	40
Power input	188 W
Speed	6.570 1/min

All values measured in optimum energy efficiency point.

Production date code is printed on the fan label.


3.6 Aerodynamics

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions. Power consumption of the fan motor when operating at normal voltage is shown. Depending on the operating conditions of the application, the power input may be higher.

a.) Operation condition:

6.600 1/min at free air flow	U Contr. 10 V

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	1.230,0 m3/h
Max. static pressure (Δp = max. / $\dot{V}$ =0)	1.180 Pa



3.7 Sound Data

Measurement conditions:	Sound pressure level: 1 Meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see section 3.5

a.) Operation condition:

6.600 1/min at free air flow	U Contr. 10 V

Optimal operating point	1.200,0 m3/h @ 44 Pa
Sound power level at the optimal operating point	8,2 bel(A)
Sound pressure level at free air flow, measured in rubber bands	74,0 dB(A)

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C
Max. permitted ambient temperature TU max.	65 °C
Min. permitted storage temperature TL min.	-40 °C
Max. permitted storage temperature TL max.	80 °C

4.2 Climatic Requirements*)

Humidity requirements	humid heat, cyclic; according to DIN EN 60068-2-30, 6 cycles
Water exposure	None
Dust requirements	Dust check; according to DIN EN 60068-2-68, 6g/m2d, 1 day
Salt fog requirements	None

*) Permitted application area:
The product is for the use in sheltered rooms with limited controlled temperature. Occasionally condensed water is allowed. Direct exposure to water must be avoided. Saline ambient conditions must be avoided.

Pollution degree 2 (according DIN EN 60664-1)
It occurs only non-conductive pollution. Occasionally, temporary conductivity caused by condensation occurs.

4.3 Mechanical Requirements

severity level	Vibration (sinusoidal)	
2 G	Vibration (sinusoidal) in use IEC 60068-2-6 Displacement / frequency range Acceleration / frequency range Sweep rate Sweep cycles Duration Axes of vibration	 Vibration (sinusoidal) 0,15 mm / 10-58, 58-10 Hz 2 G / 58-500-58 Hz 1 Oct./min 10 2 hrs. 3

severity level	stationary use		
1	storage / transportation	Random vibration not in use IEC 60068-2-64 Frequency range / ASD G_{RMS} Axes of vibration Test duration	 Random vibration 5 - 20 Hz : 1,0 m^2 / s^3 20 - 500 Hz : - 3 dB / Oct 0,91 G 3 3 x 30 min
	storage / transportation	Bump not in use IEC 60068-2-29 Shock spectrum Acceleration Duration Number of bumps (+X, -X, -Y, +Y, -Z, +Z) Total bumps	 Bump half sine 18 G 6 ms 100 in each direction 600
	stationary use	Random vibration in use IEC 60068-2-64 Frequency range / ASD G_{RMS} Axes of vibration Test duration	 Random vibration 5 - 10 Hz : +6 dB / Oct 10 - 50 Hz : 1,0 m^2 / s^3 50 - 200 Hz : - 6 dB / Oct 0,65 G 3 3 x 30 min
	stationary use	Bump in use IEC 60068-2-29 Shock spectrum Acceleration Duration Number of bumps (+X, -X, -Y, +Y, -Z, +Z) Total bumps	 Bump half sine 5 G 11 ms 100 in each direction 600

severity level	Railroad application	
1 IEC 61373 Category 1 Class B	Random vibration in use IEC 60068-2-64 Frequency range / ASD G_{RMS} Axes of vibration Test duration	 Random vibration 5 - 10 Hz : +6 dB / Oct 10 - 50 Hz : 1,0 m^2 / s^3 50 - 200 Hz : - 6 dB / Oct 0,65 G 3 3 x 30 min
	Shock in use IEC 60068-2-27 Shock spectrum Acceleration Duration Number of bumps (+X, -X, -Y, +Y, -Z, +Z) Total bumps	 Shock half sine 7 G 18 ms 10 in each direction 60

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	 1000 VAC / 1 Min. 1000 VAC / 1 Sec.
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm
clearance / creepage distance	1,0 mm / 1,5 mm
Protection class	I

5.2 Approval Tests

CE	EC Declaration of Conformity	No
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL audited by CSA according to UL507, Electric Fans
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Yes / GB 12350 Safety Requirements for small Power Motors


6 Reliability


6.1 General

Life expectancy L10 at TU = 40 °C	**70.000 h**
Life expectancy L10 at TU max.	**40.000 h**
Life expectancy L10 Delta (40 °C)	**140.000 h**

Copying of this document, and giving it others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

Schraube: Duo-Taptite n. DIN7500, CM 4x8, Torx
Screw: Duo-Taptite according to DIN7500, CM4x8, Torx





1) Maße für Montageausschnitt
2) Anzahl und Länge der Litzen sowie Länge des Schlauches siehe Produktspezifikation
3) nur, wenn in Stückliste enthalten

- Axialspiel der Kugellager mit Feder spielfrei gelagert

1) measures of mounting cut out
2) length and number of wires and length of tube see product specification
3) only if included in bill of material

- ball bearing without clearance by a pre-load spring

Zeichnung entspricht 3D-Modell:
Drawing is equivalent to 3D-Model:
9295420200_000_B (B)
System: CATIA V5 R 16

ebmpapst