Product Data Sheet DV6224 TDA

ebmpapst

The engineer's choice



GREEN TECH

DV6224 TDA

INDEX

1 General 3

2 Mechanics 3

2.1 General 3
2.2 Connections 3

3 Operating Data 4

3.1 Electrical Interface - Input 4
3.2 Electrical Operating Data 5
3.3 Electrical Features 7
3.4 Aerodynamics 8
3.5 Sound Data 9

4 Environment 9

4.1 General 9
4.2 Climatic Requirements 9

5 Safety 10

5.1 Electrical Safety 10
5.2 Approval Tests 10

6 Reliability 10

6.1 General 10

1 General

Fan type	Mixed-flow fan	
Rotating direction looking at rotor	Counterclockwise	
Airflow direction	Air outlet over struts	
Bearing system	Ball bearing	
Mounting position - shaft	Any	


2 Mechanics

2.1 General

Depth	51,0 mm	
Diameter	172,0 mm	
Mass	0,820 kg	
Housing material	Metal	
Impeller material	Plastic	
Max. torque when mounted across both mounting flanges Screw size	Wire outlet corner: 180 Ncm Remaining corners: 180 Ncm ISO 4762 - M4 degreased, without an additional brace and without washer	

2.2 Connections

Electrical connection	Wires	
Lead wire length Tolerance	L = 365 mm +- 10,0 mm	
Tube length Tolerance	S = 15 mm +- 3,0 mm	
Wire size (AWG)	22	
Insulation diameter	1,70 mm	



Wire	Color	Operation
1	red	+ UB
2	blue	- GND
3	violet	CONTR

3 Operating Data


3.1 Electrical Interface - Input

Control input	Analog


Features

Input voltage range		0 V - 10 V

Characteristics



Schematics



Speed control:
By control voltage U Contr. 0... 10 V
Fan turning stops if the input signal connection is lost.
No internal pull-up resistor

3.2 Electrical Operating Data

Measurement conditions:	Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; Motor axis horizontal; warm-up time before measuring 5 minutes (unless otherwise specified). In the intake and outlet area should not be any solid obstruction within 0,5 m.

$\Delta p = 0$: corresp. to free air flow (see chapter aerodynamics)
I: corresp. to arithm. mean current value

Name	Condition		
U Contr. 0001	U Contr.: 10,0 V		

Note:
No inrush current at Unom means:


The internal electrolytic capacitor 470uF/35V has a resistor 0R1, this is limiting the inrush current!

Features	Condition	Symbol	Values		
Voltage range		U	16 V		28,0 V
Nominal voltage		U_N		24,0 V	
Power consumption Tolerance	$\Delta p = 0$ U Contr. 0010	P	41,6 W +- 15 %	91,2 W +- 15,0 %	95,2 W +- 15,0 %
Current consumption Tolerance	$\Delta p = 0$ U Contr. 0010	I	2.600 mA +- 15,0 %	3.800 mA +- 15,0 %	3.400 mA +- 15,0 %
Speed Tolerance	$\Delta p = 0$ U Contr. 0010	n	4.200 1/min +- 10,0 %	5.500 1/min +- 10,0 %	5.500 1/min +- 10,0 %


Motor testing

The motor testing relates to a fan, operating with horizontal shaft, at free wir flow. It is possible to run this motor in an uncontrolled state. For some testings the motor may set in a test cycle by connecting to a voltage follower as below mentioned.

Voltage graph to start the test cycle


Betriebsspannung / Operating voltage [VDC] +- 1%
28
26
24
22
20
18
16
0,2
0,6
0,9
1,3
1,6
2,1
t [s]


Speed graph after starting the test cycle



Voltage	24,0 V
Power consumption	105,6 W
Tolerance	+- 15,0 %
Current consumption	4.400 mA
Tolerance	+- 15,0 %
Speed	5.900 1/min
Tolerance	+- 10,0 %

3.3 Electrical Features

Electronic function	Speed-Controlled	
Reversed polarity protection Max. residual current at U_N	P-CH FET I_F <= 20 mA	
Locked rotor protection	Auto restart	
Locked rotor current at U_N	I_{block}	
Clock signal at locked rotor	t_3 / t_4 typical: 1,0 s / 3,1 s	



Internal Fuse:
Littlefuse NANO2(R) FUSE; Very fast acting 451 Series; 7 A (Art.-Nr.: 451007)

3.4 Aerodynamics

Measurement conditions:	Measured with a double chamber intake rig acc. to DIN EN ISO 5801. Normal air density = 1,2 kg/m3; Temperature 23°C +/- 3°C; In the intake and outlet area should not be any solid obstruction within 0,5 m. Motor shaft horizontal. The information is only valid under the specified test conditions and may be changed by the installation conditions. If there are deviations from the standard test conditions, the characteristic values must be checked under the installed conditions.

a.) Operation condition:

5.500 1/min at free air flow	U Contr. 10,0 V		

Max. free-air flow (Δp = 0 / $\dot{V}$ = max.)	680,0 m3/h	
Max. static pressure (Δp = max. / $\dot{V}$ =0)	620 Pa	

3.5 Sound Data

Measurement conditions:	Sound pressure level: 1 meter distance between microphone and the air intake. Sound power level: Acc. to DIN 45635 part 38 (ISO 10302) Measured in a semianchoic chamber with a background noise level of Lp(A) < 5 dB(A) For further measurement conditions see chapter aerodynamics.

a.) Operation condition:

5.500 1/min at free air flow	U Contr. 10,0 V		

Optimal operating point	460,0 m3/h @ 233 Pa	
Sound power level at the optimal operating point	8,1 bel(A)	
Sound pressure level at free air flow, measured in rubber bands	70,0 dB(A)	

4 Environment

4.1 General

Min. permitted ambient temperature TU min.	-20 °C	
Max. permitted ambient temperature TU max.	60 °C	
Min. permitted storage temperature TL min.	-40 °C	
Max. permitted storage temperature TL max.	80 °C	

4.2 Climatic Requirements

Humidity requirements	humid heat, constant; according to DIN EN 60068-2-78, 14 days	
Water exposure	None	
Dust requirements	None	
Salt fog requirements	None	

Permitted application area:
The product is intended for use in sheltered rooms with controlled temperature and controlled humidity. Directly exposure to water must be avoided.

Pollution degree 1 (according DIN EN 60664-1)
There is either no pollution or it occurs only dry, non-conductive pollution. The pollution has no negative impact.

Please require severity levels and specification parameters from the responsible development departments.

5 Safety

5.1 Electrical Safety

Dielectric strength DIN EN 60950 (VDE 0805) and DIN EN 60335 (VDE 0700) A.) Type test Measuring conditions: After 48h of storage at 95% R.H. and 25°C. No arcing or breakdown is allowed! All connections together to ground. B.) Routine test Measuring conditions: At indoor climate. No arcing or breakdown is allowed! All connections together to ground.	500 VAC / 1 Min. 850 VDC / 1 Sec.	
Isolation resistance Measuring conditions: After 48h of storage at 95% R.H. and 25°C measured with U=500 VDC for 1 min.	RI > 10 MOhm	
Clearance / creepage distance	1,0 mm / 1,2 mm	
Protection class	III	


5.2 Approval Tests


CE	EC Declaration of Conformity	Yes
EAC	Eurasian Conformity	Yes
UL	Underwriters Laboratories	Yes / UL507, Electric Fans
VDE	Association for Electrical, Electronic and Information Technologies	Yes / Approval acc. to EN 60950 (VDE 0805) - Information technology equipment
CSA	Canadian Standards Association	Yes / C22.2 No. 113 Fans and Ventilators
CCC	China Compulsory Certification	Not applicable


6 Reliability

6.1 General

Life expectancy L10 at TU = 40 °C	65.000 h	
Life expectancy L10 at TU max.	40.000 h	







Anzahl und Länge der Litzen siehe Bv-Bl. 1

Ⓑ 2) nur bei " I " Ausführung
(NTC auf Leiterplatte)

1) Durchmesser für Montagewand
Axialspiel: mit Feder spielfrei verspannt

Toleranzen: Allgemeintoleranzen DIN 7167				
	Datum	Name	DIN ISO 7368-mK-B	Artikel	Halbstab
Bearbeitet			PAPST	Zchg.-Nr.	Blatt
	Index	Ausf.-Nr.	PAPST-MOTOREN GmbH & Co KG D-78112 St.Georgen Germany	Ers./Zchg.	A2
Geprueft u. zur Verwendung freigegeben von		am			

Copies of this document, use of it or its content and the communication of its contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.
Schutzvermerk nach DIN 34 beachten