**K3G400-AH05-64**

# EC centrifugal module

backward-curved, single-intake

with support plate

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **K3G400-AH05-64** |
| **Motor** | **M3G084-DF** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 277 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ml |
| Speed (rpm) | $min^{-1}$ | 1550 |
| Power consumption | W | 275 |
| Current draw | A | 1.4 - 1.0 |
| Min. ambient temperature | °C | 0 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

## Data according to Commission Regulation (EU) 327/2011

| | | Actual | Req. 2015 |
|---|---|---|---|
| 01 Overall efficiency $\eta_{es}$ | % | 58.7 | 45.5 |
| 02 Measurement category | | A | |
| 03 Efficiency category | | Static | |
| 04 Efficiency grade N | | 75.2 | 62 |
| 05 Variable speed drive | | Yes | |

| | | |
|---|---|---|
| 09 Power consumption $P_{ed}$ | kW | 0.27 |
| 09 Air flow $q_v$ | $m^3/h$ | 1605 |
| 09 Pressure increase $p_{fs}$ | Pa | 324 |
| 10 Speed (rpm) n | $min^{-1}$ | 1565 |
| 11 Specific ratio* | | 1.00 |

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

LU-154637

# EC centrifugal module

backward-curved, single-intake

with support plate

## Technical description

| | |
|---|---|
| **Weight** | 8.8 kg |
| **Fan size** | 400 mm |
| **Rotor surface** | Painted black |
| **Electronics housing material** | Die-cast aluminum |
| **Impeller material** | Sheet aluminum |
| **Support plate material** | Sheet aluminum |
| **Spacer material** | Aluminum |
| **Inlet nozzle material** | Sheet aluminum |
| **Number of blades** | 6 |
| **Direction of rotation** | Clockwise, viewed toward rotor |
| **Degree of protection** | IP20 |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | F0 |
| **Max. permitted ambient temp. for motor (transport/storage)** | +80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | -40 °C |
| **Installation position** | Rotor on top |
| **Condensation drainage holes** | None |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Operation and alarm display with LED<br>- Integrated PID controller<br>- LON / RS485 with DCI function<br>- Motor current limitation<br>- PFC, active<br>- Soft start<br>- Control interface with SELV potential safely disconnected from the mains<br>- Thermal overload protection for electronics/motor<br>- Line undervoltage / phase failure detection |
| **EMC immunity to interference** | According to EN 61000-6-2 (industrial environment) |
| **EMC circuit feedback** | According to EN 61000-3-2/3 |
| **EMC interference emission** | According to EN 61000-6-4 (industrial environment) |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | <= 3.5 mA |
| **Electrical hookup** | With plug |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **With cable** | Variable |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 61800-5-1 |
| **Approval** | UL 507; CSA C22.2 No. 113 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support plate

## Product drawing




| | |
|---|---|
| 1 | Terminal box |
| 2 | Connector housing 3-pole GST18/3 Wieland 92.032.9058.1 |
| 2.1 | N |
| 2.2 | PE |
| 2.3 | L |
| 3 | 8-pole socket housing tyco 100616-2 |
| 4 | 8-pole socket housing tyco 100616-2 |
| 5 | Switch, ARCOLECTRIC SWITCHES P L C (no. H8550VBACF) As-delivered condition end customer switch set to "OFF" |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support plate

## Connection diagram




LED1 / LED2

| Status | Priority | Address S/N | Speed | LED red | LED green |
|---|---|---|---|---|---|
| General malfunction | 1 | S/N any | n any | Flashing 1 Hz | OFF |
| Signal function | 2 | S/N <> 1/1 | n any | OFF | Flashing 10 Hz |
| As-delivered condition | 3 | S/N = 1/1 | n > 0 | Always ON | OFF |
| After initializing | 3 | S/N <> 1/1 | n > 0 | OFF | Always ON |
| Fan to speed 0 | 3 | S/N <> 1/1 | n = 0 | OFF | Flashing 1 Hz |
| As-delivered condition | 3 | S/N = 1/1 | n = 0 | Always ON | Flashing 1 Hz |

| No. | Conn. | Designation | Function/assignment |
|---|---|---|---|
| ST1/ST3 | 1 | LON_A | Bus connection RS485, LON_A |
| ST1/ST3 | 2 | LON_B | Bus connection RS485, LON_B |
| ST1/ST3 | 3 | LON_A | Bus connection RS485, LON_A |
| ST1/ST3 | 4 | - | Bridge ST1 – ST3 |
| ST1/ST3 | 5 | - | Bridge ST1 – ST3 |
| ST1/ST3 | 6 | LON_B | Bus connection RS485, LON_B |
| ST1/ST3 | 7 | GND | Reference ground |
| ST1/ST3 | 8 | DCI | Daisy chain signal |
| ST1/ST3 | S | Schirm | Shield for RJ45 CAT5 wire |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC centrifugal module

backward-curved, single-intake

with support plate

## Curves: Air performance 50 Hz




Measurement: LU-154637-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | f | n | $P_{ed}$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 230 | 50 | 1550 | 214 | 0.94 | 2485 | 0 | 1465 | 0.00 |
| 2 | 230 | 50 | 1550 | 261 | 1.14 | 2015 | 200 | 1185 | 0.80 |
| 3 | 230 | 50 | 1550 | 275 | 1.21 | 1540 | 350 | 905 | 1.41 |
| 4 | 230 | 50 | 1550 | 265 | 1.16 | 1045 | 450 | 615 | 1.81 |
| 5 | 230 | 50 | 1300 | 123 | 0.54 | 2065 | 0 | 1215 | 0.00 |
| 6 | 230 | 50 | 1300 | 150 | 0.66 | 1680 | 139 | 990 | 0.56 |
| 7 | 230 | 50 | 1300 | 159 | 0.70 | 1280 | 243 | 755 | 0.98 |
| 8 | 230 | 50 | 1300 | 153 | 0.67 | 870 | 312 | 515 | 1.25 |
| 9 | 230 | 50 | 1050 | 65 | 0.28 | 1670 | 0 | 980 | 0.00 |
| 10 | 230 | 50 | 1050 | 79 | 0.35 | 1355 | 91 | 800 | 0.37 |
| 11 | 230 | 50 | 1050 | 84 | 0.37 | 1035 | 159 | 610 | 0.64 |
| 12 | 230 | 50 | 1050 | 80 | 0.35 | 705 | 203 | 415 | 0.81 |
| 13 | 230 | 50 | 800 | 29 | 0.13 | 1270 | 0 | 750 | 0.00 |
| 14 | 230 | 50 | 800 | 35 | 0.15 | 1035 | 53 | 610 | 0.21 |
| 15 | 230 | 50 | 800 | 37 | 0.16 | 790 | 92 | 465 | 0.37 |
| 16 | 230 | 50 | 800 | 36 | 0.16 | 535 | 118 | 315 | 0.47 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_{ed}$ = Power consumption · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com