**R2E150-AN91-33**

# AC circulation blower for hot air

for solid-fuel heating systems

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **R2E150-AN91-33** |
| **Motor** | **M2E068-BF** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Frequency | Hz | 50 |
| Method of obtaining data | | fa |
| Valid for approval/standard | | CE |
| Speed (rpm) | $min^{-1}$ | 2400 |
| Power consumption | W | 32 |
| Current draw | A | 0.14 |
| Capacitor | µF | 1 |
| Capacitor voltage | VDB | 400 |
| Capacitor standard | | S0 (CE) |
| Min. back pressure | Pa | 0 |
| Min. back pressure | inH2O | 0 |
| Min. ambient temperature | °C | -25 |
| Max. ambient temperature | °C | 80 |
| Starting current | A | 0.2 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# AC circulation blower for hot air

for solid-fuel heating systems

## Technical description

| | |
|---|---|
| **Weight** | 1.8 kg |
| **Fan size** | 150 mm |
| **Rotor surface** | Unpainted |
| **Impeller material** | Sheet steel, stainless |
| **Number of blades** | 6 |
| **Motor suspension** | Motor mounted on support plate for one-sided vibration damping |
| **Direction of rotation** | Counterclockwise, viewed toward rotor |
| **Degree of protection** | IP44; installation- and position-dependent |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | H0 - dry environment |
| **Max. permitted ambient temp. for motor (transport/storage)** | + 80 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | - 40 °C |
| **Installation position** | Any |
| **Condensation drainage holes** | None |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | < 0.75 mA |
| **Motor protection** | Thermal overload protector (TOP) internally connected |
| **With cable** | Lateral |
| **Protection class** | I (with customer connection of protective earth) |
| **Motor capacitor according to EN 60252-1 in safety protection class** | S0 |
| **Conformity with standards** | EN 60335-1; CE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC circulation blower for hot air

for solid-fuel heating systems

## Product drawing




| | |
|---|---|
| 1 | Cable Raychem Spec. 44, AWG24, 3-pole connector housing tyco 1241809-2, 3x plug pin tyco 926885-1 |
| 1.1 | + / red |
| 1.2 | - / black |
| 1.3 | out / white |
| 2 | Cable PVC 4G 0.5 mm² |
| 2.1 | Flat push-on receptacle 6.3 x 0.8 insulated with heat shrink tube |
| 2.2 | Flat push-on receptacle 6.3 x 0.8 with connector housing |
| 2.3 | Flat push-on receptacle 6.3 x 0.8 with connector housing |
| 2.4 | Flat push-on receptacle 6.3 x 0.8 with connector housing |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC circulation blower for hot air

for solid-fuel heating systems

## Connection diagram




| | |
|---|---|
| 1 | Fan connection diagram |
| L | blue |
| N | black |
| PE | green/yellow |
| 2 | Hall IC circuit |
| 2.1 | Hall IC |
| 2.2 | red (+5 V) |
| 2.3 | white (out) |
| 2.4 | black (0 V) |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC circulation blower for hot air

for solid-fuel heating systems

## Curves: Air performance 50 Hz




Measurement: LU-75643-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 230 | 50 | 2400 | 32 | 0.14 | 235 | 0 | 140 | 0.00 |
| 2 | 230 | 50 | 2375 | 32 | 0.14 | 190 | 50 | 110 | 0.20 |
| 3 | 230 | 50 | 2400 | 31 | 0.13 | 145 | 100 | 85 | 0.40 |
| 4 | 230 | 50 | 2500 | 29 | 0.13 | 110 | 150 | 65 | 0.60 |

U = Power supply · f = Frequency · n = Speed (rpm) · $P_e$ = Power consumption · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com