**R2E225-RA92-46**

# AC centrifugal fan - RadiCal

backward curved

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **R2E225-RA92-46** |
| **Motor** | **M2E068-DF** |

| | | | |
|---|---|---|---|
| Phase | | 1~ | 1~ |
| Nominal voltage | VAC | 230 | 230 |
| Frequency | Hz | 50 | 60 |
| Type of data definition | | ml | ml |
| Valid for approval / standard | | CE | CE |
| Speed (rpm) | $min^{-1}$ | 2500 | 2600 |
| Power input | W | 150 | 205 |
| Current draw | A | 0.7 | 0.9 |
| Motor capacitor | µF | 3.5 | 3.5 |
| Capacitor voltage | VDB | 450 | 450 |
| Capacitor standard | | S0 (CE) | S0 (CE) |
| Min. back pressure | Pa | 0 | 0 |
| Min. ambient temperature | °C | -25 | -25 |
| Max. ambient temperature | °C | 65 | 50 |
| Starting current | A | 1.25 | 1.2 |

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

## Data according to ErP directive

| | | Actual | Request 2015 |
|---|---|---|---|
| 01 Overall efficiency $\eta_{es}$ | % | 42.5 | 42.5 |
| 02 Measurement category | | A | |
| 03 Efficiency category | | Static | |
| 04 Efficiency grade N | | 62 | 62 |
| 05 Variable speed drive | | No | |

| | | |
|---|---|---|
| 09 Power input $P_e$ | kW | 0.14 |
| 09 Air flow $q_v$ | $m^3/h$ | 715 |
| 09 Pressure increase $p_{fs}$ | Pa | 301 |
| 10 Speed (rpm) n | $min^{-1}$ | 2540 |
| 11 Specific ratio* | | 1.00 |

Data definition with optimum efficiency.
The ErP data is determined using a motor-impeller combination in a standardised measurement configuration.

* Specific ratio = 1 + $p_{fs}$ / 100 000 Pa

LU-129921

# AC centrifugal fan - RadiCal

backward curved

## Technical features

| | |
|---|---|
| **Mass** | 2.2 kg |
| **Size** | 225 mm |
| **Surface of rotor** | Uncoated |
| **Material of impeller** | PA plastic |
| **Number of blades** | 7 |
| **Direction of rotation** | Clockwise, seen on rotor |
| **Type of protection** | IP 44; Depending on installation and position as per EN 60034-5 |
| **Insulation class** | "F" |
| **Humidity (F)/environmental protection class (H)** | H0 - dry environment |
| **Max. permissible ambient motor temp. (transp./ storage)** | + 80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | - 40 °C |
| **Mounting position** | Any |
| **Condensate discharge holes** | On the stator side |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)** | < 0.75 mA |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Cable exit** | Variable |
| **Protection class** | I (if protective earth is connected by customer) |
| **Product conforming to standard** | EN 60335-1; EN 60335-2-31; CE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan - RadiCal


backward curved

## Product drawing




| | |
|---|---|
| 1 | Accessory part: Inlet nozzle 96358-2-4013, not included in scope of delivery. |
| 2 | Thread reach max. 5 mm |
| 3 | Connection line silicone 4G 0.5 mm², 4x lead tips crimped |

## Connection screen




| | | | | | |
|---|---|---|---|---|---|
| U1 | blue | Z | brown | U2 | black |
| PE | green/yellow | | | | |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan - RadiCal

backward curved

## Charts: Air flow 50 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-129921-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 230 | 50 | 2635 | 131 | 0.57 | 1150 | 0 | 675 | 0.00 |
| 2 | 230 | 50 | 2500 | 150 | 0.70 | 960 | 150 | 565 | 0.60 |
| 3 | 230 | 50 | 2540 | 146 | 0.64 | 710 | 300 | 415 | 1.20 |
| 4 | 230 | 50 | 2605 | 135 | 0.59 | 420 | 400 | 245 | 1.61 |

U = Supply voltage · f = Frequency · n = Speed (rpm) · $P_e$ = Power input · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# AC centrifugal fan - RadiCal

backward curved

## Charts: Air flow 60 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-129925-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | U | f | n | $P_e$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|
| | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | inH2O |
| 1 | 230 | 60 | 2865 | 187 | 0.82 | 1255 | 0 | 735 | 0.00 |
| 2 | 230 | 60 | 2600 | 205 | 0.90 | 1025 | 150 | 605 | 0.60 |
| 3 | 230 | 60 | 2660 | 202 | 0.87 | 700 | 350 | 415 | 1.41 |
| 4 | 230 | 60 | 2780 | 193 | 0.84 | 465 | 450 | 275 | 1.81 |

U = Supply voltage · f = Frequency · n = Speed (rpm) · $P_e$ = Power input · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com