R4E280-AM19-12

AC centrifugal fan

backward curved

ebm-papst Mulfingen GmbH & Co. KG
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

Nominal data

Type	**R4E280-AM19-12**
Motor	**M4E068-CF**

Phase		1~
Nominal voltage	VAC	230
Frequency	Hz	50
Type of data definition		cu
Valid for approval / standard		CE
Speed (rpm)	min^{-1}	850
Power input	W	50
Current draw	A	0.22
Motor capacitor	µF	1.5
Capacitor voltage	VDB	400
Capacitor standard		S2 (CE)
Min. back pressure	Pa	0
Min. ambient temperature	°C	-25
Max. ambient temperature	°C	60
Starting current	A	0.25

ml = Max. load · me = Max. efficiency · fa = Running at free air · cs = Customer specs · cu = Customer unit
Subject to alterations

AC centrifugal fan

backward curved

Technical features


Mass	2.3 kg
Size	280 mm
Surface of rotor	Coated in black
Material of impeller	PA plastic
Number of blades	9
Direction of rotation	Counter-clockwise, seen on rotor
Type of protection	IP 44; Depending on installation and position as per EN 60034-5
Insulation class	"B"
Humidity (F)/environmental protection class (H)	H0+
Max. permissible ambient motor temp. (transp./ storage)	+ 80 °C
Min. permissible ambient motor temp. (transp./storage)	- 40 °C
Mounting position	Shaft horizontal or rotor on bottom; rotor on top on request
Condensate discharge holes	Rotor-side
Operation mode	S1
Motor bearing	Ball bearing
Speed steps	3
Touch current acc. IEC 60990 (measuring network Fig. 4, TN system)	< 0.75 mA
Motor protection	Thermal overload protector (TOP) brought out, basic insulation
Cable exit	Variable
Protection class	I (if protective earth is connected by customer)
Product conforming to standard	EN 60335-1; CE

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

AC centrifugal fan

backward curved

Product drawing




1	Accessory part: Inlet nozzle 31050-2-4013 not included in scope of delivery
2	Thread reach max. 5 mm
3	Connection line ETFE AWG20, 1x connector housing Phönix 6-pin 1757051 (MSTB 2.5/6-ST/5.08)
3.1	Red (capacitor)
3.2	white (level 1)
3.3	grey (level 2)
3.4	black (level 3)
3.5	blue (N)
3.6	orange (bridge)
4	Connection line ETFE AWG20, 1x connector housing Phönix 2-pin 1757019 (MSTB 2.5/2-ST/5.08)
4.1	yellow (TW)
4.2	yellow (TW)
5	Connection line ETFE AWG20, 1x lead tip (green/yellow) crimped
6	Grommet 64901-4-7011 EPDM black

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

AC centrifugal fan

backward curved

Accessory part




Inlet nozzle 31050-2-4013 not included in scope of delivery

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

AC centrifugal fan

backward curved

Connection screen



Note: Fast speed (step III); slow speed (step I)


1	PE (green/yellow)	2	TW (yellow)	3	TW (yellow)
4	Capacitor (red)	5	L= Level 1 (white)	6	L= Level 2 (grey)
7	L= Level 3 (black)	8	L1	9	N (blue)
10	Capacitor (orange)				

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

AC centrifugal fan

backward curved

Charts: Air flow 50 Hz



ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-65843-1
Measurement: LU-65844-1
Measurement: LU-65845-1

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

Measured values

	Stage	U	f	n	P_e	I	LpA_{in}	q_V	q_V	p_{fs}
		V	Hz	min^{-1}	W	A	dB(A)	m^3/h	cfm	inH2O
1	3	230	50	850	50	0.22	44	725	425	0.00
2	2	230	50	610	37	0.17	34	505	295	0.00
3	1	230	50	450	29	0.14	28	350	205	0.00

U = Supply voltage · f = Frequency · n = Speed (rpm) · P_e = Power input · I = Current draw · LpA_{in} = Sound pressure level inlet side · q_V = Air flow

ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com