W6D910-KD01-01/F05
8317078322

AC axial fan - AxiBlade

sickle-shaped blades (S series)

with square full nozzle

ebm-papst Ventilator (Shanghai) Co.,Ltd.
No.418, Hua Jing Road, Wai Gao Qiao Free Trade Zone, Pudong
Tel:+86(021)-50460183
www.ebmpapst.com

Nominal data

Type	**W6D910-KD01-01/F05**
Motor	**M6D138-LA**

Phase		3~	3~
Nominal voltage	VAC	400	400
Wiring		Δ	Y
Frequency	Hz	50	50
Method of obtaining data		ml	ml
Valid for approval/standard		CE	CE
Speed (rpm)	min^{-1}	870	640
Power consumption	W	1920	1170
Current draw	A	3.8	2.2
Max. back pressure	Pa	170	95
Max. back pressure	in. wg	0.68	0.38
Min. ambient temperature	°C	-40	-40
Max. ambient temperature	°C	55	55
Starting current	A	13	4.3

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

Data according to Commission Regulation (EU) 327/2011

		Actual	Req. 2015
01 Overall efficiency η_{es}	%	41.9	35.1
02 Measurement category		A	
03 Efficiency category		Static	
04 Efficiency grade N		46.8	40
05 Variable speed drive		No	

09 Power consumption P_e	kW	1.68
09 Air flow q_v	m^3/h	18355
09 Pressure increase p_{fs}	Pa	139
10 Speed (rpm) n	min^{-1}	900
11 Specific ratio*		1.00

Data obtained at optimum efficiency level.
The ErP data is determined using a motor-impeller combination in a standardized measurement setup.

* Specific ratio = 1 + p_{fs} / 100 000 Pa

LU-192850

ebmpapst

W6D910-KD01-01/F05
8317078322

AC axial fan - AxiBlade

sickle-shaped blades (S series)

with square full nozzle

Technical description


Weight	47.2 kg
Size	910 mm
Motor size	138
Rotor surface	Cast in aluminum
Terminal box material	PP plastic
Blade material	PP plastic
Fan housing material	Sheet steel, galvanized and coated with black plastic (RAL 9005)
Guard grille material	Steel, coated with black plastic (RAL 9005)
Number of blades	5
Blade pitch	0°
Airflow direction	V
Direction of rotation	Clockwise, viewed toward rotor
Degree of protection	IP54
Insulation class	"F"
Moisture (F) / Environmental (H) protection class	H2
Ambient temperature note	Occasional start-up at temperatures between -40°C and -25°C is permitted. For continuous operation at ambient temperatures below -25°C (such as refrigeration applications), use must be made of a fan design with special low-temperature bearings.
Max. permitted ambient temp. for motor (transport/storage)	+80 °C
Min. permitted ambient temp. for motor (transport/storage)	-40 °C
Installation position	Any
Condensation drainage holes	On rotor and stator sides
Mode	S1
Motor bearing	Ball bearing
Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)	<= 3.5 mA
Electrical hookup	Terminal box
Motor protection	Thermal overload protector (TOP) with basic insulation
Protection class	I (with customer connection of protective earth)
Approval	EAC

AC axial fan - AxiBlade

sickle-shaped blades (S series)

with square full nozzle

Product drawing



1	Airflow direction "V"
2	Tightening torque 1.5 ± 0.2 Nm
3	Cable diameter min. 7 mm, max. 14 mm, tightening torque 2 ± 0.3 Nm


ebmpapst

AC axial fan - AxiBlade

sickle-shaped blades (S series)

with square full nozzle

Connection diagram



Δ	Delta connection	Y	Star connection	L1	= U1 = yellow
L2	= V1 = green	L3	= W1 = brown	W2	blue
U2	black	V2	white	TOP	2x gray
PE	green/yellow				

ebmpapst


W6D910-KD01-01/F05
8317078322

AC axial fan - AxiBlade

sickle-shaped blades (S series)

with square full nozzle

Curves: Air performance 50 Hz



ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-192850-1
Measurement: LU-193182-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

Fan performance

	Wired	U	f	n	P_e	I	LpA_{in}	LwA_{in}	LwA_{out}	q_V	p_{fs}	q_V	p_{fs}
		V	Hz	min^{-1}	W	A	dB(A)	dB(A)	dB(A)	m^3/h	Pa	cfm	in. wg
1	Δ	400	50	945	1113	2.82	70	77	77	27765	0	16340	0.00
2	Δ	400	50	925	1349	3.09	68	75	75	24635	56	14500	0.22
3	Δ	400	50	910	1572	3.36	68	75	75	20825	110	12255	0.44
4	Δ	400	50	870	1920	3.80	77	85	85	14840	170	8735	0.68
5	Y	400	50	825	836	1.58	66	74	73	24370	0	14345	0.00
6	Y	400	50	775	970	1.84	63	71	70	20595	39	12120	0.16
7	Y	400	50	730	1064	2.03	61	68	68	16715	71	9840	0.29
8	Y	400	50	640	1170	2.20	69	76	77	11280	98	6640	0.39

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · P_e = Power consumption · I = Current draw · LpA_{in} = Sound pressure level intake side · LwA_{in} = Sound power level intake side
LwA_{out} = Sound power level outlet side · q_V = Air flow · p_{fs} = Pressure increase

ebmpapst