
Copying of this document, and giving it others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.



Steckergehäuse: Molex 22-01-3047
plug housing: Molex 22-01-3047
Kontakt: Molex 08-56-0109
contact: Molex 08-56-0109

Steckerbelegung / PIN configuration
PIN 1 = violett/violet (PWM)
PIN 2 = weiß/white (Tacho)
PIN 3 = rot /red (+)
PIN 4 = blau/blue (-)

1) Maße fuer Montageausschnitt
- Axialspiel: mit Feder spielfrei verspannt

1) measures for mounting cut-out
- without axial clearance by a pre-loaded spring

FR		V5R19	PAPST
SAP Status/State	Aend.-Nr./ Change-No.	CATIA-System-Version/ CATIA-System-Version	CAD-Umgebung/ CAD-Environment

	Datum	Name
Bearb./ Drawn	21.09.2010	HAASA
Gepr./ Checked	27.09.2010	HAASA
Freig./ Releas.	27.09.2010	WEISSERN

Tolerierung / Tolerances: DIN 7167

Allgemeintoleranzen / Gen. Tolerances: DIN ISO 2768-mK-E

ebmpapst

ebm-papst St.Georgen GmbH & Co KG

Werkstoff / Material:

Volumen / Volume (mm^3):

Gewicht / Mass (g):

Artikel / Title:

Axialluefter
axial fan

Zchg.-Nr./ Drawing No: **9693530185**

Ers.f.Zchg. / Replaces:

Dokumenttyp / Type of Document	Teildokument (Blatt/Page)	Index / Index	Format / Size:	Massstab/Scale
C2D	002	-	A3	2:1 1:1

Vertraulich / Confidential Information 02.01.2012