**A3G350-AN01-38**

# EC axial fan - HyBlade

sickle-shaped blades (S series)

**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
Amtsgericht (court of registration) Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **A3G350-AN01-38** |
| **Motor** | **M3G074-CF** |

| | | |
|---|---|---|
| Phase | | 1~ |
| Nominal voltage | VAC | 230 |
| Nominal voltage range | VAC | 200 .. 240 |
| Frequency | Hz | 50/60 |
| Method of obtaining data | | ce |
| Speed (rpm) | $min^{-1}$ | 1350 |
| Power consumption | W | 125 |
| Current draw | A | 1.1 |
| Max. back pressure | Pa | 70 |
| Max. back pressure | in. wg | 0.28 |
| Min. ambient temperature | °C | -40 |
| Max. ambient temperature | °C | 40 |

ml = Max. load · me = Max. efficiency · fa = Free air · cs = Customer specification · ce = Customer equipment
Subject to change

# EC axial fan - HyBlade

sickle-shaped blades (S series)

## Technical description

| | |
|---|---|
| **Weight** | 2.2 kg |
| **Size** | 350 mm |
| **Motor size** | 74 |
| **Rotor surface** | Thick-film passivated |
| **Blade material** | Press-fitted sheet steel blank, sprayed with PP plastic |
| **Number of blades** | 5 |
| **Airflow direction** | V |
| **Direction of rotation** | Counterclockwise, viewed toward rotor |
| **Degree of protection** | IP54 |
| **Insulation class** | "B" |
| **Moisture (F) / Environmental (H) protection class** | H1 |
| **Max. permitted ambient temp. for motor (transport/storage)** | + 70 °C |
| **Min. permitted ambient temp. for motor (transport/storage)** | - 40 °C |
| **Installation position** | Any |
| **Condensation drainage holes** | None, open rotor |
| **Cooling hole/opening** | On rotor side |
| **Mode** | S1 |
| **Motor bearing** | Ball bearing with low-temperature lubricant; (sealed, without air gap) |
| **Technical features** | - Speed setting input (230 V)<br>- Power limiter<br>- Motor current limitation<br>- Soft start<br>- Overvoltage detection<br>- Thermal overload protection for electronics/motor<br>- Line undervoltage detection |
| **Speed levels** | 2 |
| **EMC immunity to interference** | According to EN 61000-6-2 (industrial environment) |
| **EMC interference emission** | According to EN 61000-6-4 (industrial environment) |
| **Touch current according to IEC 60990 (measuring circuit Fig. 4, TN system)** | <= 3.5 mA |
| **Motor protection** | Electronic motor protection |
| **With cable** | Variable |
| **Protection class** | I (with customer connection of protective earth) |
| **Conformity with standards** | EN 60034-1; EN 60204-1; EN 60335-1; CE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

## Product drawing




| | |
|---|---|
| 1 | Airflow direction "V" |
| 2 | Max. clearance for screw 10 mm |
| 3 | Max. clearance for screw 5 mm |
| 4 | Cable PVC 4G 0.5 mm² |
| | 4x flat push-on receptacle 6.3x0.8 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

## Connection diagram




| No. | Conn. | Designation | Color | Function/assignment |
|---|---|---|---|---|
| | CON 10 | L | black | Power supply 230 VAC, 50-60 Hz, see nameplate for voltage range |
| | CON 11 | N | blue | Neutral conductor |
| | CON 12 | PE | green/yellow | Protective earth |
| | CON 70 | SL | brown | Speed selection: switch open speed 1; switch closed speed 2 |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan - HyBlade

sickle-shaped blades (S series)

## Curves: Air performance 50 Hz




ρ = 1.15 kg/m³ ± 2 %

Measurement: LU-198496-1
Measurement: LU-198636-1

Air performance measured according to ISO 5801 installation category A. For detailed information on the measurement setup, contact ebm-papst. Intake sound level: Sound power level according to ISO 13347 / sound pressure level measured at 1 m distance from fan axis. The values given are valid under the specified measuring conditions and may vary due to conditions of installation. For deviations from the standard configuration, the parameters have to be checked on the installed unit.

## Measured values

| | Stage | Wired | U | f | n | $P_{ed}$ | I | $q_V$ | $p_{fs}$ | $q_V$ | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | V | Hz | $min^{-1}$ | W | A | $m^3/h$ | Pa | cfm | in. wg |
| 1 | 1 | 1~ | 230 | 50 | 1350 | 125 | 1.10 | 2315 | 0 | 1360 | 0.00 |
| 2 | 1 | 1~ | 230 | 50 | 1345 | 131 | 1.15 | 1605 | 70 | 945 | 0.28 |
| 3 | 2 | 1~ | 230 | 50 | 1145 | 73 | 0.67 | 1935 | 0 | 1140 | 0.00 |
| 4 | 2 | 1~ | 230 | 50 | 1135 | 78 | 0.71 | 1350 | 50 | 795 | 0.20 |

Wired = Wiring · U = Voltage · f = Frequency · n = Speed (rpm) · $P_{ed}$ = Power consumption · I = Current draw · $q_V$ = Air flow · $p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 (0) 7938 81-0 · Fax +49 (0) 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com