**S1G200-CA91-21**

# EC axial fan

sickled blades (S series)

ESM guard grille



**ebm-papst Mulfingen GmbH & Co. KG**
Bachmühle 2 · D-74673 Mulfingen
Phone +49 7938 81-0
Fax +49 7938 81-110
info1@de.ebmpapst.com
www.ebmpapst.com

Limited partnership · Headquarters Mulfingen
County court Stuttgart · HRA 590344

General partner Elektrobau Mulfingen GmbH · Headquarters Mulfingen
County court Stuttgart · HRB 590142

## Nominal data

| | |
|---|---|
| **Type** | **S1G200-CA91-21** |
| **Motor** | **M1G055-BD** |

| | | | |
|---|---|---|---|
| Phase | | 1~ | 1~ |
| Nominal voltage | VAC | 230 | 230 |
| Frequency | Hz | 50/60 | 50/60 |
| Type of data definition | | ml | - |
| Speed | $min^{-1}$ | 2000 | 1500 |
| Power input | W | 34 | - |
| Current draw | A | 0.26 | |
| Max. back pressure | Pa | 45 | |
| Min. ambient temperature | °C | -30 | -30 |
| Max. ambient temperature | °C | 60 | 60 |

ml = max. load · me = max. efficiency · fa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

# EC axial fan

sickled blades (S series)

ESM guard grille

## Technical features

| | |
|---|---|
| **Mass** | 1 kg |
| **Size** | 200 mm |
| **Material of impeller** | PA plastic |
| **Material of guard grille** | PP plastic |
| **Number of blades** | 5 |
| **Direction of air flow** | "A" |
| **Direction of rotation** | Counter-clockwise, seen on rotor |
| **Type of protection** | IP 54 |
| **Insulation class** | "B" |
| **Humidity class** | F3-1 |
| **Max. permissible ambient motor temp. (transp./ storage)** | + 80 °C |
| **Min. permissible ambient motor temp. (transp./storage)** | - 40 °C |
| **Mounting position** | Any |
| **Condensate discharge holes** | None |
| **Operation mode** | S1 |
| **Motor bearing** | Ball bearing |
| **Technical features** | - Speed selection max/min<br>- Soft start<br>- Over-temperature protected motor |
| **Speed steps** | 2 |
| **EMC interference immunity** | Acc. to EN 61000-6-2 (industrial environment) |
| **EMC harmonics** | Acc. to EN 61000-3-2/3 |
| **EMC interference emission** | Acc. to EN 61000-6-3 (household environment) |
| **Motor protection** | Thermal overload protector (TOP) wired internally |
| **Protection class** | II |
| **Product conforming to standard** | EN 60335-1; CE |
| **Approval** | UL 507; CSA C22.2 Nr.113; VDE |




ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan

sickled blades (S series)


ESM guard grille

## Product drawing




| | |
|---|---|
| 1 | Direction of air flow "A" |

## Connection screen







ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com

# EC axial fan

sickled blades (S series)

ESM guard grille

## Charts: Air flow 50 Hz




Measurement: LU-113009
Measurement: LU-113010

Air performance measured as per ISO 5801 Installation category A. For detailed information on the measuring set-up, please contact ebm-papst. Suction-side noise levels: LwA measured as per ISO 13347 / LpA measured with 1m distance to fan axis. The values given are valid under the measuring conditions mentioned above and may vary according to the actual installation situation. With any deviation from the standard set-up, the specific values have to be checked and reviewed with the unit installed.

## Measured values

| | Stage | U | f | n | $P_{ed}$ | I | $LpA_{in}$ | $LwA_{in}$ | qv | $p_{fs}$ |
|---|---|---|---|---|---|---|---|---|---|---|
| | | V | Hz | $min^{-1}$ | W | A | dB(A) | dB(A) | $m^3/h$ | Pa |
| 1 | 2 | 230 | 50 | 2000 | 32 | 0.24 | 54 | 64 | 735 | 0 |
| 2 | 2 | 230 | 50 | 2000 | 33 | 0.25 | 54 | 64 | 660 | 15 |
| 3 | 2 | 230 | 50 | 2000 | 33 | 0.26 | 53 | 63 | 580 | 30 |
| 4 | 2 | 230 | 50 | 2000 | 34 | 0.26 | 54 | 64 | 485 | 45 |
| 5 | 2 | 230 | 50 | 1500 | 18 | 0.16 | 50 | 59 | 545 | 0 |
| 6 | 2 | 230 | 50 | 1500 | 19 | 0.16 | 50 | 58 | 500 | 9 |
| 7 | 2 | 230 | 50 | 1500 | 19 | 0.16 | 49 | 58 | 445 | 18 |
| 8 | 2 | 230 | 50 | 1500 | 20 | 0.16 | 50 | 59 | 375 | 26 |

U = Supply voltage · f = Frequency · n = Speed · $P_{ed}$ = Power input · I = Current draw · $LpA_{in}$ = Sound pressure level inlet side · $LwA_{in}$ = Sound power level inlet side · qv = Air flow
$p_{fs}$ = Pressure increase



ebm-papst Mulfingen GmbH & Co. KG · Bachmühle 2 · D-74673 Mulfingen · Phone +49 7938 81-0 · Fax +49 7938 81-110 · info1@de.ebmpapst.com · www.ebmpapst.com